







PERSONALIZED CUSTOMER SERVICE

REMPHOS BUILDS STRONG RELATIONSHIPS WITH EXCELLENT CUSTOMER SERVICE AND IMMEDIATE RESPONSE TO ISSUES. WE SUPPORT YOU BEFORE, DURING AND AFTER YOUR PURCHASE.

PROVEN PRODUCT RELIABILITY

REMPHOS APPLIES THE PRINCIPLES OF TRUST, INTEGRITY AND COMMITMENT IN OUR MANUFACTURING, DESIGN AND DEVELOPMENT, RESULTING IN PROVEN TRACK RECORDS AS A SUPPLIER TO THE LARGEST LIGHTING OEMS.

FOCUSED PRODUCT DESIGN

FROM OUR PRODUCT INCEPTION TO YOUR INSTALLATION, OUR GOAL IS TO SAVE OUR CUSTOMERS MONEY. OUR PRODUCTS EXCEED DESIGN AND PERFORMANCE CRITERIA EQUALING COST-EFFECTIVE METHODS TO LIGHTING.

FAST LEAD TIMES

PRODUCT DELIVERY SCHEDULED TO MEET YOUR LEAD TIMES. MOST ITEMS IN STOCK.

CUSTOM ITEMS RECEIVE PRIORITY FROM OUR ENGINEERING AND PRODUCTION TEAMS.



WE ARE STRATEGISTS, ENGINEERS, CREATIVES, SCIENTISTS AND DESIGNERS. WE ARE UNCONVENTIONAL. WE ARE INNOVATIONAL. WE ARE SAVVY. WE ARE REMPHOS. YOU ARE OUR PRIORITY.



David L. Gershaw is an American inventor and entrepreneur. He is the founder of two high-tech design and manufacturing companies. As a high school student, David started his first company designing and producing an LED upgrade for BMW headlights sold through BMW parts catalogs and distributors nationwide. He filed his first patent at 17 and has since authored 9 patents related to LED technology. In 2008 while earning his engineering and business degrees, he launched RemPhos Technologies.

David is determined to have RemPhos reduce America's carbon footprint through lighting alternatives and believes that LED technology is a proven solution. He shares his knowledge as a guest presenter at industry conferences and as an invited student mentor for non-profit and academic presentations.



explore the remphos line of lamps

linear P9, 10 screw base P11





HIGH EFFICACY

Highest in class up to 170LPW.

WARRANTY

5-10 year warranties available.

TOTALtUBE

Plug + Play or Ballast Bypass .

SAFETY

Integrated intelligent switching systems - SMARTSENSE-TLED® + TEMPSENSE®.

THERMAL STABILITY ENVIRONMENTAL PROTECTION

Highly engineered heatsinks and weatherproof protection for outdoor use on our screw in HID replacement lamps.

AND WITHOUT A FLUORESCENT WITH A 7 YEAR WARRANTY.





TOTALtUBE® T8 G2

Ballast compatible + line voltage

SOURCE LED WATTAGE 9-16

LUMENS 1250-2250

VOLTAGE 120-277V AC OR

FL BALLAST

LENGTH (FT) 2, 3, 4, U-BENT ≥138 LPW **EFFICACY**

LIFETIME L70 >100,000 HRS













BCTUBE® T8

Dimming ballast compatible (UL Type A T8)

SOURCE LED WATTAGE 12-14 LUMENS 1680-1860

FL BALLAST VOLTAGE **LENGTH (FT)** 2, 3, 4

EFFICACY ≥130 LPW









EXT DRIVE T8

External driver (UL Type C)

SOURCE LED WATTAGE 9-15*

LUMENS 1080-1740* VOLTAGE 120-277V AC

LENGTH (FT) 2, 3, 4 **EFFICACY** ≥116 LPW

LIFETIME L70 >100,000 HRS



^{*} Lumens and wattage with 1 lamp



TOTALtUBE® T5

Ballast compatible or HE or HO

(UL Type A T5)

SOURCE LED WATTAGE 11-24* LUMENS 1500-3100 FL BALLAST **VOLTAGE LENGTH (FT)** 2, 3, 4 **EFFICACY** ≥125 LPW

LIFETIME L70 >100,000 HRS



^{*} Wattage is bare lamp (not system)



INTDRIVE T5

Line voltage (UL Type B)

SOURCE LED WATTAGE 10-35 LUMENS 1300-4550 **VOLTAGE** 120-277V AC **LENGTH (FT)** 2, 3, 4, 5 **EFFICACY** 130 LPW LIFETIME L70 >100,000 HRS





LEDBIAX

Line voltage (UL Type B)

SOURCE LED WATTAGE 15-20 LUMENS 1500-2000 **VOLTAGE** 120-277V AC **LENGTH (IN)** 16, 22

EFFICACY 100 LPW LIFETIME L70 >100,000 HRS







LEDSS G2

Omnidirectional 360° + uplight

SOURCE LED WATTAGE 15-125 LUMENS 2000-19000 VOLTAGE 120-277V AC HEIGHT (IN) 5.6 - 13.9 **EFFICACY** >130 LPW

L70 >100,000 HRS



LIFETIME





LEDSS H (Horizontal)

Horizontal 180° directional output

SOURCE LED WATTAGE 20-40 3000-6000 LUMENS **VOLTAGE** 120-277V AC HEIGHT (IN) 7.5, 10.3 **EFFICACY** >130 LPW

LIFETIME L70 >100,000 HRS









180° DIRECTIONAL LIGHT OUTPUT. FOR



REFLECTORS AND OPTICS INSIDE

LEDSS G2

Omnidirectional 360°

SOURCE LED WATTAGE 30-50 LUMENS 4000-5600 VOLTAGE 120-277V AC

HEIGHT (IN) 10

EFFICACY >130 LPW










retrofit kits

drum + sconce + vanity P 15 HID + HPS + MH P 16 linear P 17



RETROFIT KITS | drum + sconce + vanity HID + HPS + MH linear



HIGHLY FLEXIBLE FOR CUSTOMIZABLE USE

Each product can be configured at the factory or infield for fit in a wide variety of fixture types and sizes.

EASY TO INSTALL

All mounting hardware included. Installation method optimized for a fast install.

ELIMINATES THE NEED FOR BALLAST AND SOCKETS

Providing a reliable long term install.

OPTIONAL INTEGRATED HIGH/LOW OCCUPANCY AND DAYLIGHT SENSORS

Sensor can read through plastic and glass fixture lenses.

RETROFIT KITS | drum + sconce + vanity

HID + HPS + MH

OUR LEDCR, SR AND VR FEATURE A PATENT-PENDING DESIGN ALLOWING THE LED BOARDS TO BE EASILY ORIENTED ACHIEVING THE DESIRED POSITION TO FIT **FIXTURES OF DIFFERENT SHAPES** AND SIZES. THESE RETROFIT KITS CAN BE PAIRED WITH OUR INTE-**GRATED OCCUPANCY SENSOR** FOR MAXIMUM ENERGY SAVINGS.





Drum and pendant fixture retrofit

SOURCE LED 7-27 WATTAGE LUMENS 900-3000 VOLTAGE 120-277V AC

DIAMETER (IN) 9

EFFICACY >110 LPW

LIFETIME L70 >100,000 HRS











LEDSR

Sconce fixture retrofit

SOURCE LED WATTAGE 7 LUMENS 900 **VOLTAGE** 120-277V AC

SIZE (IN) 6.5×4

EFFICACY 120 LPW

LIFETIME L70 >100,000 HRS





LEDVR

Bathroom vanity fixture retrofit

SOURCE LED 10-12 WATTAGE LUMENS 1200, 1600 **VOLTAGE** 120-277V AC **LENGTH (IN)** 12, 16, 20 **EFFICACY** >120 LPW

LIFETIME L70 >100,000 HRS







EASILY RETROFIT ALMOST ANY VANITY FIXTURE WITH THIS HIGH EFFICIENCY LED KIT. DESIGNED FOR A QUICK INSTALL.

RETROFIT KITS | drum + sconce + vanity HID + HPS + MH

THE LEDSS EXT® COMES WITH A PROPRIETARY ADJUSTABLE **BRACKET SYSTEM FOR EASY** INSTALLATION. ALLOWS THE LIGHT ENGINE TO BE MOUNT-ED TO VIRTUALLY ANY FIXTURE IN EITHER BASE UP OR BASE DOWN ORIENTATION.

INTEGRATED PATENTED OPTICS ON EACH LED DIRECTS LIGHT DOWN TO THE GROUND.





LEDSSEXT

Omnidirectional 360° post-top retrofit kit

SOURCE LED WATTAGE 16, 40 LUMENS 1800-4400 VOLTAGE 120-277V AC

HEIGHT (IN) 3-5

EFFICACY >110 LPW

LIFETIME L70 >100,000 HRS









LEDBLOCK G3

Directional 180° HID retrofit kit

SOURCE LED WATTAGE 30-270 LUMENS 5000-40000 VOLTAGE 120-277V AC SIZE 4.7x5.2 to 10.6x10.5

EFFICACY >160 LPW

LIFETIME L70 >100,000 HRS







OUR FLEXIBLE MOUNTING SYSTEM MAKES THE LEDBLOCK G3 THE PERFECT RETROFIT FOR VARIOUS FIXTURES INCLUDING HIGHBAY, SHOEBOX, WALL PACK AND FLOOD LIGHTING.





LEDBARKITJ

Linear FL fixture retrofit kit

SOURCE WATTAGE LED 10-60

LUMENS

1300-7800

VOLTAGE

120-277V AC

LENGTH (FT) 2, 3, 4

OF LAMPS 1, 2, 3 PER DRIVER

EFFICACY

130 LPW


LIFETIME

L70 >100,000 HRS









RETROFIT KITS | drum + sconce + vanity HID + HPS + MH linear

REMPHOS & THE BMW i3. LIGHTING SMART. DRIVING SMART. COME DRIVE OUR ALL-ELECTRIC BMW i3. THE INSIDE DOOR PANELS ARE MADE OF SWAMP GRASS, THE DASH OF RECYCLED EUCALYPTUS.





indoor + outdoor fixtures

sconce P 21 drum P 22, 23 linear P 24, 25 industrial P 26 garage + canopy P 27 wallmount P 28 special application P 29



FIXTURES | sconce drum

drum linear troffer industrial garage + canopy wallmount special applicatior



FUTURE PROOF YOUR LIGHTING

Many fixtures feature an infield replaceable and upgradeable light engine, such as the LEDCR.

HIGHEST IN-CLASS DELIVERED EFFICIENCY AND FOOT CANDLES

130 LPW LEDCR light engine and proprietary high transmission fixture lenses have 20-50% more light output at same wattage compared to competition.

OPTIONAL INTEGRATED HIGH/LOW OCCUPANCY AND DAYLIGHT SENSORS

Sensor can read through plastic and glass fixture lenses.

AVAILABLE EMERGENCY BATTERY BACKUP

Most fixture styles can include embedded EMG battery backup without the need for increasing fixture height, this means a cleaner, more uniform appearance between fixtures with and without EMG.



DESIGNER SCONCE

Decorative, cost effective fixture

SOURCE LED WATTAGE 7

LUMENS 900

VOLTAGE 120-277V AC


LENGTH (IN) 11

EFFICACY 120 LPW

LIFETIME L70 >100,000 HRS




SCONCE FIXTURE
FEATURES THE
REPLACEABLE LEDSR
LIGHT ENGINE.



FIXTURES | sconce

linear
industrial
garage + canopy
wallmount
special application

IN SEPTEMBER OF 2016 WE BROKE GROUND FOR OUR WORLDWIDE HEADQUARTERS IN MIDDLETON, MASSACHUSETTS.



drum

garage + canopy wallmount special application



UTILITY DRUM

Indoor mushroom style fixture

SOURCE LED WATTAGE 7-27 720-2400 LUMENS

120-277V AC VOLTAGE SIZE (IN) 11, 14

100 LPW **EFFICACY**

LIFETIME L70 >100,000 HRS









DESIGNER DRUM

Decorative, cost effective fixture

SOURCE LED WATTAGE 7-27 **LUMENS** 720-2400 120-277V AC **VOLTAGE** 14, 18 SIZE (IN)

100 LPW **EFFICACY**

L70 >100,000 HRS LIFETIME











ECONOMY DRUM

Contractor grade, cost effective fixture

SOURCE LED WATTAGE 7 720 LUMENS

120-277V AC VOLTAGE

SIZE (IN) 9

EFFICACY 100 LPW

LIFETIME L70 >100,000 HRS









OUTDOOR DRUM

Waterproof and vandal resistant fixture

SOURCE LED WATTAGE 7-27 720-2400 LUMENS **VOLTAGE** 120-277V AC

SIZE (IN) 12 100 LPW **EFFICACY**









TOUGHDRUM®

Waterproof and vandal resistant fixture

SOURCE LED WATTAGE 7-18 LUMENS 720-1760

VOLTAGE 120-277V AC

SIZE (IN) 13 **EFFICACY** 100 LPW

LIFETIME L70 >100,000 HRS











drum

garage + canopy wallmount special application



drum

linear

troffer garage + canopy wallmount special application





LIVC (powered by LED array) Stairwell and corridor fixture

SOURCE LED

WATTAGE 15-25 LUMENS 1800, 2800

VOLTAGE 120-277V AC

LENGTH (FT) 2, 4

EFFICACY >110 LPW

LIFETIME L70 >100,000 HRS





LIVA (powered by LED tubes) Angled lens vanity fixture

SOURCE LED

WATTAGE 8-18 LUMENS

700-1700 **VOLTAGE** 120-277V AC

LENGTH (IN) 18, 24

EFFICACY 130 LPW





linear

troffer

garage + canopy

wallmount





LIVB (powered by LED tubes)

Cube profile vanity and common area fixture

SOURCE WATTAGE LED 8-18

LUMENS 700-1700 120-277V AC

VOLTAGE LENGTH (IN)

18, 24

130 LPW **EFFICACY**

LIFETIME L70 >100,000 HRS





LIVH (powered by LED array)

Compact, cost effective strip fixture

SOURCE

WATTAGE

40-60 5400, 8400

LED

LUMENS 120-277V AC **VOLTAGE**

LENGTH (FT) 4,8 **EFFICACY**

>130 LPW

LIFETIME L70 >100,000 HRS









LIV WRAP (powered by LED tubes)

Highest efficiency LED wrap on the market

SOURCE

LED 18-24

WATTAGE 1800-2400 LUMENS

120-277V AC VOLTAGE

LENGTH (FT) 2, 4

EFFICACY 100 LPW

LIFETIME L70 >100,000 HRS





LIV MODERN (powered by LED array)

Decorative vanity fixture

SOURCE LED

18-24 WATTAGE 1800-2400 LUMENS

VOLTAGE 120-277V AC

LENGTH (FT) 2, 3, 4 130 LPW **EFFICACY**



troffer

garage + canopy

wallmount

special application



•

LED PANEL

Sophisticated LED PANEL w/ controls

SOURCE

LED 25-48

WATTAGE

3250-6240 LUMENS

VOLTAGE 120-277V AC **LENGTH (FT)** 1x4, 2x2, 2x4

EFFICACY >130 LPW









troffer industrial

garage + canopy wallmount special application



HIGHBAY CIRCULAR

Traditional circular appearance

SOURCE LED 100-200 WATTAGE 11000-21800 LUMENS **VOLTAGE** 120-277V AC

DIAMETER (IN) 12

EFFICACY >130 LPW

LIFETIME L70 >100,000 HRS







HIGHBAY LINEAR

Modern linear appearance

SOURCE LED WATTAGE 110-325 14300-42250 LUMENS 120-277V AC VOLTAGE

LENGTH (FT) 2, 4

>130 LPW **EFFICACY**

LIFETIME L70 >100,000 HRS







LEDVT

Vapor tight fixture with stainless steel hardware and hi/lo OCC sensor

SOURCE LED 40 WATTAGE LUMENS 4000

120-277V AC VOLTAGE

LENGTH (FT) 4

EFFICACY >100 LPW









troffer

garage + canopy

wallmount

special application



LEDCF

Rugged canopy fixture for surface or pendant mount

SOURCE LED WATTAGE 30-50

LUMENS 3000-5800 VOLTAGE 120-277V AC

LENGTH (IN) 10x10 **EFFICACY** >100 LPW

LIFETIME L70 >100.000 HRS









OUTDOOR DRUM

Waterproof and vandal resistant fixture

SOURCE LED WATTAGE 7-27 LUMENS 720-2400 **VOLTAGE** 120-277V AC

LENGTH (IN) 12

110 LPW **EFFICACY**

LIFETIME L70 >100,000 HRS













TOUGHDRUM®

Waterproof and vandal resistant fixture

SOURCE LED WATTAGE 12-20 720-1760 LUMENS **VOLTAGE** 120-277V AC

LENGTH (IN) 13 110 LPW **EFFICACY**

LIFETIME L70 >100,000 HRS









LEDVT

Compact vapor tight with integrated hi/lo OCC sensor

SOURCE LED 40 WATTAGE LUMENS 4000

VOLTAGE 120-277V AC


LENGTH (FT) 4

EFFICACY >100 LPW









ELEGANT, ENERGY EFFICIENT
AND SUPER BRIGHT LED WALL
PACK FOR OUTDOOR USE.
MULTIPLE MODELS AVAILABLE.
REPLACES UP TO A 250W HID.
OUR WALL PACK FEATURES AN
ADJUSTABLE HEAD ALLOWING
FLEXIBLE LIGHT OUTPUT DIRECTIO



WMBG2

Waterproof flex-mount wall-pack

 SOURCE
 LED

 WATTAGE
 20-70

 LUMENS
 2000-7500

 VOLTAGE
 120-277V AC

 SIZE (IN)
 9, 13

EFFICACY >100 LPW

LIFETIME L70 >100,000 HRS





FIXTURES sconce

drum linear troffer industrial garage + canopy

wallmount special application

troffer garage + canopy wallmount special application





LEDSB

Automotive spray booth fixture replacement

SOURCE LED WATTAGE 200 LUMENS 22000 VOLTAGE 120-277V AC SIZE

24x24 **EFFICACY** 120 LPW

LIFETIME L70 >100,000 HRS





MERLIN X1

Energy Efficient Desk Lamp

SOURCE LED WATTAGE 9

450 LUMENS

VOLTAGE 120-277V AC SIZE (IN) 4.7x5.5x14.2 50 LPW **EFFICACY**

LIFETIME L70 >35,000 HRS











LIGHTING THE DARKNESS IN AFRICA. REMPHOS ALONG WITH OUR PARTNER AEG HAVE DEVELOPED AND ARE MANUFACTURING A COMPLETELY OFF-THE-GRID LED LIGHTING SYSTEM FOR RURAL AFRICA. IT IS INEXPENSIVE AND EASY TO INSTALL AND USE.





DO YOU HAVE A PROJECT WE CAN HELP YOU WITH? PLEASE DON'T HESITATE TO REACH OUT TO US

^{*} Specifications are subject to change without notice. Where DLC logo is displayed all or select models may be qualified, see product cut sheet for more information.