




## Compact Industrial Power Supplies

Single and Three Phase  
 DIN rail mountable  
 Short circuit protection  
 Internal input filter  
 Wide input voltage range  
 Power Factor Correction  
 Parallel operation/Redundant  
 High efficiency  
 Adjustable output voltage  
 RoHS compliant

# Reaching new heights in automation



## Contents:

- |                                |              |
|--------------------------------|--------------|
| 1. Overview Power Supplies     | page 4       |
| 2. Power Supplies              | page 5 - 20  |
| 3. Current Control System LCCS | page 21 - 23 |

# Welcome to the Lutze Group


Machine and System Installation Technology

1



LSC Wiring System

2



Suppression Technology, Interface, Conversion Technology and Power Supplies

3



Rail Technology and Automation

4



We have been developing and manufacturing electronic and electrical engineering solutions for controls and installations for more than 45 years.

Our basic concept as system suppliers, providing a comprehensive and well-matched product range with which we can generate innovative and customized solutions for our customers, has stood the test of time.

The close relationship between product development and customer requirements allows Lutze continuously to improve and develop our products for the various markets.

Lutze systems comply with the highest industrial standards; Lutze solutions mean improvement and innovation.

**Our four product groups include components and concepts suitable for almost any control application. For more information on our products, please visit [www.lutze.com](http://www.lutze.com).**

## Power Supplies • Overview



60W - 360W



10W - 18W



**30W, 60W**



120W



240W



480W, 960W

### **DC voltage supply, regulated**

Rated power (W)		Input		Output (V)							Part-No.	Type	Page	
		AC 90-265 V	AC 170 - 364 V	5V	12V	15V	24V	48V	Screw terminal pluggable	Screw terminal	Spring terminal			
●	10 W			2A					●			728761	DRA10-05A	5
●	15 W			0,84A					●			728766	DRA10-12A	5
●	18 W			2A					●			722761	DRA10-5	6
●	30 W			0,84A					●			722766	DRA10-12	6
●	50 W			0,67A					●			722773	DRA10-15	6
●	60 W			0,42A					●			722751	DRA10-24	6
●	120 W			3A					●			722762	DRA18-5	7
●	240 W			3A					●			728762	DRA18-5A	7
●	480 W			1,5A					●			722767	DRA18-12	8
●	960 W			1,2A					●			722774	DRA18-15	8
●				0,75A					●			722752	DRA18-24	8
●				6A					●			722763	DRA30-5A	9
●				2,5A					●			722768	DRA30-12A	9
●				1,25A					●			722753	DRA30-24A	9
●				0,63A					●			722775	DRA30-48A	9
●				6A					●			728763	DRA30-5	10
●				2,5A					●			728768	DRA30-12	10
●				1,25A					●			728753	DRA30-24	10
●				0,63A					●			728775	DRA30-48	10
●		●	●	2A	2A	2A			●			716213	NGP 24/2-6213	19
●			●	10A					●			722764	DRA60-5A	11
●			●	10A					●			728764	DRA60-5	11
●		●	●	5A					●			728769	DRA60-12	12
●			●	2,5A					●			728754	DRA60-24	12
●			●	1,25A					●			728776	DRA60-48	12
●			●	5A					●			722769	DRA60-12A	13
●			●	2,5A					●			722754	DRA60-24A	13
●			●	1,25A					●			722776	DRA60-48A	13
●		●	●	10A					●			722770	DRA120-12FPB	14
●			●	5A					●			722758	DRA120-24FPB	14
●		●	●	2,5A					●			722777	DRA120-48FPB	14
●			●	10A					●			722759	DRA240-24B	15
●		●	●	5A					●			722778	DRA240-48B	15
●			●	10A					●			722781	DRA240-24A	15
●		●	●	20A					●			728782	DRA480-24	16
●			●	20A					●			722782	DRA480-24	16
●		●	●	10A					●			722779	DRA480-48	16
●			●	20A					●			722805	WRA 480-24	17
●		●	●	10A					●			722809	WRA 480-48	17
●			●	40A					●			722806	WRA 960-24	18
●		●	●	20A					●			722810	WRA 960-48	18

### DC voltage supply, unregulated

DC Voltage Supply, unregulated										Part-No.	Type	Page
Rated power (W)		Input			Output (V)							
●	60 W	●	●	AC 115 V (AC 104 - 196 V)		5 V	2,5A	●	722962	NG24/2,5-2962	20	
●	120 W	●	●	AC 230 V (AC 207 - 244 V)		12 V	5A	●	722963	NG24/5-2963	20	
●	240 W	●	●	AC 400 V (AC 360 - 424 V)		15 V	10A	●	722972	NG24/10-2972	20	
●	360 W	●	●			24 V	10A	●	722973	NG24/15-2973	20	
						48 V		Spring terminal				

# Power supply · regulated, 10 W


**Primary switchmode power supply, Single-phase, Class 2**

**Input: Wide range input AC 90 V - 265V; DC 120 V - 370 V**

**Output: 5 V / 12 V - adjustable**




## Dimensions




## PIN assignment

1	V+	Positive output
2	V-	Negative output
3	↓	Ground this to minimize high-frequency emissions
4	N	Input
5	L	Input

## Derating



## Parallel mode



Description	Part-No.	Type	PU	
<b>Screw terminal</b>				
Output voltage/current	DC 5 V; 2 A DC 12 V; 0.84 A	728761 728766	DRA 10-05 DRA 10-12	1 1
<b>Input</b>	<b>DRA 10-05</b>	<b>DRA 10-12</b>		
Voltage	AC 100–240 V			
Operation voltage range	AC 90–265 V / DC 120–370 V			
Line frequency	47 – 63 Hz			
Rated current	$V_{in} = 115 \text{ V}$ ; AC: 120 mA / $V_{in} = 230 \text{ V}$ ; AC: 70 mA			
Inrush current	$V_{in} = 115 \text{ V}$ ; AC: 10 A / $V_{in} = 230 \text{ V}$ ; AC: 18 mA			
Input fuse	T2A / AC 250 V internal			
Power Factor Correction P.F.C.	–			
<b>Output</b>				
Rated voltage output	DC 5 V	DC 12 V		
Rated current output	2 A	0.84 A		
Voltage trim range	4.5–5.75 V	10.8–13.8 V		
Accuracy	±1 %			
Line regulation	±1 %			
Load regulation	±2 %			
Transient recovery time	300 µs			
Temperature coefficient	±0.02 % / °C			
Ripple & Noise	50 mV			
Hold up time	$V_{in} = 115 \text{ V}$ : 25 ms / $V_{in} = 230 \text{ V}$ : 100 ms			
Status indication DC ON (LED green)	≥4.5 V	≥10.8 V		
Status indication DC LOW (LED red)	<3.75–4.50 V	<9–10.8 V		
Parallel mode	with external diodes			
Efficiency	73 %	75 %		
Rated over load protection	110–135 %			
Over voltage protection	125–145 %			
Short circuit characteristics	Hiccup-mode			
<b>General</b>				
Switching frequency	min. 100 kHz			
Isolation voltage input/output	3 kVeff			
Isolation resistance at DC 500 V	100 MΩ			
Operation temperature range	-10°C – 70°C (Derating)			
Derating	-3% / °C starting at 61°C			
Storage temperature range	-25 °C – 85 °C			
M.T.B.F.	210000 h			
Relative humidity	20–95 % RH			
Dimensions	22.5 × 90.0 × 115.0 mm			
Cooling	Air convection			
Housing material	Plastic			
Field installation	rail TS 35 (EN 50022)			
Installation position	vertical			
IP rating	IP 20			
Protection class	2			
Weight (per unit)	0.12 kg / 0.265 lbs			
Termination	Screw terminal: 0.2–2.0 mm²			
Approvals	UL: UL 508 listed cUL: UL 60950-1, UL 1310 Class 2 TÜV: EN 60950-1 CE: EN 50081-1 / EN 55022 Class B, EN 6100-3-2, EN 601000-3-3, EN 50082-1 / EN 55024			
<b>Monitoring</b>				
DC ON Control (Rdy)	LED green/red			
Switching voltage	–			
Switching current	–			
Switching capacity	–			
Isolation voltage	–			

# Power supply · regulated, 10 W


**Primary switchmode power supply, Single-phase, Class 2**

**Input: Wide range input AC 90 V - 265 V; DC 120 V - 370 V**

**Output: 5 V / 12 V / 15 V / 24 V - adjustable**




## Dimensions




## PIN assignment

1	V+	Positive output
2	V-	Negative output
3	↓	Ground this to minimize high-frequency emissions
4	N	Input
5	L	Input

## Derating



## Parallel mode



Description	Part-No.	Type	PU
<b>Spring terminal</b>			
Output voltage/current	DC 5 V; 2 A	DRA 10-05	1
	DC 12 V; 0.84 A	DRA 10-12	1
	DC 15 V; 0.67 A	DRA 10-15	1
	DC 24 V; 0.42 A	DRA 10-24	1
<b>Input</b>			
Voltage	DRA 10-05	DRA 10-12	DRA 10-15
		AC 100–240 V	
Operation voltage range		AC 90–265 V / DC 120–370 V	
Line frequency		47 – 63 Hz	
Rated current	$V_{in}= 115 \text{ V}$ ; AC: 120 mA / $V_{in}= 230 \text{ V}$ ; AC: 70 mA		
Inrush current	$V_{in}= 115 \text{ V}$ ; AC: 10 A / $V_{in}= 230 \text{ V}$ ; AC: 18 mA		
Input fuse		T2A / AC 250 V internal	
Power Factor Correction P.F.C.			
<b>Output</b>			
Rated voltage output	DC 5 V	DC 12 V	DC 15 V
	2 A	0.84 A	0.67 A
		0.42 A	
Voltage trim range	4.5–5.75 V	10.8–13.8 V	13.5–17.25 V
Accuracy		±1 %	
Line regulation		±1 %	
Load regulation		±2 %	
Transient recovery time		300 µs	
Temperature coefficient		±0.02 % / °C	
Ripple & Noise		50 mV	
Hold up time	$V_{in}= 115 \text{ V}$ : 25 ms / $V_{in}= 230 \text{ V}$ : 100 ms		
Status indication DC ON (LED green)	$\geq 4.5 \text{ V}$	$\geq 10.8 \text{ V}$	$\geq 13.5 \text{ V}$
Status indication DC LOW (LED red)	<3.75–4.50 V	<9–10.8 V	<11.25–13.5 V
Parallel mode	with external diodes		
Efficiency	73 %	75 %	76 %
Rated over load protection		110–135 %	
Over voltage protection		125–145 %	
Short circuit characteristics		Hiccup-mode	
<b>General</b>			
Switching frequency		min. 100 kHz	
Isolation voltage input/output		3 kVeff	
Isolation resistance at DC 500 V		100 MΩ	
Operation temperature range		-10°C – 70°C (Derating)	
Derating		-3% / °C starting at 61°C	
Storage temperature range		-25 °C – 85 °C	
M.T.B.F.		210000 h	
Relative humidity		20–95 % RH	
Dimensions		22.5 × 90.0 × 115.0 mm	
Cooling		Air convection	
Housing material		Plastic	
Field installation		rail TS 35 (EN 50022)	
Installation position		vertical	
IP rating		IP 20	
Protection class		2	
Weight (per unit)		0,12 kg / 0.265 lbs	
Termination		Spring terminal: 0.2–2.0 mm²	
Approvals			
		UL: UL 508 listed	
		cUL: UL 60950-1, UL 1310 Class 2	
		TÜV: EN 60950-1	
		CE: EN 50081-1 / EN 55022 Class B, EN 6100-3-2, EN 601000-3-3, EN 50082-1 / EN 55024	
<b>Monitoring</b>			
DC ON Control (Rdy)		LED green/red	
Switching voltage		–	
Switching current		–	
Switching capacity		–	
Isolation voltage		–	

# Power supply · regulated, 15 W


## Primary switchmode power supply, Single-phase, Class 2

**Input:** Wide range input AC 90 V - 265 V; DC 120 V - 370 V

**Output:** 5 V - adjustable




### Dimensions




### PIN assignment

1	V+	Positive output
2	V-	Negative output
3	↓	Ground this to minimize high-frequency emissions
4	N	Input
5	L	Input

### Derating



### Parallel mode



Description	Part-No.	Type	PU
<b>Screw terminal</b> Output voltage/current	DC 5 V; 3 A	DRA 18-05A	1
<b>Spring terminal</b> Output voltage/current	DC 5 V; 3 A	DRA 18-05	1
<b>Input</b>	<b>DRA 18-05A</b>	<b>DRA 18-05</b>	
Voltage	AC 100–240 V		
Operation voltage range	AC 90–265 V / DC 120–370 V		
Line frequency	47 – 63 Hz		
Rated current	$V_{in} = 115 \text{ V}$ ; AC: 170 mA / $V_{in} = 230 \text{ V}$ ; AC: 90 mA		
Inrush current	$V_{in} = 115 \text{ V}$ ; AC: 10 A / $V_{in} = 230 \text{ V}$ ; AC: 18 mA		
Input fuse	T2A / AC 250 V internal		
Power Factor Correction P.F.C.	–		
<b>Output</b>			
Rated voltage output	DC 5 V		
Rated current output	3 A		
Voltage trim range	4.5–5.75 V		
Accuracy	±1 %		
Line regulation	±1 %		
Load regulation	±2 %		
Transient recovery time	300 µs		
Temperature coefficient	±0.02 % / °C		
Ripple & Noise	50 mV		
Hold up time	$V_{in} = 115 \text{ V}$ : 25 ms / $V_{in} = 230 \text{ V}$ : 75 ms		
Status indication DC ON (LED green)	≥4.5 V		
Status indication DC LOW (LED red)	<3.75–4.50 V		
Parallel mode	with external diodes		
Efficiency	77 %		
Rated over load protection	110–135 %		
Over voltage protection	125–145 %		
Short circuit characteristics	Hiccup-mode		
<b>General</b>			
Switching frequency	min. 100 kHz		
Isolation voltage input/output	3 kVeff		
Isolation resistance at DC 500 V	100 MΩ		
Operation temperature range	-10°C – 70°C (Derating)		
Derating	-3% / °C starting at 61 °C		
Storage temperature range	-25 °C – 85 °C		
M.T.B.F.	210000 h		
Relative humidity	20–95 % RH		
Dimensions	22.5 × 90.0 × 115.0 mm		
Cooling	Air convection		
Housing material	Plastic		
Field installation	rail TS 35 (EN 50022)		
Installation position	vertical		
IP rating	IP 20		
Protection class	2		
Weight (per unit)	0,15 kg / 0.331 lbs		
Termination	Screw terminal: 0.2–2.0 mm² Spring terminal: 0.2–2.0 mm²		
Approvals	UL: UL 508 listed cUL: UL 60950-1, UL 1310 Class 2 TÜV: EN 60950-1		
CE: EN 50081-1 / EN 55022 Class B, EN 61000-3-2, EN 601000-3-3, EN 50082-1 / EN 55024			
<b>Monitoring</b>			
DC ON Control (Rdy)	LED green/red		
Switching voltage	–		
Switching current	–		
Switching capacity	–		
Isolation voltage	–		

# Power supply · regulated, 18 W


## Primary switchmode power supply, Single-phase, Class 2

**Input:** Wide range input AC 90 V - 265 V; DC 120 V - 370 V

**Output:** 12 V / 15 V / 24 V - adjustable




### Dimensions




### PIN assignment

1	V+	Positive output
2	V-	Negative output
3	↓	Ground this to minimize high-frequency emissions
4	N	Input
5	L	Input

### Derating



### Parallel mode



Description	Part-No.	Type	PU
<b>Spring terminal</b>			
Output voltage/current	DC 12 V; 1.5 A	DRA 18-12	1
	DC 15 V; 1.2 A	DRA 18-15	1
	DC 24 V; 0.75 A	DRA 18-24	1
<b>Input</b>			
Voltage	DRA 18-12	DRA 18-15	DRA 18-24
Operation voltage range	AC 90–265 V / DC 120–370 V	AC 100–240 V	
Line frequency	47 – 63 Hz		
Rated current	$V_{in} = 115 \text{ V}$ ; AC: 200 mA / $V_{in} = 230 \text{ V}$ ; AC: 110 mA		
Inrush current	$V_{in} = 115 \text{ V}$ ; AC: 10 A / $V_{in} = 230 \text{ V}$ ; AC: 18 mA		
Input fuse	T2A / AC 250 V internal		
<b>Power Factor Correction P.F.C.</b>			
<b>Output</b>			
Rated voltage output	DC 12 V	DC 15 V	DC 24 V
Rated current output	1.5 A	1.2 A	0.75 A
Voltage trim range	10.8–13.8 V	13.5–17.25 V	21.6–28.8 V
Accuracy	±1 %		
Line regulation	±1 %		
Load regulation	±2 %		
Transient recovery time	300 µs		
Temperature coefficient	±0.02 % / °C		
Ripple & Noise	50 mV		
Hold up time	$V_{in} = 115 \text{ V}$ : 25 ms / $V_{in} = 230 \text{ V}$ : 75 ms		
Status indication DC ON (LED green)	≥10.8 V	≥13.5 V	≥21.6 V
Status indication DC LOW (LED red)	<9–10.8 V	<11.25–13.5 V	<18–21.6 V
Parallel mode	with external diodes		
Efficiency	77 %		
Rated over load protection	110–135 %		
Over voltage protection	125–145 %		
Short circuit characteristics	Hiccup-mode		
<b>General</b>			
Switching frequency	min. 100 kHz		
Isolation voltage input/output	3 kVeff		
Isolation resistance at DC 500 V	100 MΩ		
Operation temperature range	-10°C – 70°C (Derating)		
Derating	-3% / °C starting at 61 °C		
Storage temperature range	-25 °C – 85 °C		
M.T.B.F.	210000 h		
Relative humidity	20–95 % RH		
Dimensions	22.5 × 90.0 × 115.0 mm		
Cooling	Air convection		
Housing material	Plastic		
Field installation	rail TS 35 (EN 50022)		
Installation position	vertical		
IP rating	IP 20		
Protection class	2		
Weight (per unit)	0,15 kg / 0.331 lbs		
Termination	Spring terminal: 0.2–2.0 mm²		
Approvals	UL: UL 508 listed cUL: UL 60950-1, UL 1310 Class 2 TÜV: EN 60950-1		
CE: EN 50081-1 / EN 55022 Class B, EN 6100-3-2, EN 60100-3-3, EN 50082-1 / EN 55024			
<b>Monitoring</b>			
DC ON Control (Rdy)	LED green/red		
Switching voltage	–		
Switching current	–		
Switching capacity	–		
Isolation voltage	–		

# Power supply · regulated, 30 W


**Primary switchmode power supply, Single-phase, Class 2**

**Input: Wide range input AC 85 V - 264 V; DC 90 V - 375 V**

**Output: 5 V / 12 V / 24 V / 48 V - adjustable**




## Dimensions




## PIN assignment

1 RDY	DC OK output for relay
2 +	Positive output
3 +	Positive output
4 -	Negative output
5 -	Negative output
6 ↓	Ground this to minimize high-frequency emissions
7 N	Input: neutral conductor
8 L	Input: phase conductor

## Derating



## Parallel mode



Description	Part-No.	Type	PU
<b>Screw terminal</b>			
Output voltage/current	DC 5 V; 6 A	DRA 30-05	1
	DC 12 V; 2.5 A	DRA 30-12	1
	DC 24 V; 1.25 A	DRA 30-24	1
	DC 48 V; 0.625 A	DRA 30-48	1
<b>Input</b>			
Voltage	DRA 30-05	DRA 30-12	DRA 30-24
		AC 100–240 V	DRA 30-48
Operation voltage range		AC 85–264 V / DC 90–375 V	
Line frequency		47 – 63 Hz	
Rated current	$V_{in} = 115 \text{ V}$ ; AC: 360 mA / $V_{in} = 230 \text{ V}$ ; AC: 190 mA		
Inrush current	$V_{in} = 115 \text{ V}$ ; AC: 20 A / $V_{in} = 230 \text{ V}$ ; AC: 40 mA		
Input fuse		T2A / AC 250 V internal	
Power Factor Correction P.F.C.			
<b>Output</b>			
Rated voltage output	DC 5 V	DC 12 V	DC 24 V
	6 A	2.5 A	1.25 A
Voltage trim range	5–5.5 V	12–14 V	24–28 V
Accuracy		±1 %	
Line regulation		±0.5 %	
Load regulation		±0.5 %	
Transient recovery time		1.0 ms	
Temperature coefficient		±0.02 % / °C	
Ripple & Noise		50 mV	
Hold up time	$V_{in} = 115 \text{ V}$ : 20 ms / $V_{in} = 230 \text{ V}$ : 30 ms		
Status indication DC ON (LED green)	$\geq 4 \text{ V}$	$\geq 9.6 \text{ V}$	$\geq 19.2 \text{ V}$
Status indication DC LOW (LED red)			–
Parallel mode		with external diodes	
Efficiency	79 %	84 %	86 %
Rated over load protection	120 – 136 %		110 – 140 %
Over voltage protection		125–137 %	
Short circuit characteristics		Hiccup-mode	
<b>General</b>			
Switching frequency		min. 100 kHz	
Isolation voltage input/output		3 kVeff	
Isolation resistance at DC 500 V		100 MΩ	
Operation temperature range		-10°C – 70°C (Derating)	
Derating		-2.5% / °C starting at 61 °C	
Storage temperature range		-25 °C – 85 °C	
M.T.B.F.		210000 h	
Relative humidity		20–90% RH	
Dimensions	40.5 × 90.0 × 115.0 mm		
Cooling		Air convection	
Housing material		Plastic	
Field installation		rail TS 35 (EN 50022)	
Installation position		vertical	
IP rating		IP 20	
Protection class	–	2	
Weight (per unit)		0.29 kg / 0.639 lbs	
Termination		Screw terminal: 0.2–2.0 mm²	
Approvals	UL: UL 508 listed; cUL: UL 60950-1, UL 1310 Class 2; TÜV: EN 60950-1; CE: EN 61000-6-3 / EN 55022 Class B, EN 6100-3-2, EN 601000-3-3, EN 55024, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 6100-4-6, EN 61000-4-8, EN 61000-4-11		
Monitoring			
DC ON Control (Rdy)	–	Open Collector	–
Switching voltage	–	DC 24 V	–
Switching current	–	≤ 35 mA	–
Switching capacity	–	–	–
Isolation voltage	–	none	–

# Power supply · regulated, 30 W


**Primary switchmode power supply, Single-phase, Class 2**

**Input: Wide range input AC 85 V - 264 V; DC 90 V - 375 V**

**Output: 5 V / 12 V / 24 V / 48 V - adjustable**




## Dimensions




## PIN assignment

1 RDY	DC OK output for relay
2 +	Positive output
3 +	Positive output
4 -	Negative output
5 -	Negative output
6 ↓	Ground this to minimize high-frequency emissions
7 N	Input: neutral conductor
8 L	Input: phase conductor

## Derating



## Parallel mode



Description	Part-No.	Type	PU
<b>Spring terminal</b>			
Output voltage/current	DC 5 V; 6 A	DRA 30-05	1
	DC 12 V; 2.5 A	DRA 30-12	1
	DC 24 V; 1.25 A	DRA 30-24	1
	DC 48 V; 0.625 A	DRA 30-48	1
<b>Input</b>			
Voltage	DRA 30-05	DRA 30-12	DRA 30-24
		AC 100–240 V	DRA 30-48
Operation voltage range		AC 85–264 V / DC 90–375 V	
Line frequency		47 – 63 Hz	
Rated current	$V_{in} = 115 \text{ V}$ ; AC: 360 mA / $V_{in} = 230 \text{ V}$ ; AC: 190 mA		
Inrush current	$V_{in} = 115 \text{ V}$ ; AC: 20 A / $V_{in} = 230 \text{ V}$ ; AC: 40 mA		
Input fuse		T2A / AC 250 V internal	
Power Factor Correction P.F.C.			
<b>Output</b>			
Rated voltage output	DC 5 V	DC 12 V	DC 24 V
Rated current output	6 A	2.5 A	1.25 A
Voltage trim range	5–5.5 V	12–14 V	24–28 V
Accuracy		±1 %	
Line regulation		±0.5 %	
Load regulation		±0.5 %	
Transient recovery time		1.0 ms	
Temperature coefficient		±0.02 % / °C	
Ripple & Noise		50 mV	
Hold up time	$V_{in} = 115 \text{ V}$ : 20 ms / $V_{in} = 230 \text{ V}$ : 30 ms		
Status indication DC ON (LED green)	$\geq 4 \text{ V}$	$\geq 9.6 \text{ V}$	$\geq 19.2 \text{ V}$
Status indication DC LOW (LED red)			–
Parallel mode		with external diodes	
Efficiency	79 %	84 %	86 %
Rated over load protection		110–140 %	
Over voltage protection	120–136 %	125–137 %	
Short circuit characteristics		Hiccup-mode	
<b>General</b>			
Switching frequency		min. 100 kHz	
Isolation voltage input/output		3 kVeff	
Isolation resistance at DC 500 V		100 MΩ	
Operation temperature range		-10°C – 70°C (Derating)	
Derating		-2.5% / °C starting at 61 °C	
Storage temperature range		-25 °C – 85 °C	
M.T.B.F.		210000 h	
Relative humidity		20–90% RH	
Dimensions	40.5 × 90.0 × 115.0 mm		
Cooling		Air convection	
Housing material		Plastic	
Field installation		rail TS 35 (EN 50022)	
Installation position		vertical	
IP rating		IP 20	
Protection class	–	2	
Weight (per unit)		0.29 kg / 0.639 lbs	
Termination		Spring terminal: 0.2–2.0 mm²	
Approvals	UL: UL 508 listed; cUL: UL 60950-1; TÜV: EN 60950-1; CE: EN 61000-6-3 / EN 55022 Class B, EN 6100-3-2, EN 601000-3-3, EN 55024, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11		
Monitoring			
DC ON Control (Rdy)	–	Open Collector	–
Switching voltage	–	DC 24 V	–
Switching current	–	≤ 35 mA	–
Switching capacity	–	–	–
Isolation voltage	–	none	–

# Power supply · regulated, 50 W


## Primary switchmode power supply, Single-phase

**Input:** Wide range input AC 85 V - 264 V; DC 90 V - 375 V

**Output:** 5 V - adjustable




### Dimensions




### PIN assignment

1 RDY	DC OK output for relay
2 +	Positive output
3 +	Positive output
4 -	Negative output
5 -	Negative output
6 ↓	Ground this to minimize high-frequency emissions
7 N	Input: neutral conductor
8 L	Input: phase conductor

### Derating



### Parallel mode



Description	Part-No.	Type	PU
<b>Screw terminal</b> Output voltage/current	DC 5 V; 10 A	DRA 60-05	1
<b>Spring terminal</b> Output voltage/current	DC 5 V; 10 A	DRA 60-05A	1
<b>Input</b>	<b>DRA 60-05</b>	<b>DRA 60-05A</b>	
<b>Voltage</b>			
Operation voltage range	AC 85–264 V / DC 90–375 V		
Line frequency	47 – 63 Hz		
Rated current	$V_{in}= 115 \text{ V}$ ; AC: 550 mA / $V_{in}= 230 \text{ V}$ ; AC: 280 mA		
Inrush current	$V_{in}= 115 \text{ V}$ ; AC: 30 A / $V_{in}= 230 \text{ V}$ ; AC: 60 mA		
Input fuse	T2A / AC 250 V internal		
Power Factor Correction P.F.C.			
<b>Output</b>			
Rated voltage output	DC 5 V		
Rated current output	10 A		
Voltage trim range	5–5.5 V		
Accuracy	±1 %		
Line regulation	±0.5 %		
Load regulation	±0.5 %		
Transient recovery time	1.0 ms		
Temperature coefficient	±0.02 % / °C		
Ripple & Noise	50 mV		
Hold up time	$V_{in}= 115 \text{ V}$ : 20 ms / $V_{in}= 230 \text{ V}$ : 30 ms		
Status indication DC ON (LED green)	≥4 V		
Status indication DC LOW (LED red)	–		
Parallel mode	with external diodes		
Efficiency	79 %		
Rated over load protection	110–150 %		
Over voltage protection	120–136 %		
Short circuit characteristics	Hiccup-mode		
<b>General</b>			
Switching frequency	min. 100 kHz		
Isolation voltage input/output	3 kVeff		
Isolation resistance at DC 500 V	100 MΩ		
Operation temperature range	-10°C – 70°C (Derating)		
Derating	-2.5% / °C starting at 61 °C		
Storage temperature range	-25 °C – 85 °C		
M.T.B.F.	210000 h		
Relative humidity	20–90% RH		
Dimensions	40.5 × 90.0 × 115.0 mm	0.0 × 90.0 × 115.0 mm	
Cooling	Air convection		
Housing material	Plastic		
Field installation	rail TS 35 (EN 50022)		
Installation position	vertical		
IP rating	IP 20		
Protection class	–		
Weight (per unit)	0.36 kg / 0.794 lbs		
Termination	Screw terminal 0.2–2.0 mm <sup>2</sup> Spring terminal 0.2–2.0 mm <sup>2</sup>		
Approvals	UL: UL 508 listed; cUL: UL 60950-1; TÜV: EN 60950-1; CE: EN 61000-6-3 / EN 55022 Class B, EN 6100-3-2, EN 601000-3-4 ,EN 55024, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8 ,EN 61000-4-11		
<b>Monitoring</b>			
DC ON Control (Rdy)	–		
Switching voltage	–		
Switching current	–		
Switching capacity	–		
Isolation voltage	–		

# Power supply · regulated, 60 W


**Primary switchmode power supply, Single-phase, Class 2**

**Input: Wide range input AC 85 V - 264 V; DC 90 V - 375 V**

**Output: 12 V / 24 V / 48 V - adjustable**




## Dimensions




## PIN assignment

1 RDY	DC OK output for relay
2 +	Positive output
3 +	Positive output
4 -	Negative output
5 -	Negative output
6 ↓	Ground this to minimize high-frequency emissions
7 N	Input: neutral conductor
8 L	Input: phase conductor

## Derating



## Parallel mode



Description	Part-No.	Type	PU
<b>Spring terminal</b>			
Output voltage/current	DC 12 V; 5 A	DRA 60-12	1
	DC 24 V; 2.5 A	DRA 60-24	1
	DC 48 V; 1.25 A	DRA 60-48	1
<b>Input</b>		<b>DRA 60-12</b>	<b>DRA 60-24</b>
Voltage		AC 100–240 V	
Operation voltage range		AC 85–264 V / DC 90–375 V	
Line frequency		47 – 63 Hz	
Rated current	$V_{in}= 115 \text{ V}$ ; AC: 690 mA / $V_{in}= 230 \text{ V}$ ; AC: 360 mA		
Inrush current	$V_{in}= 115 \text{ V}$ ; AC: 30 A / $V_{in}= 230 \text{ V}$ ; AC: 60 mA		
Input fuse		T2A / AC 250 V internal	
Power Factor Correction P.F.C.		–	
<b>Output</b>			
Rated voltage output	DC 12 V	DC 24 V	DC 48 V
Rated current output	5 A	2.5 A	1.25 A
Voltage trim range	12–14 V	24–28 V	48–55 V
Accuracy	±1 %		
Line regulation	±0.5 %		
Load regulation	±0.5 %		
Transient recovery time	1.0 ms		
Temperature coefficient	±0.02 % / °C		
Ripple & Noise	50 mV		
Hold up time	$V_{in}= 115 \text{ V}$ : 20 ms / $V_{in}= 230 \text{ V}$ : 30 ms		
Status indication DC ON (LED green)	≥9.6 V	≥19.2 V	≥37 V
Status indication DC LOW (LED red)		–	
Parallel mode		with external diodes	
Efficiency	86 %	89 %	89 %
Rated over load protection		110–150 %	
Over voltage protection		125–138 %	
Short circuit characteristics		Hiccup-mode	
<b>General</b>			
Switching frequency		min. 100 kHz	
Isolation voltage input/output		3 kVeff	
Isolation resistance at DC 500 V		100 MΩ	
Operation temperature range		-10°C – 70°C (Derating)	
Derating		-2.5% / °C starting at 61 °C	
Storage temperature range		-25 °C – 85 °C	
M.T.B.F.		210000 h	
Relative humidity		20–90% RH	
Dimensions	40.5 × 90.0 × 115.0 mm		
Cooling		Air convection	
Housing material		Plastic	
Field installation		rail TS 35 (EN 50022)	
Installation position		vertical	
IP rating		IP 20	
Protection class	–	2	
Weight (per unit)		0.36 kg / 0.794 lbs	
Termination		Spring terminal 0.2–2.0 mm²	
Approvals	UL: UL 508 listed; cUL: UL 60950-1, UL 1310 Class 2; TÜV: EN 60950-1; CE: EN 61000-6-3 / EN 55022 Class B, EN 6100-3-2, EN 601000-3-3, EN 55024, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 6100-4-6, EN 61000-4-8, EN 61000-4-11		
<b>Monitoring</b>			
DC ON Control (Rdy)	–	Open Collector	–
Switching voltage	–	DC 24 V	–
Switching current	–	≤ 35 mA	–
Switching capacity	–	–	
Isolation voltage	–	none	–

# Power supply · regulated, 60 W


**Primary switchmode power supply, Single-phase, Class 2**

**Input: Wide range input AC 85 V - 264 V; DC 90 V - 375 V**

**Output: 12 V / 24 V / 48 V - adjustable**




## Dimensions




## PIN assignment

1 RDY	DC OK output for relay
2 +	Positive output
3 +	Positive output
4 -	Negative output
5 -	Negative output
6 ↓	Ground this to minimize high-frequency emissions
7 N	Input: neutral conductor
8 L	Input: phase conductor

## Derating



## Parallel mode



Description	Part-No.	Type	PU
<b>Screw terminal</b>			
Output voltage/current	DC 12 V; 5 A	DRA 60-12	1
	DC 24 V; 2.5 A	DRA 60-24	1
	DC 48 V; 1.25 A	DRA 60-48	1
<b>Input</b>			
Voltage	DRA 60-12	DRA 60-24	DRA 60-48
Operation voltage range	AC 100–240 V	AC 85–264 V / DC 90–375 V	
Line frequency	47 – 63 Hz		
Rated current	$V_{in}= 115 \text{ V}$ ; AC: 690 mA / $V_{in}= 230 \text{ V}$ ; AC: 360 mA		
Inrush current	$V_{in}= 115 \text{ V}$ ; AC: 30 A / $V_{in}= 230 \text{ V}$ ; AC: 60 mA		
Input fuse	T2A / AC 250 V internal		
<b>Power Factor Correction P.F.C.</b>			
<b>Output</b>			
Rated voltage output	DC 12 V	DC 24 V	DC 48 V
Rated current output	5 A	2.5 A	1.25 A
Voltage trim range	12–14 V	24–28 V	48–55 V
Accuracy	±1 %		
Line regulation	±0.5 %		
Load regulation	±0.5 %		
Transient recovery time	1.0 ms		
Temperature coefficient	±0.02 % / °C		
Ripple & Noise	50 mV		
Hold up time	$V_{in}= 115 \text{ V}$ : 20 ms / $V_{in}= 230 \text{ V}$ : 30 ms		
Status indication DC ON (LED green)	≥9.6 V	≥19.2 V	≥37 V
Status indication DC LOW (LED red)		–	
Parallel mode		with external diodes	
Efficiency	86 %	89 %	
Rated over load protection	110–150 %		
Over voltage protection	125–138 %		
Short circuit characteristics	Hiccup-mode		
<b>General</b>			
Switching frequency	min. 100 kHz		
Isolation voltage input/output	3 kVeff		
Isolation resistance at DC 500 V	100 MΩ		
Operation temperature range	-10°C – 70°C (Derating)		
Derating	-2.5% / °C starting at 61 °C		
Storage temperature range	-25 °C – 85 °C		
M.T.B.F.	210000 h		
Relative humidity	20–90% RH		
Dimensions	40.5 × 90.0 × 115.0 mm		
Cooling	Air convection		
Housing material	Plastic		
Field installation	rail TS 35 (EN 50022)		
Installation position	vertical		
IP rating	IP 20		
Protection class	–	2	
Weight (per unit)	0.36 kg / 0.794 lbs		
Termination	Screw terminal: 0.2–2.0 mm²		
Approvals	UL: UL 508 listed; cUL: UL 60950-1, UL 1310 Class 2; TÜV: EN 60950-1; CE: EN 61000-6-3 / EN 55022 Class B, EN 6100-3-2, EN 601000-3-3, EN 55024, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 6100-4-6, EN 61000-4-8, EN 61000-4-11		
<b>Monitoring</b>			
DC ON Control (Rdy)	–	Open Collector	–
Switching voltage	–	DC 24 V	–
Switching current	–	≤ 35 mA	–
Switching capacity	–	–	–
Isolation voltage	–	none	–

# Power supply · regulated, 120 W


**Primary switchmode power supply, PFC, Single-phase, screw terminal - pluggable**

**Input: Wide range input AC 93 - 132 V; DC 186 - 264 V, DC 210 - 370 V - adjustable**

**Output: 12 V / 24 V / 48 V - adjustable**




## Dimensions




## PIN assignment

1	RDY	Normal open relay contact for DC ON level control
2	V+	Positive output
3	V+	Positive output
4	V-	Negative output
5	V-	Negative output
6	↓	Ground this to minimize high-frequency emissions
7	L	Input: phase conductor
8	N	Input: neutral conductor

## Derating



## Parallel mode



Description	Part-No.	Type	PU			
<b>Screw terminal</b>						
Output voltage/current	DC 12 V; 10 A	DRA 120-12	1			
	DC 24 V; 5 A	DRA 120-24	1			
	DC 48 V; 2.5 A	DRA 120-48	1			
<b>Input</b>						
	<b>DRA 120-12</b>	<b>DRA 120-24</b>	<b>DRA 120-48</b>			
Voltage	AC 115 / 230 V (manual switch)					
Operation voltage range	AC 93–132 V; AC 186–264 V / DC 210–370 V					
Line frequency	47 – 63 Hz					
Rated current	$V_{in} = 115 \text{ V}$ ; AC: 1.25 A / $V_{in} = 230 \text{ V}$ ; AC: 0.63 A					
Inrush current	$V_{in} = 115 \text{ V}$ ; AC: 24 A / $V_{in} = 230 \text{ V}$ ; AC: 48 mA					
Input fuse	T2A / AC 250 V internal					
Power Factor Correction P.F.C.	0,7					
<b>Output</b>						
Rated voltage output	DC 12 V	DC 24 V	DC 48 V			
Rated current output	10 A	5 A	2.5 A			
Voltage trim range	11.4–14.5 V	22.5–30 V	45–55 V			
Accuracy	±1 %					
Line regulation	±0.5 %					
Load regulation	Single ±1 %, Parallel ±5 %					
Transient recovery time	1.0 ms					
Temperature coefficient	±0.3 % / °C					
Ripple & Noise	50 mV					
Hold up time	$V_{in} = 115 \text{ V}$ : 25 ms / $V_{in} = 230 \text{ V}$ : 30 ms					
Status indication DC ON (LED green)	≥10–11 V	≥21–22 V	≥42–44 V			
Status indication DC LOW (LED red)	<10–11.2 V	20.5/22.5 V	<41–45 V			
Parallel mode	max. 3 units					
Efficiency	84 %	86 %	87 %			
Rated over load protection	105–125 %					
Over voltage protection	125–145 %					
Short circuit characteristics	Current limit					
<b>General</b>						
Switching frequency	min. 80 kHz					
Isolation voltage input/output	3 kVeff					
Isolation resistance at DC 500 V	100 MΩ					
Operation temperature range	-10°C – 70°C (Derating)					
Derating	-2.5% / °C starting at 61 °C					
Storage temperature range	-25 °C – 85 °C					
M.T.B.F.	210000 h					
Relative humidity	20–90% RH					
Dimensions	63.5 × 142.0 × 116.0 mm					
Cooling	Air convection					
Housing material	metal					
Field installation	rail TS 35 (EN 50022)					
Installation position	vertical					
IP rating	IP 20					
Protection class	–					
Weight (per unit)	0.86 kg / 1.895 lbs					
Termination	Screw terminal: 0.2–2.0 mm²					
Approvals	UL: UL 508 listed cUL: UL 60950-1 TÜV: EN 60950					
CE: EN 50081-1; EN 55022 Class B EN 6100-3-2, EN 6100-3-3, EN 50082-1, EN 55024						
<b>Monitoring</b>						
DC ON Control (Rdy)	–	Normally open	–			
Switching voltage	–	DC 60 V	–			
Switching current	–	max. 300 mA	–			
Switching capacity	–	–	–			
Isolation voltage	–	DC 500 V	–			

# Power supply · regulated, 240 W


## Primary switchmode power supply, PFC, Single-phase

**Input:** Wide range input AC 93 - 132 V; AC 186 - 264 V, DC 210 - 370 V - automatic

**Output:** 24 V / 48 V - adjustable




### Dimensions




### PIN assignment

1	RDY	Normal open relay contact for DC ON level control
2		
3	V+	Positive output
4	V+	Positive output
5	V-	Negative output
6	V-	Negative output
7	↓	Ground this to minimize high-frequency emissions
8	L	Input: phase conductor
9	N	Input: neutral conductor

### Derating



### Parallel mode



Description	Part-No.	Type	PU
<b>Screw terminal, pluggable</b>			
Output voltage/current	DC 24 V; 10 A	DRA 240-24B	1
	DC 48 V; 5 A	DRA 240-48B	1
<b>Screw terminal</b>			
Output voltage/current	DC 24 V; 10 A	DRA 240-24A	1
<b>Input</b>	<b>DRA 240-24B</b>	<b>DRA 240-48B</b>	<b>DRA 240-24A</b>
Voltage	AC 115 / 230 V (auto select)		
Operation voltage range	AC 93–132 V; AC 186–264 V / DC 210–370 V		
Line frequency	47 – 63 Hz		
Rated current	$V_{in} = 115 \text{ V}$ ; AC: 2.4 A / $V_{in} = 230 \text{ V}$ ; AC: 1.2 A		
Inrush current	$V_{in} = 115 \text{ V}$ ; AC: 30 A / $V_{in} = 230 \text{ V}$ ; AC: 60 mA		
Input fuse	T6.3A / AC 250 V internal		
Power Factor Correction P.F.C.	0,7		
<b>Output</b>			
Rated voltage output	DC 24 V	DC 48 V	DC 24 V
Rated current output	10 A	5 A	10 A
Voltage trim range	22.5–28.5	47–56 V	22.5–28.5 V
Accuracy	$\pm 1\%$		
Line regulation	$\pm 0.5\%$		
Load regulation	Single $\pm 1\%$ , Parallel $\pm 5\%$		
Transient recovery time	1.0 ms		
Temperature coefficient	$\pm 0.3\% / ^\circ\text{C}$		
Ripple & Noise	100 mV		
Hold up time	$V_{in} = 115 \text{ V}$ : 25 ms / $V_{in} = 230 \text{ V}$ : 30 ms		
Status indication DC ON (LED green)	< 17.6/19.4 V	< 37–43 V	< 17.6/19.4 V
Status indication DC LOW (LED red)	< 17.6/19.4 V	< 37–43 V	< 17.6/19.4 V
Parallel mode	max. 3 units at 90% load current, manual switch		
Efficiency	89 %	90 %	89 %
Rated over load protection	105–145 %		
Over voltage protection	120–145 %		
Short circuit characteristics	Current limit		
<b>General</b>			
Switching frequency	min. 80 kHz		
Isolation voltage input/output	3 kVeff		
Isolation resistance at DC 500 V	100 M $\Omega$		
Operation temperature range	-10°C – 70°C (Derating)		
Derating	-2.5% / °C starting at 61 °C		
Storage temperature range	-25 °C – 85 °C		
M.T.B.F.	210000 h		
Relative humidity	20–95% RH		
Dimensions	83.0 × 142.0 × 116.0 mm		
Cooling	Air convection		
Housing material	metal		
Field installation	rail TS 35 (EN 50022)		
Installation position	vertical		
IP rating	IP 20		
Protection class	–		
Weight (per unit)	1 kg / 2.204 lbs		
Termination	Screw terminal: 0.5–4.0 mm <sup>2</sup> , pluggable	Screw terminal: 0.2–2.0 mm <sup>2</sup>	
<b>Approvals</b>	UL: UL 508 listed cUL: UL 60950-1 approved TÜV: EN 60950-1; CE: EN 61000-6-3 / EN 55022 Class B EN 6100-3-2, EN 6100-3-3, EN 61000-6-2, EN 55024		
<b>Monitoring</b>			
DC ON Control (Rdy)	Normally open	–	Normally open
Switching voltage	DC 60 V	–	DC 60 V
Switching current	max. 300 mA	–	max. 300 mA
Switching capacity	–	–	–
Isolation voltage	DC 500 V	–	DC 500 V

# Power supply · regulated, 480 W


## Primary switchmode power supply, PFC, Single-phase

**Input:** Wide range input AC 90 - 264 V; DC 120 - 370 V, DC 24 - 48 V - adjustable

**Output:** 24 V / 48 V - adjustable




### Dimensions




### PIN assignment

1	RDY	Normal open relay contact for DC ON level control
2	V+	Positive output
3	V+	Positive output
5	V-	Negative output
6	V-	Negative output
7	↓	Ground this to minimize high-frequency emissions
8	L	Input: phase conductor
9	N	Input: neutral conductor

### Derating



### Parallel mode



Description	Part-No.	Type	PU
<b>Screw terminal, pluggable</b>			
Output voltage/current	DC 24 V; 20 A	DRA 480-24B	1
<b>Screw terminal</b>			
Output voltage/current	DC 24 V; 20 A	DRA 480-24A	1
	DC 48 V; 10 A	DRA 480-48A	1
<b>Input</b>	<b>DRA 480-24B</b>	<b>DRA 480-24A</b>	<b>DRA 480-48A</b>
Voltage	AC 115 / 230 V (auto select)		
Operation voltage range	AC 90–264 V; DC 120–370 V		
Line frequency	47 – 63 Hz		
Rated current	$V_{in} = 115 \text{ V}$ ; AC: 4.8 A / $V_{in} = 230 \text{ V}$ ; AC: 2.45 A		
Inrush current	$V_{in} = 115 \text{ V}$ ; AC: 25 A / $V_{in} = 230 \text{ V}$ ; AC: 50 mA		
Input fuse	T10A / AC 250 V internal		
Power Factor Correction P.F.C.	0,99		
<b>Output</b>			
Rated voltage output	DC 24 V	DC 48 V	
Rated current output	20 A	10 A	
Voltage trim range	22.5–28.5 V	47–56 V	
Accuracy	±1 %		
Line regulation	±0.5 %		
Load regulation	Single ±0.5 %, Parallel ±5 %		
Transient recovery time	1.0 ms		
Temperature coefficient	±0.02 % / °C		
Ripple & Noise	100 mV		
Hold up time	min. 30 ms		
Status indication DC ON (LED green)	< 17.6/19.4 V	<37/40 V	
Status indication DC LOW (LED red)	< 17.6/19.4 V	<37–43 V	
Parallel mode	max. 3 units at 90% load current, manual switch		
Efficiency	89 %	90 %	
Rated over load protection	120–140 %		
Over voltage protection	125–137 %	119–131 %	
Short circuit characteristics	Current limit		
<b>General</b>			
Switching frequency	min. 100 kHz		
Isolation voltage input/output	3 kVeff		
Isolation resistance at DC 500 V	100 MΩ		
Operation temperature range	-25°C – 71°C (Derating)		
Derating	-4% / °C starting at 61 °C		
Storage temperature range	-25 °C – 85 °C		
M.T.B.F.	210000 h		
Relative humidity	20–95% RH		
Dimensions	175.0 × 125.0 × 116.0 mm		
Cooling	Air convection		
Housing material	metal		
Field installation	rail TS 35 (EN 50022)		
Installation position	vertical		
IP rating	IP 20		
Protection class	–		
Weight (per unit)	1,92 kg / 4.232 lbs		
Termination	Screw terminal: 0.2–5.0 mm² - pluggable	Screw terminal: 0.2–5.0 mm²	
<b>Approvals</b>	UL: UL 508 listed cUL: UL 60950-1 approved		
	TÜV: EN 60950-1; CE: EN 61000-6-3 / EN 55022 Class B EN 6100-3-2, EN 6100-3-3, EN 61000-6-2, EN 55024		
<b>Monitoring</b>			
DC ON Control (Rdy)	Normally open	–	
Switching voltage	DC 60 V	–	
Switching current	max. 300 mA	–	
Switching capacity	–		
Isolation voltage	DC 500 V	–	

# Power supply · regulated, 480 W, 3-phase


**Primary switchmode power supply, PFC, 3-phase, screw terminal**

**Input: Wide range input AC 340 - 576 V; DC 480 - 820 V**

**Output: 24 V / 48 V - adjustable**




## Dimensions




## PIN assignment

1, 2	V <sub>O+</sub>	Positive output
3, 4	V <sub>O-</sub>	Negative output
5	Ground	
6, 7, 8	Input terminal	
DC on	LED DC- ok	
DC low	LED DC- under voltage	
Rdy	Signal contact, only 24V	

## Derating



## Parallel mode



Description	Part-No.	Type	PU	
<b>Screw terminal</b>				
Output voltage/current	DC 24 V; 20 A	722805	WRA 480-24	1
	DC 48 V; 10 A	722809	WRA 480-48	1
<b>Input</b>	<b>WRA 480-24</b>	<b>WRA 480-48</b>		
Voltage	AC 380–500 V			
Operation voltage range	AC 340–576 V; DC 480–820 V			
Line frequency	47 – 63 Hz			
Rated current	$V_{in} = 400 \text{ V}$ ; AC: 1.5 A / $V_{in} = 480 \text{ V}$ ; AC: 1.2 A			
Inrush current	18 A			
Input fuse	T3, 15 A / internal per phase			
Power Factor Correction P.F.C.	0,7			
<b>Output</b>				
Rated voltage output	DC 24 V	DC 48 V		
Rated current output	20 A	10 A		
Voltage trim range	22.5 – 28.5 V	47–56 V		
Accuracy	1 %			
Line regulation	$\pm 1 \%$			
Load regulation	Single $\pm 1 \%$ , Parallel $\pm 5 \%$			
Transient recovery time	1.0 ms			
Temperature coefficient	$\pm 0.02 \text{ \% / } ^\circ\text{C}$			
Ripple & Noise	100 mV			
Hold up time	min. 20 ms			
Status indication DC ON (LED green)	< 17.6/19.4 V	< 37–43 V		
Status indication DC LOW (LED red)	< 17.6/19.4 V	< 37–43 V		
Parallel mode	max. 3 units at 90% load current, manual switch			
Efficiency	90 %			
Rated over load protection	115–135 %			
Over voltage protection	125–137 %	125–142 %		
Short circuit characteristics	Current limit (C) / Hiccup-mode (D), with switch C/D			
<b>General</b>				
Switching frequency	min. 100 kHz			
Isolation voltage input/output	3 kVeff			
Isolation resistance at DC 500 V	100 MΩ			
Operation temperature range	-25°C – 71°C (Derating)			
Derating	-2.5% / °C starting at 61 °C			
Storage temperature range	-25 °C – 85 °C			
M.T.B.F.	210000 h			
Relative humidity	20–95% RH			
Dimensions	150.0 × 125.0 × 116.0 mm			
Cooling	Air convection			
Housing material	metal			
Field installation	rail TS 35 (EN 50022)			
Installation position	vertical			
IP rating	IP 20			
Protection class	–			
Weight (per unit)	1.75 kg / 3.857 lbs			
Termination	Screw terminal: 0.2–5.0 mm <sup>2</sup>			
Approvals	UL: UL 508 listed cUL: UL 60950-1 approved TÜV: EN 60950-1; CE: EN 61000-6-3 / EN 55022 Class B EN 6100-3-2, EN 6100-3-3, EN 61000-6-2, EN 55024			
<b>Monitoring</b>				
DC ON Control (Rdy)	Normally open	–		
Switching voltage	DC 60 V	–		
Switching current	max. 300 mA	–		
Switching capacity	–			
Isolation voltage	DC 500 V	–		

# Power supply · regulated, 960 W, 3-phase


**Primary switchmode power supply, PFC, 3-phase, screw terminal**

**Input: Wide range input AC 340 - 576 V; DC 480 - 820 V**

**Output: 24 V / 48 V - adjustable**




## Dimensions




## PIN assignment

1, 2	Rdy	Signal contact, only 24V
3, 4	P,G	Current share
5, 6, 7	V <sub>O+</sub>	Positive output
8, 9, 10	V <sub>O-</sub>	Negative output
11	G	Ground
12, 13, 14	Input terminal	
DC on	LED DC- ok	
DC low	LED DC- under voltage	

## Derating



## Parallel mode



Description	Part-No.	Type	PU
<b>Screw terminal</b>			
Output voltage/current	DC 24 V; 40 A	722806	WRA 960-24
	DC 48 V; 20 A	722810	WRA 960-48
			1
			1
<b>Input</b>	<b>WRA 960-24</b>	<b>WRA 960-48</b>	
Voltage	AC 400–500 V		
Operation voltage range	AC 340–575 V; DC 480–820 V		
Line frequency	47 – 63 Hz		
Rated current	$V_{in} = 400 \text{ V}$ ; AC: 2,4 A / $V_{in} = 480 \text{ V}$ ; AC: 1,6 A		
Inrush current	30 A		
Input fuse	T6, 3 A / internal per phase		
	0,7		
<b>Output</b>			
Rated voltage output	DC 24 V	DC 48 V	
Rated current output	40 A	20 A	
Voltage trim range	22.5–28.5 V	47–56 V	
Accuracy	1 %		
Line regulation	$\pm 1 \%$		
Load regulation	Single $\pm 1 \%$ , Parallel $\pm 5 \%$		
Transient recovery time	–		
Temperature coefficient	$\pm 0.02 \text{ \% / } ^\circ\text{C}$		
Ripple & Noise	80 mV		
Hold up time	min. 20 ms		
Status indication DC ON (LED green)	>17.6–19.4 V	<37–43 V	
Status indication DC LOW (LED red)	>17.6–19.4 V	<37–43 V	
Parallel mode	max. 2 units at 90% load current, terminal P, G for current share		
Efficiency	92 %		
Rated over load protection	Rated over load protection: 110 % – 130 %		
Over voltage protection	125–137 %	125–142 %	
Short circuit characteristics	Current limit		
<b>General</b>			
Switching frequency	min. 100 kHz		
Isolation voltage input/output	3 kVeff		
Isolation resistance at DC 500 V	100 MΩ		
Operation temperature range	-25°C – 71°C (Derating)		
Derating	-3.5% / °C starting at 61°C		
Storage temperature range	-25 °C – 85 °C		
M.T.B.F.	210000 h		
Relative humidity	20–95% RH		
Dimensions	276.0 × 125.0 × 118.0 mm		
Cooling	Air convection		
Housing material	metal		
Field installation	rail TS 35 (EN 50022)		
Installation position	vertical		
IP rating	IP 20		
Protection class	–		
Weight (per unit)	3,2 kg / 7.053 lbs		
Termination	Screw terminal: 0.2–5.0 mm²		
Approvals	UL: UL 508 listed cUL: UL 60950-1 anerkannt TÜV: EN 60950-1; CE: EN 61000-6-3 / EN 55022 Class B EN 6100-3-2, EN 6100-3-3, EN 61000-6-2, EN 55024		
<b>Monitoring</b>			
DC ON Control (Rdy)	Normally open	–	
Switching voltage	DC 60 V	–	
Switching current	max. 300 mA	–	
Switching capacity	–		
Isolation voltage	DC 500 V	–	

# Power supply · regulated, 50 W


**Primary switchmode power supply, Single-phase, spring terminal**

**Input: AC 170 – 264 V**


**Output: 10–24 V - adjustable**



## Dimensions



## PIN assignment



Description	Part-No.	Type	PU
<b>Spring terminal</b>			
Output voltage/current	DC 24 V; 2 A	716213	NGP 24/2-6213
			1
<b>Input</b>		<b>NGP 24/2-6213</b>	
Voltage		AC 230 V	
Operation voltage range		AC 170–264 V	
Line frequency		47 – 63 Hz	
Rated current		$V_{in}=230 \text{ V}; \text{AC}: 350 \text{ mA}$	
Inrush current		$V_{in}=230 \text{ V}; \text{AC}: 10 \text{ A}$	
Input fuse		recommended back-up fuse: MT 1A / 250 V	
Power Factor Correction P.F.C.		–	
<b>Output</b>			
Rated voltage output		DC 24 V (delivery status)	
Rated current output		2 A	
Voltage trim range		10–24 V	
Accuracy		<1 %	
Line regulation		–	
Load regulation		–	
Transient recovery time		5.0 ms	
Temperature coefficient		–	
Ripple & Noise		160 mV	
Hold up time		$V_{in} = 230 \text{ V}: 10 \text{ ms}$	
Status indication DC ON (LED green)		Yes	
Status indication DC LOW (LED red)		–	
Parallel mode		No	
Efficiency		85 %	
Rated over load protection		110–150 %	
Over voltage protection		120–136 %	
Short circuit characteristics		Hiccup-mode	
<b>General</b>			
Switching frequency		min. 100 kHz	
Isolation voltage input/output		4 kVeff	
Isolation resistance at DC 500 V		– MΩ	
Operation temperature range		–	
Derating		No	
Storage temperature range		-40 °C – 85 °C	
M.T.B.F.		– h	
Relative humidity		20–80 % RH	
Dimensions		59.5 × 120.0 × 62.5 mm	
Cooling		Air convection	
Housing material		metal	
Field installation		rail TS 35 (EN 50022)	
Installation position		vertical	
IP rating		IP 20	
Protection class		1	
Weight (per unit)		0,24 kg/0,529 lbs	
Termination		Spring terminal 0.2–2.0 mm²	
Approvals		CE: EN 55022; Class B; EN 50081-1; EN 50082-2 cULus submitted	
<b>Monitoring</b>			
DC ON Control (Rdy)		–	
Switching voltage		–	
Switching current		–	
Switching capacity		–	
Isolation voltage		–	

# Power supply · unregulated, 60–360 W


**Power supply unit, Single-phase, unregulated, screw terminal**

**Input: AC 115 V / 230 V / 400 V**


**Output: DC 24 V**



## Dimensions




## PIN assignment



Description	Part-No.	Type	PU
<b>Screw terminal</b>			
Rated voltage	DC 24V; 2.5A	722962	NG 24/2,5-2962
	DC 24V; 5A	722963	NG 24/5-2963
	DC 24V; 10A	722972	NG 24/10-2972
	DC 24V; 15A	722973	NG 24/15-2973
<b>Input</b>			
Input voltage	AC 115 / 230 / 400V		
Operation voltage range	AC 104–196V / AC 207–224V / AC 360–424V		
Line frequency	47 – 63 Hz		
Rated current	1.6A / 0.6A / 0.4A	2.4A / 1.1A / 0.6A	5.0A / 2.4A / 1.8A
Rated power	60 W	120 W	240 W
Recommended back-up fuse	115V: 4A / 230V: 2A / 400V: 1A	115V: 4A / 230V: 2A / 400V: 2A	115V: 6A / 230V: 4A / 400V: 2A
Termination	Screw terminal with additional blade terminal: 0.5–6 mm <sup>2</sup>		
<b>Output</b>			
Rated voltage output	DC 24 V		
Rated current output	2.5 A	5 A	10 A
Voltage	at open-circuit 30.2 V, at full load: 20.4 V		
Line regulation	–		
Load regulation	–		
Transient recovery time	–		
Temperature coefficient	–		
Ripple & Noise	650 mV		
Hold up time	–		
Status indication DC ON (LED green)	Yes		
Status indication DC LOW (LED red)	–		
Parallel mode	with 90% load current		
Efficiency	73 %	77 %	80 %
Rated over load protection	No		
Short circuit characteristics	–		
Output circuit	Varistor and capacitor		
Termination	Screw terminal 0.5–10 mm <sup>2</sup>		
<b>General</b>			
Switching frequency	–		
Isolation voltage input/output	4 kVeff		
Isolation class	T 40 / B		
Insulation class	according to VDE B, UL/CSA: class 130		
Operation temperature range	-25 °C – 50 °C		
Derating	–		
Storage temperature range	-40 °C – 80 °C		
Relative humidity	80% occasional condensation possible		
Dimensions	85 × 137 × 98 mm	106 × 160 × 113 mm	121 × 170 × 128 mm
Cooling	Air convection		
Housing material	metal		
Field installation	Screw termination: 0.5–4.0 mm <sup>2</sup>		
Assembly borehole	64 × 64.5 mm/M 5	83 × 80.5 mm/M 5	104 × 90 mm/M 5
Cu application weight	0.62 kg/piece	0.6 kg/piece	0.9 kg/piece
Installation position	Optional		
IP rating	IP 00		
IP rating	I		
Weight (per unit)	2,3 kg/ 5.07 lbs	4,9 kg/ 10.80 lbs	7,5 kg/ 16.53 lbs
Standards	Transformer compliant with IEC 61-558, Output limit values compliant with EN 61 131-2		
	EMC compliant with EN 50 081-1 and EN 50 082-2, Main connection compliant with EN 61 000-3-2		
Approvals	cULus		

## Fixing



# Interface technology • Current control system LCCS


## Current control system up to 10A

### Single channel version


rated current : adjustable DC 1-10A; Trip Characteristics: Fast, Intermediate, and Slow acting



### Dimensions




### Pin assignment




- 1: + Output
- 2: Control input (Set / Reset)
- 3: Status output
- 4: Optional: 1 wire bus (nc 716400)
- 5: 0V
- 6: + Supply (alternative)
- 7: + Supply

Description	Part number	Type	PU
Spring terminal			
<b>Rated voltage</b>	DC 24V	LCCS 7-6400	1
<b>Input side</b>			
Rated voltage	DC 24V		
Operating voltage range	DC 18V - 32V		
Rated current	DC 10A max. (control system 716400)		
System current max.	DC 40A via copper busbar 10 x 3 mm		
Reverse voltage protection	internal electronic		
Termination	spring terminal		
<b>Control input (Set/Reset)</b>			
Signal level	DC 24V (EN61131)		
Switch-off time (Reset)	pulse (trailing edge) > 100ms, < 800ms		
Switch-on time (Set)	pulse (trailing edge) > 1s		
Termination	Spring terminal: 0,25 - 2,5mm <sup>2</sup>		
<b>Output Side</b>			
Switch method	MosFet		
Output current	max. DC 10A		
Voltage drop	< 170mV (10A)		
Status indication	green: ok; green flashing: 90% load, red flashing: error and no acknowledge; red: error		
Switch on capacity	10.000µF		
Current range	1A - 10A (adjustable via switch in 1A steps)		
Cut-off time	Trip Characteristics: Fast, Intermediate, and Slow acting (adjustable via switch)		
<b>Singal output</b>	DC 24V, 10mA		
Signal level	DC 24V: supply voltage is ok, no error; DC 0V: error; output switch off		
Switch method	Transistor, open collector with pull up resistor		
<b>General data</b>			
Housing material	PA 6.6 (UL94-0; NFF I2, F2)		
Field installation	rail TS 35 (EN50022)		
IP rating	IP 20		
Installation position	any		
Termination	Spring terminal: 0,25 - 2,5 mm <sup>2</sup>		
Operation temperature range	-25°C - 60°C		
Storage temperature range	-40°C - 85°C		
Dimension (LxWxD)	8,1 x 114,5 x 116,0		
Weight	0.12 kg / 0.265 lbs		
Approvals	cULus, Class 1 Div 2 applied for		
Standards	EN 60950-1; EN6131-1,2; EN 60898; EN 60947-4-1; EN 50081		
<b>Accessories</b>	Part number	Type	PU
Terminal set (Supply- and end terminal)	716425	LCCS-ES 7-6425	1
Copper busbar 1 m	716426	LCCS-CU 7-6426	1
Copper busbar 1 m	716427	LCCS-AD 7-6427	1
Jumper comb 16pole, white	716428	LCCS-BKW 7-6428	5
Jumper comb 16pole, red	716429	LCCS-BKR 7-6429	5
Jumper comb 16pole, blau	716430	LCCS-BKB 7-6430	5
Identification plate (100pcs), white	716431	LCCS-BZW 7-6431	10
Identification plate (100pcs), red	716432	LCCS-BZR 7-6432	10
Identification plate (100pcs), blue	716433	LCCS-BKB 7-6433	10
Identification plate (100pcs), yellow	716434	LCCS-BZG 7-6434	10

# Modular, flexible and safe: The Current Control System LCCS



# intelligent Lutze



**USA**

LUTZE INC.  
13330 South Ridge Drive  
Charlotte, NC 28273  
Tel.: (704) 504-0222  
Fax: (704) 504-0223  
[info@lutze.com](mailto:info@lutze.com)

**Germany**

Friedrich Lütze GmbH & Co. KG  
Postfach 12 24 (PLZ 71366)  
Bruckwiesenstraße 17-19  
D-71384 Weinstadt  
Tel.: +49 (0)71 51 60 53-0  
Fax: +49 (0)71 51 60 53-277(-288)  
[info@luetze.de](mailto:info@luetze.de)

**Lutze systems  
for highest  
industrial standards:**

- Prepopulated C-track systems
- Lutze-LSC-wiring systems for all standard control panels
- Powerful module and interface technology
- Reliable suppression technology
- Efficient power supplies
- Automation systems for harsh environments

**United Kingdom**

LÜTZE Ltd.  
Unit 3 Sandy Hill Park  
Sandy Way, Amington  
Tamworth, Staffs, B77 4DU  
Tel.: +44 (0)1827 31333-0  
Fax: +44 (0)1827 31333-2  
[sales.gb@lutze.co.uk](mailto:sales.gb@lutze.co.uk)

**Austria**

LÜTZE Elektrotechnische Erzeugnisse Ges.m.b.H.  
Tel.: +43 (0)1 257 52 52-0  
Fax: +43 (0)1 257 52 52-20  
[office@luetze.at](mailto:office@luetze.at)

**Switzerland**

LÜTZE AG  
Tel.: +41 (0)55 450 23 23  
Fax: +41 (0)55 450 23 13  
[info@luetze.ch](mailto:info@luetze.ch)

**France**

LUTZE S.A.  
Tél.: +33 (0)1 34 18 77 00  
Fax: +33 (0)1 34 18 18 44  
[lutze@lutze.fr](mailto:lutze@lutze.fr)

**Spain**

LUTZE, S.L.  
Tel.: +34 93 285 7480  
Fax: +34 93 285 7481  
[info@lutze.es](mailto:info@lutze.es)

# www.lutze.com

