Building Wire-600 Volt



THHN-THWN-2, 90°C-600 Volt







Product Construction

Conductor:

Solid or stranded annealed copper

Insulation:

• Extruded layer of heat, Moisture, and flame resistant PVC with an extrusion of high heat and light stabilized Nylon

Applications

- May be installed in conduit, duct, or other recognized raceways in wet or dry locations
- Small diameter of the wire permits additional circuits or larger conductors without exceeding maximum fill limitations

Features

- Smooth outer jacket for easy pulling
- May be used as:
- Building Wire 90°C
- Appliance Wire 105°C
- Flourescent Ballast
- Hook-up 90°C

Standards

- UL 66-TFFN/TFN
- UL 1063-Machine Tool Wire
- UL 758- AWM Style 1316

Additonal Information

- All colors can be striped
- Can be provided in twisted configurations

Selling Exclusively Through Electrical Distribution Since 1977 | phone: (800) 292-OMNI | website: omnicable.com



Part #	AWG	Stranding	Insulation Thickness	Jacket Thickness	Nom. O.D.	Lbs./M'
M514SO-XX	14	Solid	.015"	.004″	.102″	16
M514ST-XX	14	19	.015"	.004"	.112″	16
M512SO-XX	12	Solid	.015″	.004″	.119″	24
M512ST-XX	12	19	.015″	.004"	.131″	24
M510SO-XX	10	Solid	.020"	.004"	.150″	37
M510ST-XX	10	19	.020"	.004"	.160"	37
M508ST-XX	8	19	.030"	.005"	.220"	64
M506ST-XX	6	19	.030"	.005″	.260"	96
M504ST-XX	4	19	.040"	.006"	.330"	155
M503ST-XX	3	19	.040"	.006"	.345″	190
M502ST-XX	2	19	.040"	.006"	.388″	235
M501ST-XX	1	19	.050"	.007"	.440"	300
M51/0ST-XX	1/0	19	.050"	.007"	.477″	370
M52/0ST-XX	2/0	19	.050"	.007"	.520"	465
M53/0ST-XX	3/0	19	.050"	.007"	.571″	570
M54/0ST-XX	4/0	19	.050"	.007"	.640"	720
M5250ST-XX	250	37	.060"	.008"	.711″	850
M5300ST-XX	300	37	.060"	.008″	.766"	1101
M5350ST-XX	350	37	.060"	.008″	.817"	1172
M5400ST-XX	400	37	.060"	.008"	.864"	1333
M5500ST-XX	500	37	.060"	.008"	.949"	1653
M5600ST-XX	600	61	.070"	.009"	1.051"	1985
M5750ST-XX	750	61	.070"	.009"	1.126"	2462

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.

Inster the color number in the -XX location:

- -01 = Black
- -02 = White
- -03 = Red
- -04 = Green
- -05 = Blue
- -06 = Gray
- -07 = Orange
- -08 = Yellow
- -09 = Purple
- -10 = Brown
- -11 = Pink
- -12 = Tan