


Straight Blade Plugs and Connectors

INDEX

| | |
|--|-----|
| Industrial Grade Plugs & Connectors | |
| Overview | M2 |
| 15A 125V & 250V | |
| Hospital Grade | M3 |
| Industrial Grade | M3 |
| Flanged Inlets and Outlets | M3 |
| Wetguard® | M5 |
| Dustguard® | M5 |
| Python™ | M6 |
| Integrated Inlets and Outlets with Weather-Resistant Covers | M7 |
| 20A 125V & 250V | |
| Hospital Grade | M4 |
| Industrial Grade | M4 |
| Flanged Inlets and Outlets | M4 |
| Wetguard® | M5 |
| Dustguard® | M5 |
| Python™ | M6 |
| Integrated Inlets and Outlets with Weather-Resistant Boots | M7 |
| Weather-Resistant Boots | M4 |
| 20 AMP Power Plugs | M8 |
| 30 AMP Nylon Angle Plugs | M8 |
| 50 AMP Nylon Angle Plugs | M9 |
| 60 AMP Nylon Angle Plugs | M10 |
| Commercial Grade Plugs & Connectors | |
| Overview | M11 |
| 15A 125V & 250V | M12 |
| 20A 125V & 250V | M13 |
| 30 Amp and 50 Amp Dual Power | |
| Attachment Plugs | M14 |
| Residential Grade Plugs & Connectors | |
| Parallel, Polarized and Non-Polarized | M15 |
| Grounding | M16 |



STRAIGHT BLADE PLUG AND CONNECTOR FEATURES

Industrial Grade Straight Blade Plugs and Connectors

A COMPLETE LINE OF PLUGS AND CONNECTORS THAT STANDS UP TO THE HARSHTEST ENVIRONMENTS

The Leviton line of straight blade plugs and connectors includes: Black & White™ Industrial Grade devices that resist impact, corrosion and chemicals; Hospital Grade devices that meet the highest standards for dependable, long-term performance; Wetguard® for water and moisture resistance; Dustguard® to resist dust and dirt; Python™, with an innovative interlocking design; rugged nylon flanged inlets and outlets; and integrated inlets and outlets with weather resistant covers.



Hospital Grade
Superior design, heavy-duty, impact-resistant, all nylon construction for long-lasting performance and reliability in the demanding healthcare environment.
8215-C shown



Angle Plugs and Connectors
For hospital and industry use where power cords must lay close to walls and floors: 8 plug positions.
8215-CAT shown



Wetguard®
Specifically developed for wet or damp locations. EPTR thermoplastic rubber body and rugged design resist water, alkalis, grease, oils and solvents.
14W48 shown



Python™
Hinged design provides speedy, simple wiring and installation, delivers top performance, stands up to rough-duty applications.
5456-VY shown



Flanged Inlets and Outlets
Fit flush on equipment mounting panels and require only 2 mounting screws for easy panel assembly.
5278-C shown



Leviton's 15 and 20 Amp nylon plugs and connectors offer superior performance and long-lasting reliability features; from ergonomic design details to rugged construction that resists impact, punishing application environments, chemicals and corrosives.

Features and Benefits

- UL 498 Listed; meets latest Federal Specifications WC-598; CSA Specification C22.2 No. 42 Certified
- Cord clamp with removable strain relief insert accepts cables rated from 10-3 ST to 18-3 SVT (.245"-.700")
- One-piece, rivetless triple-wipe brass connector contacts offer enlarged contact surface area
- Husk is constructed of ST801 Super Tough Nylon for superior impact resistance in rugged environments
- Beveled back edges prevent body from catching on corners and rough surfaces
- Ergonomic, fluted body design with radial gripping edge is ideal for gripping and pulling


Positive contact plate bundles stranded wire maximizing surface contact resulting in improved termination

NEMA configuration and device rating are molded on front of device to assist with identification

Dead front solid containment barrier prevents accidental contact with internal parts

Wiring module keyed to body for easy assembly and a tight fit

External cord grip utilizes deep triple drive steel screws that are backed out and positioned inside shrouded pockets. External clamps accepts wire mesh grips. Catalog and NEMA numbers printed on cord clamp



5266-C

#8-32 triple drive brass terminal screws


Three "U" type fast-threading, triple drive, steel screws secure wiring module to body

Wire clamps move in individual chamber — provide positive crimp lock without cutting wire strand

Captive, color-coded brass #8 terminal screws





Individual deep-funnelled chamfered wire wells. Clear housing allows inspection of wire termination and provides molded-in wire strip gage



Industrial Grade Straight Blade Plugs and Connectors



Hospital Grade —15 AMP 125V 2-Pole, 3-Wire Grounding

| DESCRIPTION | CAT. NO. PLUG NEMA 5-15P  | CAT. NO. CONNECTOR NEMA 5-15R  |
|---|---|---|
| Hospital Grade, Black & White Body | 8215-C | 8219-C |
| Hospital Grade, Transparent Body | 8215-CT | 8219-CT |
| Hospital Grade, Power Indication™ Transparent | 8215-PLC | 8219-PLC |
| Hospital Grade Angle, Transparent Body | 8215-CAT | — |

Industrial Grade —15 AMP 125V 2-Pole, 3-Wire Grounding

| | | |
|---|----------|----------|
| Black & White Nylon Body | 5266-C | 5269-C |
| High-Visibility Yellow Nylon Body | 5266-CY | 5269-CY |
| All-Black Nylon for Stage and Studio | 5266-CB | 5269-CB |
| All-Black Nylon, Power Indication™ | 5266-PLB | 5269-PLB |
| Orange & White Body | 5266-CO | 5269-CO |
| Gray Nylon Body | 5266-CG | 5269-CG |
| Black & White Nylon Body, Power Indication™ | 5266-PLC | 5269-PLC |
| Angle, Black & White Nylon Body | 5266-CA | 5269-CA |
| Black 2-Piece Nylon Shell | 5266-N | 5269-N |
| Flanged Inlet, White Nylon Body | 5278-C | — |
| Flanged Outlet, White Nylon Body | — | 5279-C |

Industrial Grade —15 AMP 250V 2-Pole, 3-Wire Grounding

| DESCRIPTION | CAT. NO. PLUG NEMA 6-15P  | CAT. NO. CONNECTOR NEMA 6-15R  |
|-----------------------------------|--|--|
| Black & White Nylon Body | 5666-C | 5669-C |
| High-Visibility Yellow Nylon Body | 5666-CY | 5669-CY |
| Angle, Black & White Nylon Body | 5666-CA | — |
| Flanged Inlet, White Nylon Body | 15678-C | — |
| Flanged Outlet, White Nylon Body | — | 15679-C |

For Weather Resistant Plug and Connector Boots, see page M4.

SPECIFICATIONS AND FEATURES

Hospital Grade

- Unmatched quality and performance confirmed by rigorous UL 498 testing
- Clearly identified by green dot

Industrial Grade


- Rugged construction resists impact, sunlight, chemicals and rough use
- All contacts are solid one-piece brass for better conductivity
- Triple-wipe, heavy-duty power contacts set in deep pockets to resist damage
- Captive, color-coded brass #8 terminal screws
- Unique cord clamp accepts wide range of cord sizes (.245"-.700"), providing secure grip without damaging cord jacket: SVT 18-3 to SO 14-3 with strain relief insert, up to ST 10-3 when strain relief insert is removed.
- Power Indication™ devices equipped with green neon bulb rated at 30,000 hours (24/7) for 3.5 years

TESTING AND CODE COMPLIANCE


- Meet NEMA WD 1 & 6, ANSI requirements
- UL Listed & meets UL Fed. Spec. requirements: Industrial Plugs & Connectors (File #13393); Hospital Grade (UL 498, File #E-13393)
- CSA Certified (File #LR-406)
- NOM Certified (#057)
- Backed by a Limited 10-Year Warranty

MATERIAL CHARACTERISTICS

Environmental: Flammability, Rated V2
Operating Temperature: -40°C to 65°C



8215-CAT




5266-C



5269-C



5278-C



20 AMP 125 and 250V


Industrial Grade Straight Blade Plugs and Connectors



8315-PLC



5366-CA






8415-CAT



6017-Y

Hospital Grade — 20 AMP 125V 2-Pole, 3-Wire Grounding






| DESCRIPTION | CAT. NO. PLUG | CAT. NO. CONNECTOR |
|---|---|--|
| | NEMA 5-20P  | NEMA 5-20R  CSA config. in Canada  |
| Hospital Grade, Black & White Body | 8315-C | 8319-C |
| Hospital Grade, Transparent Body | 8315-CT | 8319-CT |
| Hospital Grade, Power Indication™ Transparent | 8315-PLC | 8319-PLC |
| Hospital Grade Angle, Transparent Body | 8315-CAT | — |

Industrial Grade — 20 AMP 125V 2-Pole, 3-Wire Grounding

| | | |
|---|----------|----------|
| Black & White Nylon Body | 5366-C | 5369-C |
| Black & White Nylon Body, Power Indication™ | 5366-PLC | 5369-PLC |
| All-Black Nylon, Power Indication™ | 5366-PLB | 5369-PLB |
| High-Visibility Yellow Nylon Body | 5366-CY | 5369-CY |
| Gray Nylon Body | 5366-CG | 5369-CG |
| Angle, Black & White Nylon Body | 5366-CA | 5369-CA |
| Flanged Inlet, White Nylon Body | 15378-C | — |
| Flanged Outlet, White Nylon Body | — | 15379-C |

Hospital Grade — 20 AMP 250V 2-Pole, 3-Wire Grounding

| DESCRIPTION | CAT. NO. PLUG | CAT. NO. CONNECTOR |
|--|---|--|
| | NEMA 6-20P  | NEMA 6-20R  CSA config. in Canada  |
| Hospital Grade Angle, Transparent Body | 8415-CAT | — |

Industrial Grade — 20 AMP 250V 2-Pole, 3-Wire Grounding

| | | |
|-----------------------------------|---------|---------|
| Black & White Nylon Body | 5466-C | 5469-C |
| High-Visibility Yellow Nylon Body | 5466-CY | 5469-CY |
| Flanged Inlet, White Nylon Body | 5478-C | — |
| Flanged Outlet, White Nylon Body | — | 5479-C |

Weather-Resistant Boots

Our outstanding Industrial Grade boots feature a triple-seal design to protect straight blade and locking plugs and connectors against the harmful effects of dirt and moisture in harsh environments. Boots are available in black or high-visibility yellow. The fluted surface and grip-ring design provide a non-slip grip even in wet conditions.

| DESCRIPTION | CAT. NO. |
|--|----------|
| Weather-Resistant Straight Blade Plug Boot, Black Rubber. For 15A & 20A Straight Blade Industrial Nylon Plugs | 6017 |
| Weather-Resistant Straight Blade Plug Boot, High Visibility Yellow Rubber. For 15A & 20A Straight Blade Industrial Nylon Plugs | 6017-Y |
| Weather-Resistant Straight Blade Connector Boot, Black Rubber. For 15A & 20A Straight Blade Industrial Nylon Connectors | 6018 |
| Weather-Resistant Straight Blade Connector Boot, High Visibility Yellow Rubber. For 15A & 20A Straight Blade Industrial Nylon Connectors | 6018-Y |

SPECIFICATIONS AND FEATURES

Hospital Grade

- Unmatched quality and performance confirmed by rigorous UL 498 testing
- Clearly identified by green dot

Industrial Grade

- Rugged construction resists impact, sunlight, chemicals and rough use
- All connector contacts are solid one-piece brass for superior conductivity
- Triple-wipe, heavy-duty power contacts set in deep pockets to resist damage
- Captive, color-coded brass #8 terminal screws
- Unique cord clamp accepts wide range of cord sizes (.245"–.700"), providing secure grip without damaging cord jacket: SVT 18-3 to SO 14-3 with strain relief insert, up to ST 10-3 when strain relief insert is removed.

- Power Indication™ devices equipped with green neon bulb rated at 30,000 hours (24/7) for 3.5 years


TESTING AND CODE COMPLIANCE

- Meet NEMA WD 1 & 6, ANSI requirements
- UL Listed & meets Fed. Spec. requirements: Industrial Plugs & Connectors (File #13393); Hospital Grade (UL 498, File #E-13393)
- CSA Certified (File #LR-406)
- NOM Certified (#057)
- Backed by a Limited 10-Year Warranty

MATERIAL CHARACTERISTICS













Environmental: Flammability, Rated V2
Operating Temperature: -40°C to 65°C

15 AMP 125 and 250V • 20 AMP 125 and 250V Industrial Grade Straight Blade Plugs and Connectors



Wetguard® Wetguard® Devices Engineered to IP66 & IP67 Watertight Standards

Wetguard Straight Blade Plugs and Connectors

| DESCRIPTION | CAT. NO. PLUG | CAT. NO. CONNECTOR |
|--|--|--|
| Rubber Yellow, 15A-125V 2-Pole, 3-Wire | 14W47 NEMA 5-15P  | 15W47 NEMA 5-15R  |
| Black Rubber, 15A-125V 2-Pole, 3-Wire | 14W47-B NEMA 5-15P  | 15W47-B NEMA 5-15R  |
| Yellow Rubber, 15A-250V 2-Pole, 3-Wire | 14W49 NEMA 6-15P  | 15W49 NEMA 6-15R  |
| Yellow Rubber, 15A-277V 2-Pole, 3-Wire | 14W34 NEMA 7-15P  | 15W34 NEMA 7-15R  |
| Yellow Rubber, 20A-125V 2-Pole, 3-Wire | 14W33 NEMA 5-20P  | 15W33 NEMA 5-20R  |
| Yellow Rubber, 20A-250V 2-Pole, 3-Wire | 14W48 NEMA 6-20P  | 15W48 NEMA 6-20R  |









Replacement Closure Cap

| DESCRIPTION | CAT. NO. |
|--|--------------|
| Replacement Female Closure Cap for use with 15A & 20A 2-pole, 3-wire devices | 50W50 |



Dustguard® Dustguard® Devices Engineered to IP44 Splashproof and Dust-Tight Standards

Dustguard Straight Blade Plugs and Connectors

| DESCRIPTION | CAT. NO. PLUG | CAT. NO. CONNECTOR |
|---|---|---|
| High-Visibility Yellow, 15A-125V 2-Pole, 3-Wire | 1447 NEMA 5-15P  | 1547 NEMA 5-15R  |
| High-Visibility Yellow, 15A-250V 2-Pole, 3-Wire | 1449 NEMA 6-15P  | 1549 NEMA 6-15R  |
| High-Visibility Yellow, 20A-125V 2-Pole, 3-Wire | 1433 NEMA 5-20P  | 1533 NEMA 5-20R  |
| High-Visibility Yellow, 20A-250V 2-Pole, 3-Wire | 1448 NEMA 6-20P  | 1548 NEMA 6-20R  |

For 15 and 20 Amp corrosion resistant straight blade devices, see pages N20–N21.

SPECIFICATIONS AND FEATURES

Wetguard

- IEC IP66 and IP 67 Rated, in accordance with IEC 529 as evaluated by UL and CSA
- NEMA Type 3, 3S, 4, 4X, 6 and 6P Ratings in accordance with UL 50 and CSA 94
- Outstanding resistance to wet and damp environments, extreme temperature variations, acids, alkalis, grease, oils and solvents
- Effective “tongue and groove” construction seals out water, moisture, dirt when plugs are mated with connectors
- Innovative strain-relief grips cables securely, keeps out water and moisture
- Cord clamp range: 18/3–10/3SO (.375"–.655")

- Non-magnetic stainless steel fast-threading assembly screws won't interfere with sensitive equipment
- Connector “hood” closure cap seals device when not in use

Dustguard

- IEC/IP44 Rated
- Developed to withstand dusty and dirty environments, cracking and fading, temperature extremes
- Rugged wiring modules have high performance 1-piece brass triple-wipe contacts, solid brass plug blades
- Self centering cord clamp accepts wide range of conductors, 18-3 SVT–12-3SO (.240"–.655")

TESTING AND CODE COMPLIANCE


- Meet NEMA WD 1 & 6, ANSI requirements
- UL Listed & meets Fed. Spec. requirements: Wetguard (File #13393), Dustguard (File #E-13393)
- CSA Certified (File #LR-406)
- NOM Certified (#057)
- Backed by a Limited 10-Year Warranty

MATERIAL CHARACTERISTICS

Environmental: Flammability, Rated V2
Operating Temperature: -40°C to 65°C



Straight Blade Plugs and Connectors




15 AMP 125 and 250V • 20 AMP 125 and 250V


Industrial Grade Straight Blade Plugs and Connectors



5256-VA



5456-VY



5459-VY

PYTHON™ PLUGS AND CONNECTORS Python™ Plugs and Connectors Feature a Hinged Design for Fast, Easy Installation and Assembly

Hospital Grade — 15 AMP 125V 2-Pole, 3-Wire Grounding

| DESCRIPTION | CAT. NO. PLUG | CAT. NO. CONNECTOR |
|------------------|---------------|--------------------|
| | NEMA 5-15P | NEMA 5-15R |
| White Nylon Body | 8256-V | 8259-V |

Industrial Grade — 15 AMP 125V 2-Pole, 3-Wire Grounding

| | | |
|--|---------|---------|
| Black Nylon Body | 5256-VB | 5259-VB |
| High-Visibility Yellow Nylon Body | 5256-VY | 5259-VY |
| Gray Nylon Body | 5256-VG | 5259-VG |
| Angle, High-Visibility Yellow Nylon Body | 5256-VA | — |

Hospital Grade — 15 AMP 250V 2-Pole, 3-Wire Grounding

| DESCRIPTION | CAT. NO. PLUG | CAT. NO. CONNECTOR |
|------------------|---------------|--------------------|
| | NEMA 6-15P | NEMA 6-15R |
| White Nylon Body | 8656-V | 8659-V |

Industrial Grade — 15 AMP 250V 2-Pole, 3-Wire Grounding

| | | |
|--|----------|----------|
| High-Visibility Yellow Nylon Body | 15656-VY | 15659-VY |
| Angle, High-Visibility Yellow Nylon Body | 15656-VA | — |

Hospital Grade — 20 AMP 125V 2-Pole, 3-Wire Grounding

| DESCRIPTION | CAT. NO. PLUG | CAT. NO. CONNECTOR |
|------------------|---------------|---|
| | NEMA 5-20P | NEMA 5-20R <small>CSA config. in Canada</small> |
| White Nylon Body | 8356-V | 8359-V |

Industrial Grade — 20 AMP 125V 2-Pole, 3-Wire Grounding

| | | |
|--|---------|---------|
| Black Nylon Body | 5356-VB | 5359-VB |
| High-Visibility Yellow Nylon Body | 5356-VY | 5359-VY |
| Angle, High-Visibility Yellow Nylon Body | 5356-VA | — |

Hospital Grade — 20 AMP 250V 2-Pole, 3-Wire Grounding

| DESCRIPTION | CAT. NO. PLUG | CAT. NO. CONNECTOR |
|------------------|---------------|---|
| | NEMA 6-20P | NEMA 6-20R <small>CSA config. in Canada</small> |
| White Nylon Body | 8456-V | 8459-V |

Industrial Grade — 20 AMP 250V 2-Pole, 3-Wire Grounding

| | | |
|--|---------|---------|
| High-Visibility Yellow Nylon Body | 5456-VY | 5459-VY |
| Angle, High-Visibility Yellow Nylon Body | 5456-VA | — |

SPECIFICATIONS AND FEATURES

Python

- Tough high-impact body
- Hinged design delivers fast, easy installation and assembly
- Triple-drive screws for easy wiring — Standard, Phillips, Robertson
- Wide Cord Clamp Range, 18-3 SVT-10-3 ST, (.245"-.700")


TESTING AND CODE COMPLIANCE

- Meet NEMA WD 1 & 6, ANSI requirements
- UL Listed & meets Fed. Spec. requirements: Industrial Plugs & Connectors (File #13393); Hospital Grade (UL 498, File #E-13393)
- CSA Certified (File #LR-406)
- NOM Certified (#057)
- Backed by a Limited 10-Year Warranty

MATERIAL CHARACTERISTICS

Environmental: Flammability, Rated V2
Operating Temperature: -40°C to 65°C













15 AMP 125 and 250V • 20 AMP 125 and 250V Industrial Grade Straight Blade Plugs and Connectors



Integrated Power Inlets and Outlets with Weather-Resistant Covers

- Engineered to IP 64 and NEMA 3R Protection Ratings
- Suitable for Industrial Indoor and Outdoor Use

Integrated Power Inlets and Outlets with Weather-Resistant Covers Gray, Glass-Filled Thermoplastic Cover and White, Nylon Device

| DESCRIPTION | CAT. NO. FLANGED INLET | CAT. NO. FLANGED OUTLET |
|--|--|---|
| Standard Wire Wells, 15A-125V 2-Pole, 3-Wire | 5278-CWP NEMA 5-15P  | 5279-CWP NEMA 5-15R  |
| Slots for Fork Terminals, 15A-125V 2-Pole, 3-Wire | 5278-FWP NEMA 5-15P  | 5279-FWP NEMA 5-15R  |
| Standard Wire Wells, 15A-250V 2-Pole, 3-Wire | 15678-CWP NEMA 6-15P  | 15679-CWP NEMA 6-15R  |
| Standard Wire Wells, 20A-125V 2-Pole, 3-Wire | 15378-CWP NEMA 5-20P  | 15379-CWP NEMA 5-20R  <small>CSA config. in Canada</small>  |
| Standard Wire Wells, 20A-250V 2-Pole, 3-Wire | 5478-CWP NEMA 6-20P  | 5479-CWP NEMA 6-20R  <small>CSA config. in Canada</small>  |

Note: For locking configurations, please see Section N.



5278-CWP



5278-CWP Shown Open



5279-CWP Shown Open

SPECIFICATIONS AND FEATURES


- Glass-filled thermoplastic cover and plate provide outstanding impact resistance and durability
- UL 94 VO Flammability Rating
- IP 64 Suitability rating protects against dust particles and splashing water
- NEMA Type-3R enclosure Rating ensures protection against rain, sleet and damage from external ice formations
- Available with standard wire wells or with slots that accept fork terminals
- Dual gaskets, one under plate and one under lid, for weather-resistant fit
- Stainless steel external hardware resists corrosive effects of moisture
- Large thumb-tab makes it easy to open cover with gloved hand
- Mounts to panels or FS/FD boxes
- UL Listed and CSA Certified for wet locations with cover closed

TESTING AND CODE COMPLIANCE

- UL Listed (File #-13397)
- CSA Certified (File #LR-16347)
- NOM Certified (#057)
- IP 64 Suitability Rating (protected against dust and splashing water)
- NEMA Type-3R Enclosure Rating when properly installed (protected against rain, sleet and damage from external ice formations)
- Backed by a Limited 2-Year Warranty

MATERIAL CHARACTERISTICS


Environmental: VO Flammability Rating per UL 94
Operating Temperature: -40°C to 75°C




Industrial Grade Straight Blade Plugs and Connectors

20 AMP Power Plugs

20 AMP 125/250V Straight Blade Plugs 3-Pole 3-Wire Non-Grounding


| DESCRIPTION | CAT. NO. | MATCHING RECEPTACLE | NEMA CONFIG. |
|---------------|----------|---------------------|--|
| Straight Plug | 9151-N | 5032 5032-1 | 10-20P  |

20 AMP 120/208V 4-Pole, 4-Wire, 3ØY Non-Grounding


| | | | |
|---------------|--------|---------|--|
| Straight Plug | 7251-C | 7250-FR | 18-20P  |
|---------------|--------|---------|--|

30 AMP Nylon Angle Plugs


30 AMP 125V 2-Pole 3-Wire Grounding

| DESCRIPTION | CAT. NO. | MATCHING RECEPTACLE | NEMA CONFIG. |
|-------------|----------|---------------------|---|
| Angle Plug | 9530-P | 5371 5371-IG | 5-30P  |


30 AMP 250V 2-Pole 3-Wire Grounding

| | | | |
|------------|--------|-----------------|---|
| Angle Plug | 9630-P | 5372 5372-IG | 6-30P  |
|------------|--------|-----------------|---|


30 AMP 277V 2-Pole 3-Wire Grounding

| | | | |
|------------|--|--------|---|
| Angle Plug | | 9730-A | 7-30P  |
|------------|--|--------|---|

30 AMP 125/250V 3-Pole 3-Wire Non-Grounding

| | | | |
|------------|--------|------|--|
| Angle Plug | 9332-P | 5207 | 10-30P  |
|------------|--------|------|--|


30 AMP 125/250V 3-Pole 4-Wire Grounding

| | | | |
|------------|--------|-----|--|
| Angle Plug | 9432-P | 278 | 14-30P  |
|------------|--------|-----|--|

30 AMP 250V 3-Pole 4-Wire 3-Phase Grounding


| | | | |
|------------|--------|------|--|
| Angle Plug | 8432-P | 8430 | 15-30P  |
|------------|--------|------|--|

30 AMP 120/208V 4-Pole 4-Wire 3ØY Non-Grounding

| | | | |
|------------|--------|------|--|
| Angle Plug | 8332-P | 8330 | 18-30P  |
|------------|--------|------|--|



9530-P



9432-P

For more information regarding matching receptacles, refer to Receptacles, Section G.

SPECIFICATIONS AND FEATURES

- Rugged cord clamp for secure cable grip accommodates cord diameters from .625" to 1.375" and does not tear conductor jacket
- Made of tough, heavy-duty nylon for long service life
- Devices feature heavy-sectioned dead-front right-angle
- Pressure-clamp terminal design
- Terminals accept up to #4AWG stranded conductors
- Four-way positioning front module
- Solid brass blades for maximum conductivity


TESTING AND CODE COMPLIANCE

- UL Listed (File #13393)
- UL Test 498 (CSA 42)
- CSA Certified (File #LR-406)
- NOM Certified (#057)
- Backed by a Limited Two-Year Warranty

MATERIAL CHARACTERISTICS


Environmental: Flammability, Rated V2
Operating Temperature: -40°C to 65°C

50 AMP 125, 250, 277 125/250 and 120/208V Industrial Grade Straight Blade Plugs and Connectors




50 AMP Nylon Angle Plugs


50 AMP 125V 2-Pole 3-Wire Grounding

| DESCRIPTION | CAT. NO. | MATCHING RECEPTACLE | NEMA CONFIG. |
|-------------|----------|---------------------|--|
| Angle Plug | 9550-P | 5373 | 5-50P  |


50 AMP 250V 2-Pole 3-Wire Grounding

| | | | |
|------------|--------|-----------------|--|
| Angle Plug | 9650-P | 5374 5374-IG | 6-50P  |
|------------|--------|-----------------|--|


50 AMP 277V 2-Pole 3-Wire Grounding

| | | | |
|------------|--------|--------|--|
| Angle Plug | 9750-P | 9750-A | 7-50P  |
|------------|--------|--------|--|


50 AMP 125/250V 3-Pole 3-Wire Non-Grounding

| | | | |
|------------|--------|------|---|
| Angle Plug | 9450-P | 5206 | 10-50P  |
|------------|--------|------|---|


50 AMP 125/250V 3-Pole 4-Wire Grounding

| | | | |
|------------|--------|-----|---|
| Angle Plug | 9452-P | 279 | 14-50P  |
|------------|--------|-----|---|

50 AMP 250V 3-Pole 4-Wire 3-Phase Grounding

| | | | |
|------------|--------|-----------------|--|
| Angle Plug | 8452-P | 8450 8450-IG | 15-50P  |
|------------|--------|-----------------|--|

50 AMP 120/208V 4-Pole 4-Wire 3ØY Non-Grounding

| | | | |
|------------|--------|------|---|
| Angle Plug | 8352-P | 8350 | 18-50P  |
|------------|--------|------|---|

For more information regarding matching receptacles, refer to Receptacles, Section G.



SPECIFICATIONS AND FEATURES


- Rugged cord clamp for secure cable grip accommodates cord diameters from .625" to 1.375" and does not tear conductor jacket
- Made of tough, heavy-duty nylon for long service life
- Devices feature heavy-sectioned dead-front right-angle
- Pressure-clamp terminal design
- Terminals accept up to #4AWG stranded conductors
- Four-way positioning front module
- Solid brass blades for maximum conductivity

TESTING AND CODE COMPLIANCE

- UL Listed (File #13393)
- UL Test 498 (CSA 42)
- CSA Certified (File #LR-406)
- NOM Certified (#057)
- Backed by a Limited Two-Year Warranty

MATERIAL CHARACTERISTICS

Environmental: Flammability, Rated V2
Operating Temperature: -40°C to 65°C



60 AMP 250, 125/250 and 120/208V

Industrial Grade Straight Blade Plugs and Connectors



60 AMP Nylon Angle Plugs

60 AMP 125/250V 3-Pole 4-Wire Grounding

| DESCRIPTION | CAT. NO. | MATCHING RECEPTACLE | NEMA CONFIG. |
|-------------|----------|---------------------|--------------|
| Angle Plug | 9462-P | 9460 9460-IG | 14-60P |

60 AMP 250V 3-Pole 4-Wire 3-Phase Grounding

| | | | |
|------------|--------|------|--------|
| Angle Plug | 8462-P | 8460 | 15-60P |
|------------|--------|------|--------|

60 AMP 120/208V 4-Pole 4-Wire 3ØY Non-Grounding

| | | | |
|------------|--------|------|--------|
| Angle Plug | 8362-P | 8360 | 18-60P |
|------------|--------|------|--------|

For more information regarding matching receptacles, refer to Receptacles, Section G.



SPECIFICATIONS AND FEATURES

- Rugged cord clamp for secure cable grip accommodates cord diameters from .625" to 1.375" and does not tear conductor jacket
- Made of tough, heavy-duty nylon for long service life
- Devices feature heavy-sectioned dead-front right-angle
- Pressure-clamp terminal design
- Terminals accept up to #4AWG stranded conductors
- Four-way positioning front module
- Solid brass blades for maximum conductivity

TESTING AND CODE COMPLIANCE


- UL Listed (File #13393)
- UL Test 498 (CSA 42)
- CSA Certified (File #LR-406)
- NOM Certified (#057)
- Backed by a Limited Two-Year Warranty

MATERIAL CHARACTERISTICS

Environmental: Flammability, Rated V2
 Operating Temperature: -40°C to 65°C

STRAIGHT BLADE PLUG AND CONNECTOR FEATURES


Commercial Grade Straight Blade Plugs and Connectors



LEVITON OFFERS A LARGE SELECTION OF 15, 20, 30 AND 50 AMP COMMERCIAL GRADE STRAIGHT BLADE PLUGS AND CONNECTORS, AVAILABLE IN A WIDE VARIETY OF FEATURES.

Leviton's Commercial Grade Straight Blade Plugs and Connectors are rugged performers. They are moisture, chemical and abuse-resistant. And they're ideal for indoor and outdoor use.

- EPTR rubber-backed plugs and connectors stand up to rough use, protect against dirt and moisture
- Deep-slotted, backed-out terminal screws draw backwire clamps securely over stripped leads for maximum conductivity



Built-in cord grip adjusts automatically for use with No. 18-2 through No. 12-3 cords

Triple-drive head screws — $\frac{3}{16}$ " (4.76mm.) Standard, Phillips, Robertson

NEMA Configuration and rating molded into front module for easy identification

Husk and module keyed for easy alignment during wiring



PVC Grounding Plug
Resists moisture and chemicals; suited for outdoor cords.
515PV shown



PVC Grounding Connector
Unique dimpled body design provides secure grip; resists abuse.
515CV shown



PVC Angle Grounding Plug
Speed-thread assembly screws tighten with just a few quick turns; impact-resistant.
515AN shown



Armored Grounding Plug
Ideal for shops, garages and rough-duty work with hard floors.
520PA shown



Armored Grounding Connector
Two-piece strain-relief clamp center cord for neat installation; able to take hard punishment.
615CA shown



Rubber Grounding Connector
Provides protection against rough use, dirt, moisture and temperature extremes.
515CR shown



Dual Power Vinyl Angle Plug
Thermoplastic body for long life; interchangeable blade configurations.
930 shown



Motor Base Inlet
Contains heavy gauge brass blades and thermoplastic housing.
5239 shown

Straight Blade Plugs and Connectors




15 AMP 125 and 250V

Commercial Grade Straight Blade Plugs and Connectors



515CV



515AN



5239

15 AMP Plugs, Angle Plugs, Armored Plugs and Connectors

15 AMP 125V 2-Pole 3-Wire Grounding

| DESCRIPTION | CAT. NO. | COLOR | NEMA CONFIG. |
|-----------------------------|----------|--------------------|--------------|
| PVC Grounding Plug | 515PV | Yellow | 5-15P 5-15R |
| Armored Grounding Plug | 515PA | Yellow/Steel Armor | |
| Rubber Grounding Plug | 515PR | Black | |
| PVC Angle Grounding Plug | 515AN | White | |
| PVC Grounding Connector | 515CV | Yellow | |
| Armored Grounding Connector | 515CA | Yellow/Steel Armor | |
| Rubber Grounding Connector | 515CR | Black | |
| Motor Base Inlet | 5239 | Black | |

15 AMP 250V 2-Pole 3-Wire Grounding

| DESCRIPTION | CAT. NO. | COLOR | NEMA CONFIG. |
|-----------------------------|----------|--------------------|--------------|
| PVC Grounding Plug | 615PV | Yellow | 6-15P 6-15R |
| Armored Grounding Plug | 615PA | Yellow/Steel Armor | |
| Armored Grounding Connector | 615CA | Yellow/Steel Armor | |
| Motor Base Inlet | 5240 | Black | |

SPECIFICATIONS AND FEATURES

- Triple-drive head screws — Standard, Phillips, Robertson
 - NEMA configuration number & rating molded on face of device for easy identification
 - Rubber body is dirt and moisture resistant
 - Deep-slotted, backed out terminal screws draw backwire clamps securely for maximum conductivity
 - Husk & module keyed for easy alignment during wiring
 - Built-in cord grip adjusts automatically for use with No. 18-3 through No. 12-3 cords (.245"-.655")
 - Motor Base Inlet accepts No. 10 max. copper or copper clad wire
- PVC Plugs & Connectors**
- Rugged PVC body resists moisture and chemicals; suited for outdoor cords


- Unique dimpled body design provides a secure grip
 - Speed-thread assembly screws tighten with just a few quick turns
- Armored Plugs & Connectors**
- Ideal for shops, garages and rough-duty work with hard floors
 - Two piece strain-relief clamp center cord for neat installation
- Rubber-Back Plugs & Connectors**
- Designed to stand up to rough use
 - No internal metal parts exposed
 - Elastomeric husk provides added protection against dirt and moisture entry into the back wire port
 - Designed to operate in the widest possible temperature range

TESTING AND CODE COMPLIANCE

- Meet NEMA requirements
- UL Listed (File #E-13393)
- CSA Certified (File #LR-406)
- NOM Certified (#057)
- Backed by a Limited 10-Year Warranty

MATERIAL CHARACTERISTICS



Environmental: Flammability, Rated V2 per UL 94
 Operating Temperature: -40°C to 65°C.





Commercial Grade Straight Blade Plugs and Connectors

20 AMP Plugs, Angle Plugs, Armored Plugs and Connectors

20 AMP 125V 2-Pole 3-Wire Grounding

| DESCRIPTION | CAT. NO. | COLOR | NEMA CONFIG. |
|-----------------------------|----------|--------------------|---|
| PVC Grounding Plug | 520PV | Yellow | |
| Armored Grounding Plug | 520PA | Yellow/Steel Armor | |
| PVC Grounding Connector | 520CV | Yellow | 5-20P  5-20R  |
| Armored Grounding Connector | 520CA | Yellow/Steel Armor | |

20 AMP 250V 2-Pole 3-Wire Grounding

| DESCRIPTION | CAT. NO. | COLOR | NEMA CONFIG. |
|-----------------------------|----------|--------------------|---|
| PVC Grounding Plug | 620PV | Yellow | |
| Armored Grounding Plug | 620PA | Yellow/Steel Armor | |
| PVC Grounding Connector | 620CV | Yellow | 6-20P  6-20R  |
| Armored Grounding Connector | 620CA | Yellow/Steel Armor | |
| Rubber Back Grounding Plug | 620PR | Black | |



Straight Blade Plugs and Connectors

SPECIFICATIONS AND FEATURES

- Triple-drive head screws — Standard, Phillips, Robertson
- NEMA configuration number & rating molded on device for easy identification
- Dirt and moisture resistant
- Deep-slotted, backed out terminal screws draw backwire clamps securely for maximum conductivity
- Husk & module keyed for easy alignment during wiring
- Built-in cord grip adjusts automatically for use with No. 18-3 through No. 12-3 cords (.245"–.655")

PVC Plugs & Connectors

- Rugged PVC body resists moisture and chemicals; suited for outdoor cords
- Unique dimpled body design provides a secure grip
- Speed-thread assembly screws tighten with just a few quick turns

Armored Plugs & Connectors

- Ideal for shops, garages and rough-duty work with hard floors
- Two piece strain-relief clamp center cord for neat installation

TESTING AND CODE COMPLIANCE

- Meet NEMA requirements
- UL Listed (File #E-13393)
- CSA Certified (File #LR-406)
- NOM Certified (#057)
- Backed by a Limited 10-Year Warranty

MATERIAL CHARACTERISTICS

Environmental: Flammability, Rated V2 per UL 94
Operating Temperature: -40°C to 65°C.




30 AMP—125V/50 AMP 125V, 250V/50 AMP 250V, 125/250V/50 AMP 125/250V, 125V

Commercial Grade Straight Blade Plugs and Connectors



930



931

30 AMP/50 AMP Dual Power Attachment Plugs

30 AMP 125V/50 AMP 125V Grounding

| DESCRIPTION | CAT. NO. | COLOR | NEMA CONFIG. |
|---|----------|-------|--------------|
| Dual-Power Vinyl Angle Plug, Interchangeable Blades Cord Dia. Range .630"–1.050" | 930 | Black | 5-30P 5-50P |

30 AMP 250V/50 AMP 250V Grounding

| DESCRIPTION | CAT. NO. | COLOR | NEMA CONFIG. |
|---|----------|-------|--------------|
| Dual-Power Vinyl Angle Plug, Interchangeable Blades Cord Dia. Range .630"–1.050" | 931 | Black | 6-30P 6-50P |

30 AMP 125/250V/50 AMP 125/250V Non-Grounding

| DESCRIPTION | CAT. NO. | COLOR | NEMA CONFIG. |
|---|----------|-------|----------------|
| Dual-Power Vinyl Angle Plug, Interchangeable Blades Cord Dia. Range .687"–1.050" | 287-T | Black | 10-30P 10-50P |

30 AMP 125/250V/50 AMP 125/250V Grounding

| DESCRIPTION | CAT. NO. | COLOR | NEMA CONFIG. |
|---|----------|-------|----------------|
| Dual-Power Vinyl Angle Plug, Interchangeable Blades Cord Dia. Range .750"–1.125" | 275-T | Black | 14-30P 14-50P |

30 AMP 125V 2-Pole 3-Wire Grounding

| DESCRIPTION | CAT. NO. | COLOR | NEMA CONFIG. |
|--|----------|-------|----------------------------|
| Travel Trailer Vinyl Angle Plug, for use with 7313 Receptacle Cord Dia. Range .687"–.875" | 830-T | Black | ANSI Std. C73.13 TT-30P |

SPECIFICATIONS AND FEATURES

- Tough thermoplastic shell for long life
- Shell and bottom are hinged in front for ease of assembly
- Solid brass blades with color-coded terminals simplify wiring
- Each dual combination plug supplied with 30A blades and flat 50A blade
- Dead front right angle construction
- Interchangeable blades eliminate need for stocking different devices
- Built-in rejection feature prevents closure if blades are incorrectly positioned
- Versatile cord clamp suitable for use with Nos. 14, 12, 10, 8 and 6 AWG round cord and Nos. 10/3 SRDT, 8/2-10/1 SRDT and 6/2-8/1 flat wire
- Wiring stripping gauge molded into plug cover

TESTING AND CODE COMPLIANCE

- Meet NEMA requirements
- UL Listed (File #13393)
- CSA Certified (File #LR-406)
- NOM Certified (File #057)
- Backed by a Limited 10-Year Warranty

MATERIAL CHARACTERISTICS

Environmental: Flammability, Rated V2 per UL 94
Operating Temperature: -40°C to 65°C



Residential Grade Straight Blade Plugs and Connectors

10 AMP and 15 AMP Parallel Plugs and Connectors

Easy Wire Plugs

| DESCRIPTION | CAT. NO. | COLOR | CORD DIA. (inches) | WIRE GAUGE (stranded) Amperage (Watts) | NEMA CONFIG. |
|---------------|------------------------------|-------------------------|--------------------|--|---------------------|
| Non-Polarized | 321 321-W | Brown White | | #16/2 HPN, 15A (1875 Watts) #18/2 HPN, 10A (1250 Watts) | 1-15P Non-Polarized |
| Polarized | 321-P* 321-PW* | Brown White | | #18/2 SPT-1, 10A (1250 Watts) #18/2 SPT-2, 10A (1250 Watts) | 1-15P Polarized |
| Non-Polarized | 123 123-I 123-W | Brown Ivory White | | #18/2 SPT-1, 10A (1250 Watts) | 1-15P Non-Polarized |
| Polarized | 123-P* 123-PI* 123-PW* | Brown Ivory White | | #20/2 XT, 3A (375 Watts) | 1-15P Polarized |

*Packed 500 Bulk

15 AMP 125V 2-Pole, 2-Wire

| DESCRIPTION | CAT. NO. | COLOR | CORD DIA. (inches) | WIRE GAUGE (stranded) | NEMA CONFIG. |
|--|-----------------------------|-------------------------|--------------------|--------------------------------|-----------------|
| Polarized Light Duty Clamptite Plug | 101 101-W 101-E | Brown White Black | Up to .250 | No. 20, 18, 16 Flat or Rounded | |
| <i>Note: Consult factory for availability of non-polarized version</i> | | | | | |
| Polarized Light Duty Clamptite Connector | 102 102-W 102-E | Brown White Black | Up to .250 | No. 20, 18, 16 Flat or Rounded | |
| Non-Polarized Heavy-Duty PVC Plug | 115PV | Yellow | | | |
| Non-Polarized Heavy-Duty TPE Rubber Plug | 115PR | Black | .245-.655" | AWG 18-2 to 12-2 cable. | |
| Non-Polarized Short Flat Vinyl Plug★ | 48643 48643-W 48643-E | Brown White Black | .375 max. | 18-14 | 1-15P Polarized |
| Polarized Angle Vinyl Plug★ | 638 638-B 638-W | Black Brown White | .343 max. | 16 max. | 1-15R Polarized |
| Non-Polarized Round Vinyl Handle Plug, w/Cord Clamp★ | 48646 | Black | .437 max. | 18-14 | |
| Non-Polarized Vinyl Connector, w/Cord Clamp★ | 612† | Black | .437 max. | 14 max. | |
| Non-Polarized Round Vinyl Handle Plug, w/Spring Blades★ | 48642 | Black | .375 max. | 18-14 | |

†Not UL Listed. For replacement use only.
CSA Certified except where indicated by ★

SPECIFICATIONS AND FEATURES




- Brass plug blades and connector contacts for maximum conductivity
- Armored devices have heavily plated steel shields and cord clamps
- Vinyl devices resist chipping, cracking, oils, grease and acids
- Rubber devices resist cold, abrasion, grease, oils, acids and impact
- Plastic devices resist grease, oils and acids

TESTING AND CODE COMPLIANCE

- Meet NEMA requirements (1-15P)
- UL Listed (File #E-13393)
- CSA Certified
- NOM Certified (#057)
- Backed by a Limited Two-Year Warranty

MATERIAL CHARACTERISTICS

Environmental: Flammability, Rated V2 per UL 94
Operating Temperature: -40°C to 65°C





15 AMP 125V

Residential Grade Straight Blade Plugs and Connectors



113





114



4937

15 AMP Plugs and Connectors

15 AMP 125V 2-Pole, 3-Wire Grounding

| DESCRIPTION | CAT. NO. | COLOR | CORD DIA. (inches) | WIRE GAUGE (stranded) | NEMA CONFIG. |
|---|----------|-------|--------------------|-----------------------------------|---|
| Vinyl Handle Plug, w/Cord Clamp★ | 48648 | Black | .437 max. | 18-14 | 5-15P  |
| Vinyl Connector, w/ Steel Cord Clamp | 617 | Black | .437 max. | 16 max. | |
| Rubber Plug w/Vinyl Inner Assembly | 113 | Black | .396-.562 | 18-14 | 5-15R  |
| Rubber Connector mates w/No. 113 above | 114 | Black | .396-.562 | 18-14 | |
| Weatherproof Inlet on Flush Mount Wallplate with Aluminum Cover | 4937 | | | No. 10 max. copper or copper clad | |

CSA Certified except where indicated by ★

Straight Blade Plugs and Connectors

SPECIFICATIONS AND FEATURES

- Double wipe brass contacts for maximum conductivity and blade retention

TESTING AND CODE COMPLIANCE

- Meet NEMA requirements
- UL Listed (File #E-13393)
- CSA Certified (File #LR-406)
- NOM Certified (#057)
- Backed by a Limited Two-Year Warranty

MATERIAL CHARACTERISTICS

Environmental: Flammability, Rated V2 per UL 94
 Operating Temperature: -40°C to 65°C