

Electrical, Hanging and Miscellaneous Options



Availability

Listed below are the major electrical and other options available for Lithonia Lighting commercial fixtures. The matrix shows the availability of each option within specific fixture families.

Additional options and accessories are available. Contact your Lithonia Lighting sales representative for information.

- Option available on **all models**.
- Option available on **most models**; consult factory for exceptions.

Commercial Fixtures

| | Option Designation | PMOX PM3X | M VRS | SSH | AW | CA | SB | LB CB | CS | CLM | VC |
|---|--------------------|-----------|-------|-----|----|----|----|-------|----|-----|----|
| ELECTRICAL | | | | | | | | | | | |
| Energy-saving systems | ES | ■ | □ | □ | ■ | □ | □ | ■ | ■ | ■ | ■ |
| Ballast options (page 115) | — | □ | □ | □ | □ | □ | □ | □ | □ | □ | □ |
| Dimming ballasts | — | □ | □ | □ | □ | □ | □ | ■ | ■ | □ | □ |
| Multivolt ballast (120-277V range) ¹ | MVOLT | □ | □ | □ | □ | □ | □ | □ | □ | □ | □ |
| Emergency lighting ² | EL, EL14 | ■ | ■ | □ | ■ | ■ | □ | ■ | ■ | □ | ■ |
| Fusing | GLR/GMF | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Radio interference filter (page 116) | RIF | ■ | ■ | □ | ■ | □ | ■ | ■ | ■ | □ | ■ |
| HANGING DEVICES | | | | | | | | | | | |
| Swivel-stem hanger (page 117) | SQ_ | □ | | | □ | ■ | | ■ | ■ | ■ | ■ |
| Double-stem hanger (page 117) | DSH24 | | | □ | □ | | □ | □ | | □ | |
| Ceiling spacer (page 117) | 1B | □ | | | □ | ■ | | ■ | ■ | ■ | ■ |
| Hooker® hanger (page 117) | HRC/HRC1 | | | | | | | ■ | | | |
| Single stem rod | SQRH_ | | | | | | | | | | |
| MISCELLANEOUS | | | | | | | | | | | |
| 95% reflective silver (page 108) | SSR | □ | □ | | | | | □ | | | |
| Tamper-resistant (page 116) | TPS | | □ | ■ | | | | | | | |
| Spring-loaded latch (page 116) | SLL | □ | □ | | | | | | | | |

NOTES:

- 1 Consult factory for availability.
- 2 For CSA emergency lighting, add prefix B50C.

Order hanging devices as accessories, using separate catalog numbers. Order options by adding suffix to catalog number, unless otherwise noted.

Metric Availability

Metric versions of some surface fluorescent fixtures are available. Consult your Lithonia Lighting sales representative.


Electrical, Hanging and Miscellaneous Options

Availability

Listed are the major electrical and other options available for Lithonia Lighting strip and industrial fixtures. The matrix shows the availability of each option within specific families.

Additional options and accessories are available. Contact your Lithonia Lighting sales representative for information.

- Option available on **all models**.
- Option available on **most models**; consult factory for exceptions.



Strips and Industrials

| Designation | SM | SS SST | AF AFP | PV | EJS EJD | L LA | DMW VRI | DMS DMSW | DM | RR CRR CRRS | IB | HB5 HBB | MS8 MS5HB | MS5 MS5SS | S | C | UNS UND |
|---|--------------------|-----------|-----------|----|------------|---------|------------|-------------|----|-------------------|----|------------|--------------|--------------|---|---|------------|
| ELECTRICAL | | | | | | | | | | | | | | | | | |
| Plug-in (page 114) | PLR_G/PLF_G | ■ | ■ | ■ | ■ | ■ | | | | ■ | | | □ | □ | ■ | ■ | ■ |
| Tandem quick-connect (page 114) | TWP | □ | □ | ■ | □ | □ | | | | ■ | | | | | □ | □ | ■ |
| Emergency lighting (page 116) ¹ | EL, EL14 | □ | □ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | □ | ■ | □ | □ | □ | ■ | ■ |
| Fusing (page 115) | GLR/GMF | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Radio interference filter (page 116) | RIF | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Cordset, 120V (U-ground plug) (page 116) | CS1 | ■ | ■ | ■ | ■ | ■ | | | | | □ | □ | □ | | ■ | ■ | ■ |
| Cordset, 120V (twist-lock grounded plug) (page 116) | CS3 | ■ | ■ | ■ | ■ | ■ | | | | | □ | □ | □ | | ■ | ■ | ■ |
| Cordset, 277V (U-ground plug) (page 116) | CS7 | ■ | ■ | ■ | ■ | ■ | | | | | □ | □ | □ | | ■ | ■ | ■ |
| Cordset, 277V (twist-lock grounded plug) (page 116) | CS11 | ■ | ■ | ■ | ■ | ■ | | | | | □ | □ | □ | | ■ | ■ | ■ |
| HANGING DEVICES | | | | | | | | | | | | | | | | | |
| Tong (slide clamp) hanger (page 117) | THUN | | | ■ | ■ | □ | | | | | | | | | | | □ |
| | TH2UN | | | | | □ | | | | | | | | | | | □ |
| Hooker® hanger (page 117) | THC | | □ | | | ■ | | | | | | | | | | | ■ |
| | HR_ | | | ■ | ■ | □ | □ | | | | | | | | | | □ |
| Swivel-stem hanger (page 117) | SQ_ | □ | □ | ■ | ■ | ■ | ■ | □ | □ | □ | | | ■ | ■ | ■ | ■ | ■ |
| Double-stem hanger (page 117) ² | DSH24 | | □ | □ | □ | □ | □ | | | | | | | | □ | □ | □ |
| Ceiling spacer (page 117) | 1B | □ | □ | ■ | ■ | □ | □ | | | | | | ■ | ■ | ■ | ■ | ■ |
| Chain hanger (page 117) | HC36 | | □ | ■ | ■ | □ | ■ | □ | □ | | ■ | | ■ | | ■ | ■ | □ |
| MISCELLANEOUS | | | | | | | | | | | | | | | | | |
| 95% reflective silver (page 108) | SSR | | | ■ | | ■ | | | | ■ | | | | | | | □ |
| Wireguards (page 117) | WG_ | | ■ | ■ | □ | ■ | ■ | | | | ■ | ■ | ■ | | ■ | ■ | ■ |
| Aluminum housing | AL | | ■ | | | | | ■ | | | | | | | | | ■ |

NOTES:

- 1 For CSA emergency lighting, add prefix B50C. See page XX.
- 2 Available on most 4' fixtures. Consult factory.

Order hanging devices and wireguard accessories as separate catalog numbers. Order options by adding suffix to catalog number, unless otherwise noted.

Miscellaneous Options


Tamper-Resistant Doors

Tamper-resistant Torx head T20H (with pin) screws to secure door to housing.

- TPS** Torx head T20H screws – 1 per latch
- TP4** Torx head T20H screws – 2 latch side/ 2 hinge side

Example: **2SP G 3 40 A12 120 ES TPS**

Note: Four Torx head T20H screws are standard on VRS and VRT Series.



Spring Latches (Troffers and M Series only)

- SLL** Spring-loaded latch option
- SAL** Spring-action latch option for 2GT8 only.

Example: **2M 4 40 FW A12 120 ES SLL**

Lamps Furnished and Installed (Troffers only)

- LPESCW** Energy-saving cool white
- LPESWW** Energy-saving warm white
- LP730** Min. 70 CRI & 3000K color temp.
- LP735** Min. 70 CRI & 3500K color temp.
- LP741** Min. 70 CRI & 4100K color temp.
- LP830** Min. 80 CRI & 3000K color temp.
- LP835** Min. 80 CRI & 3500K color temp.
- LP841** Min. 80 CRI & 4100K color temp.

Example: **2SP8 G 3 32 A12 120 GEB LP735**

Radio Interference Filters

- RIF** Inductive capacitor circuit designed to minimize interference from feedback into line. 120V or 277V, 50Hz or 60Hz. Order either one per fixture (RIF1) or one per ballast (RIF2).

Example: **2SP8 G 3 32 A12 277 GEB RIF1**

- EIS** Inductive capacitor circuit designed to minimize interference from feedback into line. Meets MIL-STD 461A/462/463. Order either one per fixture (EIS1) or one per ballast (EIS2).

Example: **2SP8 G 3 32 A12 120 GEB EIS2**

Cordsets

Grounded, three-wire cordsets (black) are 6' long, 18-gauge, with SJT insulation. Prewired to fixture. Others available; consult sales representative.

- CS1** 120V, U-ground plug (NEMA 5-15P)
- CS3** 120V, twist-lock plug (NEMA L5-15P)
- CS7** 277V, U-ground plug (NEMA 7-15P)
- CS11** 277V, twist-lock plug (NEMA L7-15P)
- CS24** 347V, twist-lock plug (NEMA L24-20P)

Example: **AF 2 96 277 CS7**



Emergency Battery Packs

Factory-installed Lithonia Emergency Systems battery pack available for most fluorescent fixtures. See Emergency Systems section for lamp and ballast compatibility. Addition of an emergency option may increase fixture depth in some 2'x2' troffers. Consult factory.

- | <i>UL Listed</i> | <i>CSA Certified</i> | |
|------------------|----------------------|---|
| EL | B100C | Fixture equipped for one-lamp emergency operation of 4' lamps. (PS300 installed) |
| EL5 | B90C | Fixture equipped for one-lamp emergency operation of 4' lamps. (PS500 installed) |
| EL6 | B70C | Fixture equipped for one-lamp or two-lamp emergency operation of 4' lamps and one-lamp emergency operation of 8' lamps. (PS600 installed) |
| EL14 | B50C | Fixture equipped for one-lamp or two-lamp emergency operation of 4' lamps and one-lamp operation of 8' lamps. (PS1400 installed) |
| EM | CEM | Inverter only option. Fixture labeled for emergency use, no integral ballast. |

Add suffix **DW** to catalog number to specify damp/wet listing. UL Listed only. Example: **EL6DW**

Packaging

JP – Job Pack Consult factory for availability.

Job-site load of fixtures on pallets, wrapped without individual cartons. Secured to pallet.

- No carton disposal.
- Faster and easier to unload.
- Superior protection – reduces handling damage.
- Paramax® and other Lithonia troffers G grid and MT modular trim only, packed with end protectors, secured to pallet by heavy-duty plastic.
- Industrials and strips protected by heavy-duty corrugated sheet and secured to pallet. Reflectors packed separately.

Add suffix **JP** to fixture catalog number. Factory will determine number of fixtures per pallet.

Example: **2GT8 4 32 A12 120 GEB JP**



Miscellaneous Options


Wireguards (Order separately)

14-gauge baked white enamel, 4' long. Order two for 8' fixtures.

For use with: Catalog number:

| | |
|-----------------------------|----------------|
| UN (with UNASR48 reflector) | WGUNASR |
| 2UN (9" wide) | WG2UN |
| UNS/UND | WGCUN |
| C (with CASR48 reflector) | WGCASR |
| C (with CSMR48 reflector) | WGCSMR |
| S (with SASR48 reflector) | WGSASR |
| S (with SSMR48 reflector) | WGSMSR |
| S (without reflector) | WGS |
| AF, PV | WGAFPV |
| EJ (12" wide) | WGJ |
| 2EJ (16" wide) | WG2EJ |
| L | WGL |

For optional 11-gauge construction, add suffix 11 to catalog number. Example: **WGSASR11**



Swivel-Stem Hangers (Order separately)


SQ Complete assembly with stem up to 48" (consult factory for longer lengths). Specify stem length in 2" increments and adjust as needed. 5/8" O.D. stem. Swivels 30° from vertical in any direction. Example: **SQ24**

HDSQ Complete heavy-duty assembly. Specify length in 2" increments and adjust as needed, swivels 45° from vertical. Example: **HDSQ36**

ST Pipe stem only. Specify length up to 60". Example: **ST18**

Q Canopy, offset bar and parts only.

ST_TBE Pipe stem only, threaded both ends. Coupler included. Specify length from 6" to 60". Example: **ST48TBE**.



Ceiling Spacer (Order separately)

1B Hanger spaces fixtures 1½" to 2½" from ceiling. For unit mounting, order two per fixture; for row mounting, order one per fixture plus one per row. Standard pack: 2, 20, 100.



Chain Hangers (Order separately)

HC Wire hook and 36" chain set, option or accessory. One pair per fixture furnished. Not compatible with fixtures over 5" wide.

Example: **UN 2 32 120 HC** or **HC36** (accessory)



Tong Hangers (Order separately)

Order by channel width. For unit or row mounting, order two per fixture. All tong (slide clamp) hangers are suitable for use with 3/8" or smaller mounting rods. Rods smaller than 3/8" diameter require use of appropriate washers (supplied by others). Standard pack: 2, 100.

- THUN** Hanger for 5" channel
- TH2UN** Hanger for 9" channel
- THC** Hanger for 4¾" channel
- THK** Hanger for 4¾" channel
- THSR** Hanger for 5" channel (uses carriage bolt mounting rod)



Double-Stem Hangers (Order separately)

DSH24 Complete assembly with double canopy and two 24" stems on 10" centers. For most 4' fixtures. Other stem lengths available.




Hooker® Hangers (Order separately)

Patented, no-tools system for easy mounting to grid tee ceilings. For use with inverted tee exposed grid ceilings, nominal 1" wide.

- Hooks anywhere on grid – main tee, cross tee or intersection.
- Die-formed from heavy-gauge steel.
- Fixture can be mounted parallel or perpendicular to grid, flush to ceiling or 1½" below tee.

Two required per fixture. Standard pack: 10, 48.



lightquick[®] XD
Express delivery products.

See page 11 for details about LightQuick XD.

Description

- WGL**
- WGCUN**
- HC36**

| Number | Type of mounting | For use with |
|---------------|-------------------------|--|
| HRC | Flush to ceiling | CB, L, C and ALC fixtures with 4¾" wide and 2¼" deep channels. |
| HRC1 | Spaced 1½" from ceiling | |
| HRUN | Flush to ceiling | PV, AF fixtures with 5" channels |
| HRUN1 | Spaced 1½" from ceiling | |
| HRUNS1 | Spaced 1½" from ceiling | UN, S, EJS |

HOOKER® Hanger, Pat. No. 3,589,660