



IC-Rated 900 Lumen 5" and 6" LED Downlights, Gen 4

Delivering ultra-efficient, high-performance illumination

Juno Generation 4, IC-rated, LED recessed downlights are available with 900 brilliant lumens. Their high-lumen output is perfectly suited to residential and commercial interiors with higher ceilings.

Features include:

- Shallow profile, IC-rated 5" or 6" new construction or remodel housings fit nicely between 2x6 ceiling jobs
- Ultra-efficient 13-watt consumption, providing nearly 80% energy savings compared to equivalent incandescent lamps
- Highly advanced light engines with LEDs binned within a 3-step MacAdam Ellipse, exceeding ENERGY STAR® requirements
- Superior fixture-to-fixture color uniformity
- 90+ CRI ensures outstanding color rendering
- 50,000-hour service life



JUNO®

Juno® IC-Rated 900 Lumen 5" and 6" LED Downlights, Gen 4

Power, performance and efficiency

Juno Generation 4 LED IC-rated downlights provide 900 lumens of high-performance illumination from less than 13 watts input. They are available with 2700K, 3000K, 3500K or 4000K color temperatures and are supplied with wide-flood optics (other optics optional). ENERGY STAR® and California T24 certified when used with select LED light engines and trim components.

5" IC-Rated 900 Lumen Generation 4 LED Downlight

5" New Construction



15½" L x 9¾" W x 4¾" H
Ceiling cutout: 5¾"

IC20LED G4, 900 Lumens Series

Dedicated 5" LED new construction housing with integral light engine and choice of dimmable drivers. The eldoLED driver option delivers smooth and flicker-free deep dimming performance. Air-Loc® fully sealed housing does not require separate gasket. IC housing designed for use in IC or non-IC construction. Wide flood optic provided as standard.



Example: IC20LED G4 09LM 27K 90CRI 120 FRPC

Series	Gen	Lumens	CCT	CRI	Voltage/Driver
IC20LED 5" New Construction Housing	G4	09LM 900 Lumens	27K 2700K 30K 3000K 35K 3500K 40K 4000K	90CRI 90 CRI	120 FRPC 120V Only; Forward Phase/ ELV Dimming MVOLT EZ1* Multi-Volt (120-277V) eldoLED 0-10V, 1% dim MVOLT EZ10* Multi-Volt (120-277V) eldoLED 0-10V, 10% dim

5" Remodel



13½" L x 5¾" W x 4¾" H
Ceiling cutout: 5½"

IC20RLED G4, 900 Lumen Series

Dedicated 5" LED remodel housing with integral light engine and choice of dimmable drivers. The eldoLED driver option delivers smooth and flicker-free deep dimming performance. Air-Loc® gasket kit supplied with housing. IC housing designed for use with IC or non-IC construction. Wide flood optic provided as standard.



Example: IC20RLED G4 09LM 27K 90CRI 120 FRPC

Series	Gen	Lumens	CCT	CRI	Voltage/Driver
IC20RLED 5" Remodel Housing	G4	09LM 900 Lumens	27K 2700K 30K 3000K 35K 3500K 40K 4000K	90CRI 90 CRI	120 FRPC 120V Only; Forward Phase/ ELV Dimming MVOLT EZ1* Multi-Volt (120-277V) eldoLED 0-10V, 1% dim MVOLT EZ10* Multi-Volt (120-277V) eldoLED 0-10V, 10% dim

*A+ Capable

ENERGY STAR® and T24 certification is dependent on trim finish and LED color temperature. See housing spec sheet for specific information for each trim.

Extensive Trim Options

Juno IC-Rated 900 lumen LED recessed housings are compatible with a broad selection of Juno 5" and 6" open and lensed trims. A dedicated wall wash scoop is also available for wall wash applications.



A+ Capable configurations support A+ Certified Solutions. A+ Certified solutions from Acuity Brands help you quickly and confidently select and implement lighting systems that are both compatible and consistent. Go to www.acuitybrands.com/APIus or contact your local Acuity Brands representative for more information.



Baffle



Cone



Hyperbolic



Decorative



Wall Wash



Frosted Lens



Regressed Baffle



Dome Lens

6" IC-Rated 900 Lumen Generation 4 LED Downlights

6" New Construction



15½" L x 9¾" W x 4¾" H
Ceiling cutout: 6¾"

IC22LED G4, 900 Lumen Series

Dedicated 6" LED new construction housing with integral light engine and choice of dimmable drivers. The eldoLED driver option delivers smooth and flicker-free deep dimming performance. Air-Loc® fully sealed housing does not require separate gasket. IC housing designed for use in IC or non-IC construction. Wide flood optic provided as standard.



Example: IC22LED G4 09LM 27K 90CRI 120 FRPC

Series	Gen	Lumens	CCT	CRI	Voltage/Driver
IC22LED 6" New Construction Housing	G4	09LM 900 Lumens	27K 2700K 30K 3000K 35K 3500K 40K 4000K	90CRI 90 CRI	120 FRPC 120V Only; Forward Phase/ ELV Dimming MVOLT EZ1* Multi-Volt (120-277V) eldoLED 0-10V, 1% dim MVOLT EZ10* Multi-Volt (120-277V) eldoLED 0-10V, 10% dim

6" Remodel



14½" L x 7¾" W x 5¾" H
Ceiling cutout: 6¾"

IC22RLED G4, 900 Lumen Series

Dedicated 6" LED remodel housing with integral light engine and choice of dimmable drivers. The eldoLED driver option delivers smooth and flicker-free deep dimming performance. Air-Loc® gasket kit supplied with housing. IC housing designed for use with IC or non-IC construction. Wide flood optic provided as standard.



Example: IC22RLED G4 09LM 27K 90CRI 120 FRPC

Series	Gen	Lumens	CCT	CRI	Voltage/Driver
IC22RLED 6" Remodel Housing	G4	09LM 900 Lumens	27K 2700K 30K 3000K 35K 3500K 40K 4000K	90CRI 90 CRI	120 FRPC 120V Only; Forward Phase/ ELV Dimming MVOLT EZ1* Multi-Volt (120-277V) eldoLED 0-10V, 1% dim MVOLT EZ10* Multi-Volt (120-277V) eldoLED 0-10V, 10% dim



All trademarks referenced are property of their respective owners. Specifications subject to change without notice. Printed in the U.S.A.