

## FEATURES

- Compact, open body linear high bay offers energy efficient performance
- Easy center-ballast cover allows tool-less access without lamp or reflector removal
- Extremely low profile—only 2" overall height allows fixture to be installed without concern about obstructions
- Reflector options include uplight (recommended) or solid top with either narrow or wide distribution
- Rotary locking lampholders secure lamp in position and conceal contacts
- Easy field-installed accessories or factory-installed options for sensors, wire guards, lenses
- Quick and simple hanging systems including chain, tong, pipe hanger, or aircraft mounting
- Suitable for operation in up to a 45°C (113°F) ambient environment



## ORDERING INFORMATION

[illegible]

<sup>1</sup>Use programmed start ballast. Not recommended for use with instant start. For more occupancy/daylight harvesting sensor accessories see page 98.

<sup>2</sup>Side panels/top covers or shielding options increase height to 27 7/8"

## PRODUCT AVAILABILITY

MODEL	SOURCE	NO. OF LAMPS	UPLIGHT OPTIONS	LAMP TYPE	WIDTH	LENGTH	HEIGHT <sup>2</sup>
LHA	T5H0, T8	4	U, ST	32, 54	16 $\frac{3}{16}$ "	48"	2"
	T5H0, T8	6	U, ST	32, 54	20 $\frac{3}{16}$ "	48"	2"