

Slide-to-off dimmers



- Slide up to brighten, down to dim
- Standard size dimmer shown
- Higher capacity loads require large controls

Incandescent/halogen dimmers (small controls)

Slide-to-off dimmers

Single-pole 120V 600W	N-600- XX ¹
Single-pole 120V 1000W	N-1000- XX ¹

Magnetic low-voltage and/or Neon/cold cathode dimmers* (small controls)

Slide-to-off dimmers

Single-pole 120V 600VA (450W)	NLV-600- XX ¹
----------------------------------	---------------------------------

For neon/cold cathode dimming, consult Lutron Technical Support: Application note #25.

The stated VA (Volt-Ampere) rating includes the magnetic transformer heat losses and the lamp load. The stated W (Watt) rating is the maximum lamp wattage based on assumed 20% transformer loss.

XX¹: Architectural matte color codes, see pg. 36 (1-gang wallplate included)

3-wire fluorescent dimmers*

(also for Hi-lume® A-Series LED drivers)
(small controls)

Slide-to-off dimmers

Single-pole 120V 16A	NF-10- XX ¹
-------------------------	-------------------------------

For use with EcoSystem®, Hi-lume 3D and Hi-lume ballasts and Hi-lume A-Series LED drivers.

For more information on Hi-lume A-Series LED drivers, visit www.lutron.com/HilumeLED.

No derating required if ganged.

Adjustable low-end trim.

0-10V dimmer (current sink control)

(also for Hi-lume A-Series LED drivers)
(small controls)

Slide-to-off dimmer

Single-pole 30mA max control current	NFTV- XX ¹
---	------------------------------

Control provides dimming signal only. For dimming with on/off switching, **use with Lutron Power Pack**: PP-120H, PP-277H, or PP-347H. Consult ballast manufacturer for specific ballast current draw to determine maximum number of ballasts per control.

For information on using Lutron dimmers to control Advance Mark 7 dimming ballasts, visit www.lutron.com/advance; Universal dimming ballasts, visit www.lutron.com/universal.

For compatible 0-10V LED drivers by others, visit www.lutron.com/LED.

No derating required if ganged.

For more information on ballasts, visit www.lutron.com/ballasts. Custom ganging and derating applies, see pg.179.

*Requires neutral wire connection.