


Three and four pole contactors 9 to 105A (AC3) 25 to 140A (AC1)



Standards/Marking

IEC/EN 60947-1	CSA 22.2/14
IEC/EN 60947-4-1	NFC 63-110
IEC/EN 60947-5-1	ASE 1025
EN 50005	VDE 0660/102
UL 508	CENELEC HD 419
NEMA ICS 1	
BS 5424 & 775	

Approvals



cULus

IMQ
(up to Ith=32A)

RINA

Lloyd's
RegisterBureau
Veritas

CE



(Contact GE for details)

Order codes	●	page A.42
Auxiliary contact blocks	●	page A.44
Accessories	●	page A.44
Technical data	●	page A.88
Terminal numbering	●	page A.96
Dimensions	●	page A.120

- Control circuit: Alternating current up to 690V
Direct current up to 440V
- Terminal numbering in accordance with EN 50005 and EN 50012
- Fixing by clipping onto 35mm DIN rail EN 50022-35 or by screws
- Screws protected against accidental contact in accordance with VDE 0106 T.100, VBG4.
- Ring terminal version
- Three coil terminals
- Mounting possibilities of front/side instantaneous auxiliary contact blocks, timed auxiliary contact blocks, mechanical latch, transient suppressor block and interface modules.
- Degree of protection: IP20 to CL00 ... CL02
IP10 to CL03 ... CL10

Standard voltages

To complete the catalogue number, replace the symbol ♦ by the code corresponding to the voltage and frequency of the control circuit.

AC Coils (V)

-	1	2	9	J	K	L	6	7	N	U	Y
50/60Hz	24	42	48				220-230	240			
50 Hz				110-115	127					380-400	500
60Hz				110-120		208			277	480	600

Operating voltage limits with bifrequency coils:

With 60Hz = 0.85 to 1.1 x Us

With 50Hz = 0.8 to 1.1 x Us in continuous service (ED = 100%) with a maximum ambient temperature of 40°C

DC Coils

-	B	D	G	H	J	K	N	T
Voltage	12	24	48	60	110	120-125	220	250

DC Wide Range Coils

-	WD	WE	WG	WI	WJ	WN
Voltage	24	33	48	72	110	220

Operating voltage limits with DC coils:

Standard = 0.8 to 1.1 x Us

Wide Range = 0.7 to 1.3 x Us

AC/DC Coils

-	WD	WH	WJ	WU
Voltage	24-60	48-130	100-250	250-500

Operating voltage limits with AC/DC coils:

Standard = 0.8 to 1.1 x Us

Three pole contactors. Screw terminal

Contactors

Intro

A

B

C

D

E

F

G

H

I

X



Spare coils

Max.oper.current Non-inductive load AC1 A	Motors <480V, 3 ~ 50/60Hz AC3 A	Admissible power AC3				Electrical endurance Cat. AC3 Operations	Aux. contacts		Control circuit: Alternating current		Control circuit: Direct current		Control circuit: Coil with electronic module (AC/DC)		
		220- 240V	380- 415V	440- 480V	690V		•3 •4	•1 •2	Cat. no. ⁽¹⁾	Pack ⁽³⁾	Cat. no. ⁽¹⁾	Pack ⁽³⁾	Cat. no. ⁽¹⁾	Pack ⁽³⁾	
		kW HP	kW HP	kW HP	kW HP										
25	9	2.2 3	4 5	- 5	5.5 -	2×10 ⁶	1 0	0 1	CL00A310T ♦ CL00A301T ♦	5 5	CL00D310T ♦ CL00D301T ♦	10 10	- -	- -	
25	12	3 3	5.5 7.5	- 7.5	7.5 -	2×10 ⁶	1 0	0 1	CL01A310T ♦ CL01A301T ♦	5 5	CL01D310T ♦ CL01D301T ♦	10 10	- -	- -	
32	18	4 5.5	7.5 10	- 10	10 -	1.7×10 ⁶	1 0	0 1	CL02A310T ♦ CL02A301T ♦	5 5	CL02D310T ♦ CL02D301T ♦	10 10	- -	- -	
45	25	7.5 7.5	11 15	- 15	15 -	1.2×10 ⁶	0 0	0 0	CL03A300T ♦	5	CL03D300T ♦	10	-	-	
60	32	9 10	15 15	- 20	18.5 -	2×10 ⁶	1 0	0 1	CL04A310M ♦ CL04A301M ♦	10 10	CL04D310M ♦ CL04D301M ♦	10 10	- -	- -	
60	50	15 15	22 30	- 30	30 -	0.8×10 ⁶	0 0	0 0	CL05A300M ♦	10	CL05D300M ♦	10	-	-	
110	65	18.5 20	30 40	- 40	45 -	1.7×10 ⁶	0 0	0 0	CL07A300M ♦	1	CL07D300M ♦	1	CL07E300M ♦	1	
110	80	22 25	37 50	- 50	45 -	1.5×10 ⁶	0 0	0 0	CL08A300M ♦	1	CL08D300M ♦	1	CL08E300M ♦	1	
140	95	25 30	45 60	- 60	55 -	1.7×10 ⁶	0 0	0 0	CL09A300M ♦	1	CL09D300M ♦	1	CL09E300M ♦	1	
140	105	30 40	55 75	- 75	65 -	1.5×10 ⁶	0 0	0 0	CL10A300M ♦	1	CL10D300M ♦	1	CL10E300M ♦	1	
CL00-CL03									LB1A ♦	5	LB1D ♦	5	-	-	
CL04-CL05									LB3A ♦	5	LB3D ♦	5	-	-	
CL07-CL10									LB4A ♦	5	LB4D ♦	1	-	-	
coil + electronic module CL07E-CL10E													LB4E ♦	1	

(1) To complete the catalogue number, replace the symbol ♦ by the code corresponding to the voltage and frequency of the control circuit (see page A.41).