

TRAY CABLE

PVC Jacket

PVC/Nylon Insulation

90C -600 Volt -UL Type TC-ER

Black/White/Green Conductors



CONSTRUCTION	
Conductor	- Fully annealed stranded bare copper per ASTM B3 - Class B stranding per ASTM B8
Insulation	- Flame-retardant Polyvinyl Chloride (PVC) with clear Polyamide (nylon)
Jacket	- Lead-free, flame-retardant, sunlight-resistant Polyvinyl Chloride (PVC)

COLOR CODE CHART	
Cond. #	Color
1	Black
2	White
3	Green

Applications:

- In free air, raceways and direct burial
- In wet and dry locations
- Class 1, Division 2 industrial hazardous locations per NEC
- Permitted for Exposed Run (ER) use in accordance with NEC for 3 or more conductors

Standards:

- RoHS compliant
- IEEE 1202
- UL 83 NEC Type THHN/THWN conductors
- UL 1581
- UL 1277 Type TC-ER

Part #	AWG	Conductors	Jacket Thickness	Nom. O.D.	Lbs./M'
A11403-BWG	14	3	.045"	.345"	80
A11203-BWG	12	3	.045"	.385"	109
A11003-BWG	10	3	.045"	.450"	170

*Fittings are available for these products.

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.