

Electrical OEM Materials

Applications

Products

Documentation & Literature

Support

Where to Buy

Contact Us

United States > Energy > Electrical OEM Materials > Products > Electrical OEM Products Catalog > Heat Shrink > Single (Thin) Wall Tubing > 3M™ Heat Shrink Thin-Wall Tubing FP301-3/8-48"-Black-Hdr-12 Pcs, 48 in Length sticks with header label, 12 pieces/case

3M™ Heat Shrink Thin-Wall Tubing FP301-3/8-48"-Black-Hdr-12 Pcs, 48 in Length sticks with header label, 12 pieces/case

3M ID 80611473226    UPC# 00051128596616    Part Number FP301-3/8-48"-Black-Hdr-12 Pcs

• Print



3M™ FP-301 Heat Shrink Tubing is a general-purpose, thin-wall tubing that provides a balance of electrical, physical and chemical properties, making it perfect for industrial and military applications. This tubing has a 2:1 shrink ratio and provides flame-retardant insulation for 600V-rated applications. It has a flexible polyolefin construction that offers moisture-seal protection.

- Balances electrical, physical and chemical properties for various industrial and military applications
- Offers shrink-fit protection and strain relief of wires, solder joints, terminals and connections
- Suitable for lightweight wire-harness covering, fire-resistant covering, wire marking, wire bundling and component packaging
- Expanded I.D. of 3/8 in
- 4-ft stick with a header label
- Made of black flexible polyolefin
- Withstands temperatures of -67 to 275 degrees F (-55 to 135 degrees C)
- Flame-retardant tubing is rated for 600V applications
- UL Listed, SAE-AMS-DTL-23053/5, Class 1, 2, AMS-3636, AMS-3637, ABS, CSA Certified and RoHS 2011/65/EU Compliant

Need Help?

Questions? We can help

Contact Us

Overview	Documents
<p>3M™ Heat Shrink Tubing FP-301 is color-coded for quick and easy identification of the wire. This split-resistant, flame-retardant tubing is used as shrink-fit, electrical insulation over cable splices or terminations. The high-expansion-ratio tubing is mechanically tough, easily markable and resists cold flow. It is perfect for lightweight wire-harness covering, fire-resistant covering, wire marking, wire bundling and component packaging. It withstands temperatures of -67 to 275 degrees F (-55 to 135 degrees C). UL Listed, SAE-AMS-DTL-23053/5, Class 1, 2, AMS-3636, AMS-3637, CSA Certified and RoHS 2011/65/EU Compliant.</p>	
Specifications	
Agency Approvals	CSA, UL Recognized
Brand	3M
Color	Black
Expanded Inner Diameter	0.375 Inch
Expanded Inner Diameter (metric)	9.53 mm
Flame Retardant	Yes
Length	48 Inch
Material	Polyolefin
Minimum Expanded Tubing I. D.	3 Inch
Operating Temperature (Celsius)	-55 to 135 Degrees Celsius
Operating Temperature (Fahrenheit)	-67 to 275 Degree Fahrenheit
Product Form	48 in (1.22 m) sticks with header label
Recovered Inner Diameter	0.187 Inch
Recovered Inner Diameter (metric)	4.75 mm
RoHS 2011/65/EU Compliant	Yes

RoHS EU Comments	RoHS 2011/65/EU compliant without exemption <a href="#">*Important RoHS information</a>
Shrink Ratio	2:1
Size	0.375 Inch
Size (metric)	9.52 mm
Tubing Type	Single (Thin) Wall
UL Bug Temperature (Celsius)	125 Degrees Celsius
UL Bug Temperature (Fahrenheit)	257 Degrees Fahrenheit
UL Bug Voltage	600 Volt

Manufacturing Origin: USA

The designation that a product is Manufactured in the USA means the product undergoes substantial transformation in one of our U.S. Manufacturing plants. Some products contain imported components.

Note: 3M products offered on a government contract that require country of origin representation must be certified by 3M Trade Compliance. Contact customer service at 800-245-3573 to request a certificate.

3M OEM Electrical: [Contact Us](#)

3M: [News](#) | [Careers](#) | [Partners & Suppliers](#) | [Investor Relations](#) | [SDS Search](#) | [Transport Information Search](#) | [Help Center](#)  
[Legal Information](#) | [Privacy Policy](#)

© 3M 2016. All Rights Reserved.