



Timer Controls: Electronic Countdown Timers

EI400C | Programmable Electronic Countdown Timer



EI400C

PROGRAMMABLE ELECTRONIC COUNTDOWN TIMER

Offering a programmable countdown time between one second and 24 hours, this versatile timer can handle any application, regardless of load type. No neutral connection is required.



Features & Applications

Features

- Programmable countdown time interval from one second to 24 hours

Applications

- Bathroom Fans
- Spas

- Settings stored in non-volatile memory
 - Optional audible and/or visual warning of impending load switch OFF
 - Lockable settings help avoid unintended changes
 - Single-pole or 3-way switch compatible installation
 - Incandescent/fluorescent/CFL/LED compatible
 - Isolated switch allows timer to be used with any load type including AC and DC loads
 - Replaceable CR2 lithium battery provides up to three years of operation
 - No neutral wire connection enables easy retrofitting and quicker installation:24-hour programming allows for continuous operation
- Hot Tubs
 - Storage Closets
 - Garage Lights

Specifications

Color	Inductive	Product Height (in)
Ivory	16 A, 208-277 VAC, 50/60 Hz	4.125
Wiring Configurations	Motor	Product Height (mm)
3-Way, Single	1 HP, 120 VAC, 50/60 Hz 2 HP, 240 VAC, 50/60 Hz	104.8
Time Presets	Operating Temperature	Product Width (in)
Programmable	Max (°C)	1.75
Hold Mode Included	50	Product Width (mm)
No	Operating Temperature	44.5
Battery Type	Max (F)	Product Depth (in)
CR2 Lithium	122	1.1875
Neutral Connection Required	Operating Temperature	Product Depth (mm)
No	Min (°C)	30.2
Input Voltages Display	0	Warranty
		5-year limited

120-277 VAC, 12-28 VDC, 50/60
Hz

Incandescent Load
Ratings (Multi-Gang)

15 A, 120 VAC, 50/60 Hz
6 A, 208-277 VAC, 50/60 HZ

Operating Temperature
Min (F)

32

Product Weight (kg)

0.181

Product Weight (lbs)

0.399