



Representative Image

Current Metering

Special Markings GSA Compliance

Catalog No. THQL2145

Description: THQL 2 POLE 120/240V 10K IC 45 AMP

UPC No 783164138191

Products > Circuit Breakers > Residential Circuit Breakers > Feeder Plug-in Circuit Breakers

Q line circuit breakers are one-inch wide per pole, compact, thermal-magnetic devices designed for residential and commercial applications. The QL breakers are plug-in versions of the Q Line used for connection to load centers and lighting panels. All Q Line circuit breakers feature Quick-make / Quick-break mechanisms, common trip bars, and easy to spot trip indication to ensure safety and reliability. Q Line breakers are available in 1, 2, and 3 pole versions, can be ordered with auxiliary contact and shunt trip accessories, and can be ordered for use in HID applications.

Descriptors				
Category	Feeder Plug-in Circuit Breakers			
GO Schedule	R5			
Specifications				
Trip Style	Non-Interchangeable			
Frame Type	Q-Line			

Amperage	45 A
System Voltage	120 Vac, 120/240 Vac
Poles	2
Trip Function	Ц
Continuous Current Rated	Standard
120 Vac Interrupting Rating	10 KAIC
120/240 Vac Interrupting Rating	10 KAIC
Suitable for Reverse Feed	Yes
Product Line	O-Line (Plug-In)

Q Line (ridg iii)
Fixed
Fixed
No

No **HACR**

No

Classifications		
UL File #	E11592	

geindustrial.com Created on: 01/05/2017

Publications		
Title	Publication No.	Publication Type
Q-Line Plug-In MCCB, 100A Frame 1-, 2-, or 3- Pole, Drawing		Drawings-Outline and
1-Page fully dimensioned outline drawing in .pdf format	455C872-SH1	Dimensional

Additional Documentation: Visit our <u>Publication Library</u> to find technical documentation, time current curves, CSI Specifications and promotional literature.

geindustrial.com Created on: 01/05/2017