


# **RIGID BODIES AND ASSEMBLIES**

# LL Assembly

C13





Catalog #: RLL300

#### **APPLICATIONS**

For use with threaded rigid/IMC conduit for pulling access or to split a run into multiple directions. Removable cover allows access for maintenance and making taps and splices to conductors.

N/A

#### PRODUCT FEATURES

Durable die cast aluminum construction Premium powder coat finish Includes NBR synthetic rubber gasket Stamped aluminum cover Combination head screw

#### UL LISTED

File E331564

### NEMA

NEMA 3R rated

## NEC

2014 NEC® compliant

# GENERAL PRODUCT INFORMATION

Trade Size: 3 in.

# DRAWING DIMENSIONS

Dimension A: 12.83 in. 5.89 in. 4.53 in. Dimension B: Dimension C: 4.49 in. 11.250 in. Dimension D: Dimension E:

Tapped holes #5/16UNC-2B 3-8NPT Dimension F:

30092326213296

Dimension G: Dimension H: 3.058 in.

# PRODUCT MEASUREMENTS

179.8 (2946.4) Cubic Inches (cm3):

### **PACKAGING**

12of5:

Package Type:
Ship Carton Qty.:
Product UPC-A Labeled:
Weight (Lbs. Per/C): Carton Yes 430.00 Ship Carton Length (in.): 14.00 5.88 7.13 Ship Carton Width (in.): Ship Carton Height (in.): Ctn Weight (Lbs.): UPC Number: 4.30 092326213295