


# **TDR15-W**





UPC Code: 07847738182 Country Of Origin: Mexico

\*Eligible for ARRA funded projects > \$7,443,000

**NEMA:** 5-15R





# **TDR15-W**

#### **Brand Features**

Plug Into Safety with Leviton's Line of Tamper-Resistant (TR) Receptacles. Leviton makes it easy for you to comply with the current NEC mandate for TR Receptacles in all new residential housing. This requirement resulted from a Consumer Product Safety Commission study, that reported alleged injuries in the home caused each year by children attempting to insert foreign objects into receptacles. TR receptacles have been mandated in pediatric care areas for over 20 years and have likely been successful in preventing electrical injuries. As a long-time manufacturer of tamperresistant devices, we are pleased to be at the forefront of this safety measure with an expanded product line that encompasses a wide range of TR devices in Residential , Commercial, Industrial and Hospital Grades.

### **Item Description**

15 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, Tamper-Resistant, Decora Plus, Duplex Receptacle, Straight Blade, Commercial Grade, Self Grounding, , Back &Side Wired, Steel Strap, - WHITE

#### **Technical Information**

AC Horsepower Ratings
At Rated Voltage: 1/2 HP

**Electrical Specifications** 

Dielectric Voltage: Withstands 2000V

per UL498

**Grounding:** Self-Grounding

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 125 Volt Amperage: 15 Amp

Current Limiting: Full Rated Current

Wire: 3 Pole: 2

**Environmental Specifications** 

**Operating Temperature:** -40C to 60C **Flammability:** Rated V-2 per UL94

Material Specifications

Strap Material: Zinc-Plated Steel

Body Material: Nylon
Face Material: Nylon
Ground Clips: Brass-Plated
Terminal Screws: Brass 10-32

Color: White

Line Contacts: Brass Triple-Wipe Clamp Nuts: Zinc-Plated Steel Grounding Screw: Brass 8-32 Mechanical Specifications

Product ID: Ratings are permanently

marked on device

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

Termination: Back & Side Terminal Accom.: 14-10 AWG

Product Features
Color: White
NEMA: 5-15R


Standards and Certifications
UL 498: File E13399
Warranty: 10 Year Limited

CSA C22.2 No. 42: File 152105


**ANSI:** C-73 **NOM:** 057

**NEMA:** WD-1 & WD-6

## **Dimensional Diagram**



## Wiring Diagram



5-15R

### SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

#### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:temperature} \textbf{Teléfono: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$ 

### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

### Visit our Website at: www.leviton.com

© 2012 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/



\*Leviton is the smart choice, providing the most comprehensive range of solutions to meet the needs of today's residential, commercial and industrial buildings. Leveraging more than a century of experience, Leviton helps customers create sustainable, intelligent environments through its electrical wiring devices, network and data center connectivity solutions, and lighting energy management systems. From switches and receptacles, to daylight harvesting controls, networking systems, and equipment for charging electric vehicles, Leviton solutions help customers achieve savings in energy, time and cost, all while enhancing safety.