



Energy Advantage IR PAR30

Energy Advantage IR 50PAR30S/IRC+/SP10 120V 15PK

Due to the heat that radiates from the bulb, a minimum distance of 2 ft is required between bulb and combustible materials or objects susceptible to drying or fading

Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Operating Position	Universal [Universal]
Main Application	Outdoor (OD)
Gas Filling	GAS
Life with 3 Hour Per Day Use	3.8 a
Light Technical	
Beam Angle (Nom)	10 °
Initial lumen (Nom)	900 lm
Luminous Intensity (Nom)	12300 cd
Beam Description	Spot
Correlated Color Temperature (Nom)	2740 K
Color Rendering Index (Nom)	100
Operating and Electrical	
Power (Rated) (Nom)	50 W
Voltage (Nom)	120 V
Mechanical and Housing	
Bulb Finish	Clear (CL)

Cap-Base Information	Brass [Brass Cap]
Bulb Material	Hard Glass
Reflector Finish	Aluminized
Filament Shape	CC-8 [Axial]


Approval and Application	
Estimated Energy Cost Per Year	6.02 \$

Product Data	
Order product name	Energy Advantage IR 50PAR30S/IRC+/SP10 120V 15PK
EAN/UPC - Product	046677144999
Order code	144997
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	15
Material Nr. (12NC)	924757120301
Net Weight (Piece)	190.000 g

Energy Advantage IR PAR30

Dimensional drawing

Product	D	C (max)
Energy Advantage IR 50PAR30S/IRC+/SP10 120V 15PK	3.75 in	3.625 in



PAR30S IRC 50W E26/Brass 120V Spot 10D

