



Catalog No. TH3362SS

Description: 60A 3P HD N4X 600V FUSIBLE

UPC No 783164089301

Products > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty

· Designed for commercial and industrial applications where safety, high performance and continuity of service are essential.

- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
 - Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. ٠
 - Meets or exceeds NEMA KS1 standard for enclosed switches type HD. ٠ ٠
 - Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75°C conductor rating. ٠
 - •
 - Full cover interlocks. •

Descriptors

| Category | Heavy Duty |
|-------------|------------|
| GO Schedule | S1 |

Specifications

| Voltage | 600 AC |
|---------------------------|----------------------------|
| Amperage | 60 A |
| Poles | 3 |
| Wires | 3 |
| Fusing | Fusible |
| Enclosure | NEMA 4/4X Water/Dust-tight |
| Options | None |
| Wire Range (Cu/Al) | 14-2 |
| 480 Vac, NEC Std, 1-ph | 5.0 hp |
| 480 Vac, NEC Std, 3-ph | 15.0 hp |
| 480 Vac, Time Delay, 1-ph | 20.0 hp |
| 480 Vac, Time Delay, 3-ph | 30.0 hp |
| 600 Vac, NEC Std, 1-ph | 3.0 hp |
| 600 Vac, NEC Std, 3-ph | 15.0 hp |
| 600 Vac, Time Delay, 1-ph | 25.0 hp |
| 600 Vac, Time Delay, 3-ph | 50.0 hp |
| 125 Vdc | 5.0 hp |
| 250 Vdc | 10.0 hp |
| GSA Compliance | Yes |

Classifications

| CSA Certified | Yes |
|---------------|-----|
| UL Listed | Yes |

Dimensions

| Dimensions | |
|-----------------|---------|
| Height | 19.3 in |
| Height Depth | 5.2 in |
| Width | 9.4 in |
| Weight | 23.0 lb |

| Publications | | | |
|---|-----------------|-------------------------------------|--|
| Title | Publication No. | Publication Type | |
| Spec-Setter Safety Switches | | | |
| 36 page brochure and application guide. General Electric's Spec-Setter safety switches are available for all your disconnect needs, no matter what the application. 60A (incl. 316 Stainless) - Safety Switches | DET-845 | Brochures | |
| 1 page outline drawing in .pdf format. | 10103091-SH109 | Drawings-Outline and Dimensional | |
| Stainless Steel Safety Switches Sealed Tight - Latch it! | | | |
| | DET-842 | Brochures | |
| 2 pages. New over center latch system requires no tools to open the switch. Designed for commercial and industrial applications in corrosive environments where safety, high performance and continuity of service are essential. | | | |

Additional Documentation: Visit our <u>Publication Library</u> to find technical documentation, time current curves, CSI Specifications and promotional literature.