



GE  
Lighting

## 21250 - GE LED Candles

### LED4DCAM-C3/827

- GE energy smart® decorative LEDs offer long life and low energy use in accent lighting applications. GE energy smart® LED decorative shape and long-rated life are great for sconces and chandeliers that are left on for long periods of time.
- Bent Tip candle with medium base screw
- Lasts 13.7 years based on 3 hours per day usage
- \$13 in energy savings over the life of the bulb based on 3 hours per day usage
- Energy Star Rated
- Clear

### Product Photo



### GENERAL CHARACTERISTICS

Base Description	Medium Screw
Base Type	Screw-In
Body Color	Clear
Dimmable	Yes
Lamp Type	Candle
Primary Application	Deco
Product Technology	LED
Rated Life (Hours)	15000 h
Dimmable / Non-Dimmable	Yes
10 Digit U	4316821250
Lamp Count	1
Life in Years	13.7 yr
Replacement Watts	40 W
Requested Structure	Carton
Estimated Energy Cost per Year	0.51
Base	E26
Bulb Shape	Candles

### PHOTOMETRIC CHARACTERISTICS

Nominal Initial Lumen per Watt	75
Initial Lumens-nominal	300 lm
Color Rendering Index-CRI	80
Color Temperature	2700 K

### PRODUCT INFORMATION

Product Code	21250
Description	LED4DCAM-C3/827
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168212502
Standard Package GTIN	10043168212509
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168212502
Alternative Unit Of Measure	PACK
Standard Package Quantity	
Ean UPC	043168212502
Standard Package GTIN	30043168212503
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Inner Pack
UCC	043168212502
Alternative Unit Of Measure	EACH
Standard Package Quantity	48
Ean UPC	043168212502
Standard Package GTIN	00043168212502
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	48
Sales Unit	Each
UCC	043168212502

### DIMENSIONS

Bulb Max Overall Length-MOL	4.2 in
-----------------------------	--------

### ELECTRICAL CHARACTERISTICS

Voltage <Nom>	120 V
Input Voltage [nom]	120 V
Rated power (Watts)	4 W

### CAUTIONS & WARNINGS

Caution

Risk of Electric Shock

Suitable for damp locations

Not for use in totally enclosed or recessed luminaires

This device is not intended for use with emergency exit luminaires or emergency exit lights

Oct 10, 2017 9:53:46 AM For additional information, visit [www.gelighting.com](http://www.gelighting.com)