

Grounding Busbar – EGBA14224BB



Proper bonding is essential to create an equipotential plane between service grounds and equipment during fault and transient conditions. This equipotential plane provides a near-zero voltage differential, and serves to protect people and equipment during these events. The grounding busbar is the most popular bonding product in use today.

- Provide a convenient, single-point grounding and bonding location
- Conductors are welded to the bar using a ERICO® CADWELD® exothermic connection or are mechanically fastened by using lugs
- ERICO can design and manufacture custom bars to customer specifications

Part Number	EGBA14224BB
Material	Copper
Busbar Configuration	Busbar, Insulators and Brackets
Hole Pattern	BB
Length	24" 610 mm
Width	2" 51 mm
Thickness	1/4" 6.4 mm
Tin Plating	No
Pigtail Included	No
Standard Packaging Quantity	1 pc
UPC	78285645214
UNSPSC	26121541
ETIM	EC001470
Certifications	cULus

Additional configurations are available by special order. Note special orders may incur additional lead time.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright © 2014 ERICO International Corporation. All rights reserved.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.

