


**RIGID BODIES AND ASSEMBLIES**

**C Assembly**

**C13**



TRADE	CONDUIT	A	B	C	D	E TAPPED	F TAP	G THREAD (IN)	H THREAD (IN)	VOLUME	WEIGHT (LBS)
3/8"	ALUMINUM	2.12	1.12	1.34	3.50	1/8"	1/8"	1/8"	1/8"	4.3	0.50
1/2"	ALUMINUM	2.50	1.34	1.36	3.50	1/4"	1/4"	1/4"	1/4"	4.3	0.50
3/4"	ALUMINUM	2.87	1.36	1.36	3.50	3/8"	3/8"	3/8"	3/8"	4.3	0.50
1"	ALUMINUM	3.25	1.36	1.36	3.50	1/2"	1/2"	1/2"	1/2"	4.3	0.50
1 1/4"	ALUMINUM	3.94	1.36	1.36	3.50	5/8"	5/8"	5/8"	5/8"	4.3	0.50
1 1/2"	ALUMINUM	4.21	1.36	1.36	3.50	3/4"	3/4"	3/4"	3/4"	4.3	0.50
2"	ALUMINUM	4.89	1.36	1.36	3.50	1"	1"	1"	1"	4.3	0.50
2 1/2"	ALUMINUM	5.58	1.36	1.36	3.50	1 1/4"	1 1/4"	1 1/4"	1 1/4"	4.3	0.50
3"	ALUMINUM	6.26	1.36	1.36	3.50	1 1/2"	1 1/2"	1 1/2"	1 1/2"	4.3	0.50
3 1/2"	ALUMINUM	6.95	1.36	1.36	3.50	1 3/4"	1 3/4"	1 3/4"	1 3/4"	4.3	0.50
4"	ALUMINUM	7.63	1.36	1.36	3.50	2"	2"	2"	2"	4.3	0.50



Catalog #: RLC050

**APPLICATIONS**

For use with threaded rigid/IMC conduit for pulling access or to split a run into multiple directions. Removable cover allows access for maintenance and making taps and splices to conductors.  
N/A

**PRODUCT FEATURES**

- Durable die cast aluminum construction
- Premium powder coat finish
- Includes NBR synthetic rubber gasket
- Stamped aluminum cover
- Combination head screw

**UL LISTED**

File E331564

**NEMA**

NEMA 3R rated

**NEC**

2014 NEC® compliant

**GENERAL PRODUCT INFORMATION**

Trade Size: 1/2 in.

**DRAWING DIMENSIONS**

- Dimension A: 4.72 in.
- Dimension B: 1.34 in.
- Dimension C: 1.36 in.
- Dimension D: 3.50 in.
- Dimension E: Tapped holes #8-32UNC-2B
- Thread Spec. F: 1/2-14NPT
- Dimension G: .612 in.

**PRODUCT MEASUREMENTS**

Cubic Inches (cm<sup>3</sup>): 4.3 (70.5)

**PACKAGING**

- Package Type: Carton
- Ship Carton Qty.: 5
- Product UPC-A Labeled: Yes
- Weight (Lbs. Per/C): 29.00
- Ship Carton Length (in.): 5.00
- Ship Carton Width (in.): 3.75
- Ship Carton Height (in.): 5.50
- Ctn Weight (Lbs.): 1.45
- UPC Number: 092326211970
- I2of5: 30092326211971