
# **RIGID BODIES AND ASSEMBLIES**

### C Assembly

C13





Catalog #: RLC200

#### **APPLICATIONS**

For use with threaded rigid/IMC conduit for pulling access or to split a run into multiple directions. Removable cover allows access for maintenance and making taps and splices to conductors.

N/A

#### PRODUCT FEATURES

Durable die cast aluminum construction Premium powder coat finish Includes NBR synthetic rubber gasket Stamped aluminum cover Combination head screw

#### UL LISTED

File E331564

#### NEMA

NEMA 3R rated

#### NEC

2014 NEC® compliant

## GENERAL PRODUCT INFORMATION

Trade Size: 2 in.

# DRAWING DIMENSIONS

 Dimension A:
 10.55 in.

 Dimension B:
 3.19 in.

 Dimension C:
 3.41 in.

 Dimension D:
 8.562 in.

Dimension E: Tapped holes #12-24UNC-2B Thread Spec. F: 2-11 1/2NPT

Dimension G: 2.057 in.

# PRODUCT MEASUREMENTS

Cubic Inches (cm3): 67.0 (1098)

# PACKAGING

 Package Type:
 Carton

 Ship Carton Qty.:
 2

 Product UPC-A Labeled:
 Yes

 Weight (Lbs. Per/C):
 200.00

 Ship Carton Length (in.):
 11.00

 Ship Carton Width (in.):
 4.75

 Ship Carton Height (in.):
 7.63

 Ctn Weight (Lbs.):
 4.00

UPC Number: 092326213172 12of5: 30092326213173