




RIGID BODIES AND ASSEMBLIES

C Assembly

C13



TRADE CATALOG NUMBER	A	B	C	D	E TAPPED HOLES	F TAP	G THREADED END	VOLUME	WEIGHT
1/2"	1.31	1.18	1.18	1.18	#5/16UNC-2B	1/8"	1.18	1.18	1.18
3/4"	1.51	1.38	1.38	1.38	#3/8UNC-2B	3/16"	1.38	1.38	1.38
1"	1.71	1.58	1.58	1.58	#1/2UNC-2B	1/4"	1.58	1.58	1.58
1 1/4"	2.11	1.98	1.98	1.98	#3/4UNC-2B	5/16"	1.98	1.98	1.98
1 1/2"	2.31	2.18	2.18	2.18	#7/8UNC-2B	3/8"	2.18	2.18	2.18
2"	2.71	2.58	2.58	2.58	#1UNC-2B	1/2"	2.58	2.58	2.58
2 1/2"	3.11	2.98	2.98	2.98	#1 1/4UNC-2B	5/8"	2.98	2.98	2.98
3"	3.51	3.38	3.38	3.38	#1 1/2UNC-2B	3/4"	3.38	3.38	3.38
3 1/2"	3.91	3.78	3.78	3.78	#1 3/4UNC-2B	7/8"	3.78	3.78	3.78
4"	4.31	4.18	4.18	4.18	#2UNC-2B	1"	4.18	4.18	4.18



Catalog #: RLC250

APPLICATIONS

For use with threaded rigid/IMC conduit for pulling access or to split a run into multiple directions. Removable cover allows access for maintenance and making taps and splices to conductors.

N/A

PRODUCT FEATURES

- Durable die cast aluminum construction
- Premium powder coat finish
- Includes NBR synthetic rubber gasket
- Stamped aluminum cover
- Combination head screw

UL LISTED

File E331564

NEMA

NEMA 3R rated

NEC

2014 NEC® compliant

GENERAL PRODUCT INFORMATION

Trade Size: 2-1/2 in.

DRAWING DIMENSIONS

- Dimension A: 13.46 in.
- Dimension B: 4.49 in.
- Dimension C: 3.98 in.
- Dimension D: 11.250 in.
- Dimension E: Tapped holes #5/16UNC-2B
- Thread Spec. F: 2-1/2-8NPT
- Dimension G: 2.459 in.

PRODUCT MEASUREMENTS

Cubic Inches (cm³): 157.3 (2578)

PACKAGING

- Package Type: Carton
- Ship Carton Qty.: 1
- Product UPC-A Labeled: Yes
- Weight (Lbs. Per/C): 370.00
- Ship Carton Length (in.): 14.13
- Ship Carton Width (in.): 5.00
- Ship Carton Height (in.): 5.25
- Ctn Weight (Lbs.): 3.70
- UPC Number: 092326213189
- I2of5: 30092326213180