GE Lighting

## 75184 - GE LED Bright Stik™

### LED9LS3/827

- GE's LED Bright Stik™ illuminates spaces instantly.
- Replaces 40-100 watt incandescent, halogen, and CFL
- User longer life, lower energy alternative to CFL - Last longer than CFL (15,000hrs)
- For example, using only 10 watts of energy, saves over $82 in energy costs over the rated life of a lamp versus a standard 60-watt incandescent lamp based on $0.11 per kWh.
- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS.
- Worry-free use and disposal
- Energy Star Rated

## Product Photo

### GENERAL CHARACTERISTICS

| | |
|---|---|
| Base Description | Medium Screw |
| Base Type | Screw-In |
| Dimmable | No |
| Primary Application | General Purpose |
| Product Color | White |
| Product Technology | LED |
| Rated Life (Hours) | 15000 h |
| Dimmable / Non-Dimmable | No |
| Lamp Count | 3 |
| Life in Years | 13.7 yr |
| Replacement Watts | 60 W |
| Requested Structure | Carton |
| Estimated Energy Cost per Year | 1.08 |
| Base | E26 |
| Bulb Shape | A19 |

### PHOTOMETRIC CHARACTERISTICS

| | |
|---|---|
| Lumens per Watt (Efficacy) | 88.8 lm |
| Initial Lumens-nominal | 800 lm |
| Color Rendering Index-CRI | 80 |
| Color Temperature | 2700 K |

### PRODUCT INFORMATION

| | |
|---|---|
| Product Code | 75184 |
| Description | LED9LS3/827 |
| Alternative Unit Of Measure | EACH |
| Standard Package Quantity | 16 |
| Ean UPC | 043168751841 |
| Standard Package GTIN | 00043168751841 |
| No Of Items Per Sales Unit | 1 |
| No Of Items Per Standard Package | 16 |
| Sales Unit | Each |
| UCC | |
| Alternative Unit Of Measure | CASE |
| Standard Package Quantity | 16 |
| Ean UPC | 043168751841 |
| Standard Package GTIN | 10043168751848 |
| No Of Items Per Sales Unit | |
| No Of Items Per Standard Package | 16 |
| Sales Unit | Case |
| UCC | |

### DIMENSIONS

| | |
|---|---|
| Bulb Max Overall Length-MOL | 4.45 mm |

### ELECTRICAL CHARACTERISTICS

| | |
|---|---|
| Voltage <Nom> | 120 V |
| Input Voltage [nom] | 120 V |
| Rated power (Watts) | 9 W |

### CAUTIONS & WARNINGS

Caution

Risk of Electric Shock

Suitable for damp locations

Not for use in totally enclosed or recessed luminaires

Not for use with dimmers

This device is not intended for use with emergency exit luminaires or emergency exit lights