

POWER-STRUT® PS 619 – Square Washer

_15%"	Rod Size	Hole Size	Wt./100 pcs	Available in [DF]
	1/4"	11/32"	18	Х
	3⁄8"	7⁄16"	18	Х
	1⁄2"	9⁄16"	17	Х
	5⁄8"	11⁄16"	16	
	3⁄4"	¹³ ⁄16"	15	

Note: Indicate rod size when ordering. For example, PS 619 ½.

MATERIAL:

All Power-Strut fittings are formed in punch press dies from mild, pickled and oiled, bar or strip steel. Plain or electro-galvanized fittings meet the requirements for ASTM A575 and A-576, or ASTM A-36.

STANDARD DIMENSIONS:

Standard dimensions on all fittings are as follows except where otherwise indicated:

Fitting Thickness:	1/4"
Fitting Width:	15/8"
Hole Diameter:	9/16"
Hole Spacing:	17/8" on centers & 13/16" from ends.

STANDARD FINISH:

All Power-Strut fittings are available in painted green or electro-galvanized finish.

POWER-STRUT[®] DEFENDER[™] FINISH [DF]:

Power-Strut Defender is a combination of two proprietary material coatings conforming to ASTM standards A1046 and A1059. It features unique self-healing properties.



ORDERING INFORMATION:

When ordering, add the length or size and finish to the part number.

Approval Stamp:	