

## PRODUCT DATA SHEET

Dielectric Grease, 3.3 Wt Oz Part Number: 02085

**Product Description** 

**Applications** 

Unit Package Description Brand Generic Description 1

Net Fill **UPC** Code **Unit Dimensions** Units Per Case **Case Dimensions** Cases Per Pallet Case Weight | 2 of 5 Code Appearance Base Type Flash point (F) Flash point (C) Flammability Class - CPSC Spec Gravity Concentrate Plastic Safe Film Type **Dielectric Strength** 

Non-curing silicone compound used for electrical sealing, lubricating, protecting and insulating. Waterproofs electrical connections and components. Improves electrical performance in adverse weather conditions.

Electrical panels, outdoor lighting, scoreboards, traffic lights, high voltage poles, transformers, disconnects, switching mechanisms, electrical contacts, spark plugs, battery terminals, fasteners, o-rings, rubber and plastic parts.

6 Ounce Pressurized Tube with Select-a-BEAD® Nozzle CRC

Non-Curing Silicone Compound for Sealing, Lubricating, Protecting, And Insulating Electrical Components

3.3 Wt Oz 078254020853 8.75H x 2.25W x 2.25D in 12 8.75H x 7.37W x 7.37D in 120 6 lbs 30078254020854 **Opaque White Gel** Silicone >572°F >300°C None 0.97

Safe on Most Plastics (Test small area) Non-Curing Silicone Paste >450 Volts/Mil

and Seals O-Ri


Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.

Last revised: 1/31/2017

Page 1 of 2



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with  $^{\textcircled{m}}$  and  $^{\textcircled{m}}$  are trademarks



## **PRODUCT DATA SHEET**

NLGI Grade 2 Working Temp (F) Working Temp (C) Propellant NSF Category Code H1 **NSF Number** Military Specification Number Federal Specification Number Aerosol Flammability Level Т DOT Proper Shipping Name VOC % (Federal) <1 VOC g/L (Federal) < 0.01 VOC Lbs./Gal. (Federal) < 0.1 **VOC Category** Removal (How To) solvents.

-70 to 400°F -56.7 to 204.4°C Nitrogen 151609 Meets requirements of SAE-AS-8660 FDA-CFR-21-178.3570 Aerosols, Non-Flammable, Limited Quantity Not Regulated Remove with petroleum distillates and chlorinated

> Last revised: 1/31/2017 Page 2 of 2

and adheres to the strictest guidelines for quality in all facets of research, development and production.



and Seals O-Ri

Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



 $CRC^{\circledast}, K\&W^{\circledast}, Sta-Lube^{\circledast}, Marykate^{\circledast} and products denoted with <math display="inline">^{\circledast}$  and  $^{\intercal}$  are trademarks of CRC Industries, Inc.