


PS 2504 – Guided Square Washer



Rod Size	Hole Size	Wt./100 pcs
1/4"	11/32"	18
3/8"	7/16"	18
1/2"	9/16"	17

Note: Indicate rod size when ordering.
For example, PS 2504 1/2.

MATERIAL:

All Power-Strut fittings are formed in punch press dies from mild, pickled and oiled, bar or strip steel. Plain or electro-galvanized fittings meet the requirements for ASTM A575 and A-576, or ASTM A-36.

STANDARD DIMENSIONS:

Standard dimensions on all fittings are as follows except where otherwise indicated:

Fitting Thickness: 1/4"
 Fitting Width: 1 5/8"
 Hole Diameter: 9/16"
 Hole Spacing: 1 7/8" on centers & 13/16" from ends.

STANDARD FINISH:

All Power-Strut fittings are available in painted green or electro-galvanized finish.

POWER-STRUT® DEFENDER™ FINISH [DF]:

Power-Strut Defender is a combination of two proprietary material coatings conforming to ASTM standards A1046 and A1059. It features unique self-healing properties.



ORDERING INFORMATION:

When ordering, add the length or size and finish to the part number.

Project: _____

Approval Stamp:

Architect / Engineer: _____

Date: _____ Phone: _____

Contractor: _____

Address: _____

Notes 1: _____

Notes 2: _____