

25-Pair Power Sum Category 5e

CMR/CMP

PRODUCT DESCRIPTION

25-Pair Power Sum Category 5e UTP cables are designed to provide support for both backbone and horizontal applications. These applications include inter-closet backbone links, equipment cabling between cross-connect and hub equipment and zone distribution horizontal cabling between wiring closets and multiple work area transition points. The cable is available in CMP and CMR ratings and is UL verified to meet all requirements of ANSI/TIA-568-C.2.

APPLICATIONS


- 10BASE-T through 1000BASE-T Ethernet
- Power over Ethernet (PoE) - IEEE 802.3af
- PoE+ - IEEE 802.3at Type 1 and 2
- ATM and token ring

FEATURES

- Small outside diameter
- Vibrant insulation colors
- Flexible jacket material
- Marked in feet and meters

BENEFITS

- Handles tight installations
- Easier identification of conductors
- Ease of use during installation
- Dual length marking complies with government, military and international requirements



SPECIFICATIONS

Pair Count	25
Conductor	Solid annealed copper
AWG (mm)	24 (0.51)
Insulation	CMR: Thermoplastic CMP: FEP
Separator	Cylindrical
Jacket	CMR: Flame retardant PVC CMP: Fluoropolymer
Characteristic Impedance (Ohms)	100 ± 15
Nominal Velocity of Propagation (%)	CMR: 69 CMP: 73
Performance Compliance	UL 444 CSA C22.2 No. 214-08 UL 1666 NFPA 262 ANSI/TIA-568-C.2 Article 800, NEC (NFPA 70) RoHS-compliant
NRTL Programs	UL Verified CAT 5e UL, c(UL) Listed CMR UL, c(UL) Listed CMP

PART NUMBERS AND PHYSICAL CHARACTERISTICS

Listing	Part Number ¹	Nominal Diameter in (mm)	Approx. Weight lbs/kft (kg/km)	Package	Packages per Pallet
CMR	51-478-x5	0.57 (14.5)	144 (214)	1,000' Plywood reel	4
CMP	51-478-48	0.48 (12.2)	148 (220)	1,000' Plywood reel	4

JACKET COLORS

¹ Replace "x" with:	Blue = 2	Gray = 3	White = 4
--------------------------------	----------	----------	-----------