



FS/FD Device Boxes & Covers
T&B Catalog Number:

UPC Number: 2AFS-1
Status: 04226931510
Description: Active

1/2 Inch Shallow 2 Gang Device Box, Die Cast Aluminum, Dead End, 1 Hole, Raintight When Used with Appropriate Cover

Features

- Copper-free aluminum, stainless steel cover springs and hinge pins provide increased corrosion resistance.
- Die cast construction, boxes with securely fastened mounting plates and industrial designed covers combine to produce a rugged protective enclosure for devices on industrial and OEM applications.
- Clean cover edges provide good gasket sealing.
- Precision NPT threaded hubs allow trouble-free field installation for rigid or IMC conduit.
- Clear UL, CSA and cubic content markings speed approval by inspectors.
- Device box external hub design provides increased wiring room.

Application

- Industrial grade device boxes and raintight covers protect wiring devices, switches, electronic components, and terminal blocks in dry, damp and wet locations.
- Spacious, accessible wiring chamber provides a convenient location to maintain or change a system, pull conductors and make splices.
- Junction for branch conduits.
- Aluminum boxes can be used with steel rigid conduit.

General

Material	Die Cast Aluminum
Volume (cu.in.)	36
Number of Gangs	2

Dimension Information

Hub Size (inches)	1/2
Dimension A (inches)	4 9/16
Dimension B (inches)	4 5/8
Dimension C (inches)	13/16
Dimension D (inches)	2 1/16
Dimension E (inches)	1 3/8
Dimension F (inches)	2 7/8
Dimension G (inches)	4 3/8
Dimension H (inches)	1 15/16

Specifications

3dmodel Available on Website

Packaging

T&B Order Multiple	2
T&B Inner Pack	2
Package in Units	10
T&B Sold in UOM	Each
T&B Weight Per UOM	1.13 lbs. Each

Notes

Less than .004 copper content

Certifications



File Nbr:

E 28688

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com