



# Cable to Cable – PTC2Q2QW



nVent ERICO Cadweld graphite molds are designed and engineered for thousands of connection styles and conductor combinations.

- Forms a permanent, low resistance connection
- Provides a molecular bond
- nVent ERICO Cadweld Exothermic Connections are rated with the same current capacity as the conductor
- Portable installation equipment with no external source of power required
- Installers can be easily trained to make nVent ERICO Cadweld Exothermic Connections
- Connections can be visually inspected



|                                     |                                    |
|-------------------------------------|------------------------------------|
| Part Number                         | PTC2Q2QW                           |
| Mold Family                         | PT                                 |
| Conductor 1                         | 4/0 Concentric                     |
| Conductor 1 Outer Diameter, Nominal | 13.4 mm                            |
| Conductor 2                         | 4/0 Concentric                     |
| Conductor 2 Outer Diameter, Nominal | 13.4 mm                            |
| Split Crucible                      | No                                 |
| Wear Plates                         | Yes                                |
| Mold Only                           | No                                 |
| Welding Material                    | 200 or 200PLUSF20, Sold Separately |
| Handle Clamp                        | L160, Sold Separately              |
| Price Key                           | C                                  |
| Ease of Use                         | Preferred                          |
| Certifications                      | cULus                              |
| Standard Packaging Quantity         | 1 pc                               |
| UPC                                 | 78285654842                        |

For applications such as computer room, tunnel or other low-ventilation areas, specify a smokeless nVent ERICO Cadweld Exolon mold. Add an XL prefix to the standard mold part number when ordering (for example, a TAC2Q2Q becomes XLTAC2Q2Q). Similarly, nVent ERICO Cadweld Exolon welding material is also designated by the XL prefix (for example, 150 becomes XL150).

A gap between conductors may be required. See mold tag for more information.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

**WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2018 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.