


5" Color Preference[®] Edgelit Downlight

900 lm | 120VAC | Model 53807211 | Part DL-5-90-906-SV-D



- > For new construction or remodel use
- > Energy saving 15 watt integrated LED
- > Uses 77% less energy than equivalent 65 watt incandescent bulb
- > Select color of light with integrated switch
 - > 2700K Warm White
 - > 3000K Soft White
 - > 4000K Cool White
 - > 5000K Daylight
- > Lasts 45 years* or 50,000 hours continuous use
- > Maintenance free - No bulb replacements
- > IC rated for direct contact with insulation
- > 5 year limited warranty



SPECIFICATIONS

Model	53807211
Part	DL-5-90-906-SV-D
Description	5" Color Preference [®] Edgelit Downlight
Input Voltage (VAC)	120V
Wattage	15W
Dimmability	Triac Dimmable
Average Rated Life¹	50,000 hours
Typical Lumens²	900lm
CCT³	2700/3000/4000/5000K
Location Rating	UL Wet Location
CRI⁴	90
Beam Angle	100
Operating Temperature	Min -13°F (-25° C), Max 104°F (40° C)
Power Factor	>0.9
R9	58
DUV	-0.0027
CBCP	N/A
Operating Frequency (Hz)	60Hz

¹ Hours lifetime with 70% lumen maintenance

² Thermally stable typical lumens (±10%)

³ Thermally stable CCT (±10%)

⁴ Color rendering index/Ra

TO ORDER:

www.ETiSSL.com

Call: 1.855.ETi.SSLI

1.855.384.7754





5" Color Preference® Edgelit Downlight

900 lm | 120VAC | Model 53807211 | Part DL-5-90-906-SV-D

SHIPPING INFORMATION

Model	53807211
Part	DL-5-90-906-SV-D
UPC	849489003955
Hole Size Dimensions (in.)	Fits 5 1/8 x 5 3/4 (Outer Diameter)
Product Dimensions (W x H in.)	6 x 1 5/8
Product Dimensions (W x H cm.)	15 X 3.3
Product Weight (lbs.)	1
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	20
Master Carton Bar Code	50849489003950
Master Carton Dimensions (L x W x H in.)	1' 8 5/8" x 1' 3" x 1' 3 3/16"
Master Carton Dimensions (L x W x H cm.)	52.4 x 38.1 x 38.6
Master Carton Weight (lbs)	31.3 lbs
Pallet Quantity	600

COMPATIBILITY

Dimmers:

Lutron : DVCL-153, CTCL-153P, TGCL-153P, MACL-153M, PD-6WCL, LECL-153, SCL-153P, NTCL-250, GT-150

Leviton: 6674, 6672, IPL06-10Z, DSL06-1LZ, TSL06, RDL06

Eaton : SAL06P2

Cooper: DLC03P, SUT7, TAL06P2

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.etiled.us/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256