

Project:

Type:

Catalog #:

# 201 LED Series

# **Wrap Around Surface Mount Units**

	The state of the s
	75

## STANDARD





This surface mounted wrap around unit is designed for use in most commercial, residential, and institutional type applications. The unit provides maximum light output with minimum clearance.

#### **Construction:**

 Housing is designed from heavy gauge die formed steel and is finished in baked white enamel or polyester powder coating for maximum durability and reflectivity. Clear acrylic prismatic wrap around diffuser hinges from either side and snaps on and off for easy maintenance.

# **Electrical**

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp location


#### Mounting

Unit is equipped with knockouts and holes for pendant or surface mounting. This Fixture can be mounted individually or continuous run.

### **WARRANTY & LISTINGS**

- 5-year warranty of all electronics and housing.
- UL Certified for damp location

# **DIMENSIONS**



Fixture Length				
T12	Т8	T5	Length	
F20T12	F17T8	F14T5	24"	
F40T12	F32T8	F28T5	48"	
F96T12	F96T8		96"	

For Tandem Units: Multiply lamp length above by lamp quantity

Fixture	Bulb Spacing
2 Tube	5 3/8"
4 Tube	2 1/4"- 5 3/8" - 2 1/4"
2 Tube in 4 Tube Housing	7"

max weight= 16lbs/48 32lbs/96"

#### **Ordering Guide**

201 LED

Series

Size

201 LED

2 = 2FT
4 = 4FT
4 = 4FT
6 = 6FT
fixture

\*Higher and custom lumen packages
available upon request

\*Call Factory for lumen options of 3FT and 6FT models

Lamono	
2FT 3166 (17W) 4350 (24W) 5470 (31W) 6452 (39W)	8FT 3220 (17W) 4480 (24W) 5705 (30W) 6910 (37W)
4FT	<b>8640</b> (48W)
3220 (17W)	<b>11797</b> (70W)
<b>4480</b> (24W)	<b>13820</b> (74W)
<b>5705</b> (30W)	17280 (96W)
<b>6910</b> (37W)	23594 (140W)
<b>8640</b> (48W)	
<b>11797</b> (70W)	

Color 3K 35K 4K 5K

Options

EMB = Emergency driver

REFS = Silver Reflector

OCC-E = External Occupancy Sensor

FR = Frosted Lens over LED Board

**Specifications Subject To Change Without Notice**