

FEATURES & SPECIFICATIONS

INTENDED USE — The 6" Wafer™ LED Downlight with Switchable White provides high-quality light output and efficiency featuring a switch for easy color temperature adjustment - while eliminating the need for recessed housings. The innovative, slim design allows for easy retrofit, remodel or new construction installation from below the ceiling. The LED module maintains at least 70% light output for 50,000 hours. The Wafer LED downlight is wet location listed – making it ideal for use in a breadth of outdoor residential, hospitality, commercial and multifamily applications.

CONSTRUCTION — Aluminum die cast outer frame. Durable, powder coat paint to prevent rust. FT4 plenum rated cable connector to connect from module to remote driver box. IC rated driver with convenience and value of two remote selectable color temperature options, each with a setting choice to choose either 2700K, 3000K, and 3500K or 3000K, 4000K, and 5000K using the switch. The isolated driver integrated inside steel remote box with four 7/8" knockouts with slots for pryout. Suitable for pulling wires with the 12 cubic-inch wiring compartment to accommodate up to (6) 14 gauge insulated conductors; making the Wafer LED Downlights much easier to wire in 2in/2out (plus ground) daisy-chain applications and contractor friendly.

PATENT PENDING.

INSTALLATION — Ideal for shallow ceiling plenum; no housing required. Steel spring clip for easy installation. 6" cut out template is provided to ensure a correct sized hole is cut into ceiling for proper installation of the trim. Size of hole should not exceed 6 1/4 inches for this product. Suitable for installation in t-grid and drop ceiling applications. 2" plenum space required for installation of the remote driver box.

OPTICS — Edge-lit LED technology uses light guided plate to distribute light. Polycarbonate lens provides even illumination throughout the space.

ELECTRICAL — Connect directly to 120V Class-2 (CAN ICES-005 (B) / NMB-005 (B)) LED driver. High efficient driver with power factor > 0.9. Ambient operating temperature: -40°F (-40°C) to +104°F (+40°C). Dimming down to 10% with most standard incandescent dimers (see list of approved dimmers). Replaces 75W incandescent for 850L and 100W incandescent for 1150 lumens.

LISTINGS — CSA certified to US and Canadian safety standards. ENERGY STAR® certified product. Wet location. Air Tight certified in accordance with ASTM E283-2004. NOM Certified. Can be used to comply with California Title 24 Part 6 High Efficacy LED light Source Requirements.

WARRANTY — 5-year limited warranty. Complete warranty terms located at:

www.acuitybrands.com/support/customer-support/terms-and-conditions


Note: Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications subject to change without notice.

Specifications

Aperture:	4.9 (12.4)
Ceiling opening:	6 (15.2)
Overlap trim:	6.7 (17)
Height:	1.1 (2.8)



All dimensions are inches (centimeters) unless otherwise indicated.

Catalog Number
Notes
Type

Wafer LED Recessed Downlight

WF6

6" LED Switchable White Color Temperature


IC/Non-IC
New Construction/Remodel



Matte black

Brushed nickel

Oil-rubbed bronze



ORDERING INFORMATION

For shortest lead times, configure product using **standard options (shown in bold)**.

Example: WF6 LED 30K40K50K 90CRI MW

WF6				
Series	Lamp	CCT/W/Lumens ¹	CRI	Finish
WF6 6" wafer-thin LED downlight	LL Low Lumen	27K30K35K 2700K/10W/830L 3000K/10W/900L 3500K/10W/860L	90CRI 90CRI	MW Matte White
		30K40K50K 3000K/10W/850L 4000K/10W/920L 5000K/10W/880L		MB Matte Black
	LED LED	27K30K35K 2700K/14W/1040L 3000K/14W/1150L 3500K/14W/1110L		BN Brush Nickel
		30K40K50K 3000K/14W/1090L 4000K/14W/1190L 5000K/14W/1120L		

Accessories: Order as separate catalog number.

WF8643 Pan U	Universal new construction pan
WFJB U	Remodel joist bar
WFEXC6 SW3PIN FT4	3-Pin 6ft Cable
WFEXC10 SW3PIN FT4	3-Pin 10ft Cable
WFEXC20 SW3PIN FT4	3-Pin 20ft Cable




Notes

¹ Total system delivered lumens.

WF6 Switchable White 6" LED Wafer Module

PHOTOMETRICS


Distribution Curve	Distribution Data	Output Data	Coefficient of Utilization	Illuminance Data at 30" Above Floor for a Single Luminaire																		
WF6 LED 30K40K50K, 3000K LEDs, input watts: 14, delivered lumens: 1099, LM/W=79, test no. ISF 36826P10																						
	Ave	Lumens	Zone	Lumens	% Lamp	pf	80%			20%			50%									
							pc	50%	30%	10%	50%	30%	10%	50%	30%	10%						
	0	396	0° - 30°	306.1	27.8	0	119	119	119	116	116	116	111	111	111	50% beam - 63.5°			10% beam - 108.5°			
	5	396	0° - 40°	497.2	45.2	1	104	99	96	101	98	94	97	94	91							
	15	381	0° - 60°	864.4	78.7	2	90	84	78	88	82	77	85	80	75							
	25	350	0° - 90°	1099.0	100.0	3	79	71	65	78	70	64	75	68	63							
	35	306	90° - 120°	0.0	0.0	4	70	62	55	69	61	54	67	59	54							
	45	252	90° - 130°	0.0	0.0	5	63	54	47	62	53	47	60	52	46							
	55	194	90° - 150°	0.0	0.0	6	57	48	41	56	47	41	54	46	41							
	65	133	90° - 180°	0.0	0.0	7	51	43	36	51	42	36	49	42	36							
	75	75	0° - 180°	1099.0	*100.0	8	47	38	33	46	38	32	45	38	32							
	85	21				*Efficiency	9	43	35	29	43	35	29	41	34	29						
	90	0					10	40	32	27	39	32	27	38	31	26						
						Mounting Height	Initial FC		Center Beam		Diameter		FC		Diameter		FC					
						8.0	13.1		6.8		6.5		15.3		1.3							
						10.0	7.0		9.3		3.5		20.8		0.7							
						12.0	4.4		11.7		2.2		26.4		0.4							
						14.0	3.0		14.2		1.5		31.9		0.3							
						16.0	2.2		16.7		1.1		37.5		0.2							

WF6 Switchable White 6" LED Wafer Module

PHOTOMETRICS

Distribution Curve	Distribution Data	Output Data	Coefficient of Utilization	Illuminance Data at 30" Above Floor for a Single Luminaire																
	WF6 LL LED 27K30K35K, 2700K LEDs, input watts: 10, delivered lumens: 839, LM/W=84, test no. ISF 36826P13																			
				pf	80%			20%			50%									
				pc	50%	30%	10%	50%	30%	10%	50%	30%	10%							
				pw																
	Ave	Lumens	Zone	Lumens	% Lamp															
	0	303	0° - 30°	233.7	27.8	0	119	119	119	116	116	116	111	111	111	50% beam - 63.5°			10% beam - 108.5°	
	5	302	0° - 40°	379.7	45.2	1	104	99	96	101	98	94	97	94	91					
	15	291	0° - 60°	660.2	78.7	2	90	84	78	88	82	77	85	80	75					
	25	267	0° - 90°	839.3	100.0	3	79	71	65	78	70	64	75	68	63					
	35	234	90° - 120°	0.0	0.0	4	70	62	55	69	61	54	67	59	54					
45	192	90° - 130°	0.0	0.0	5	63	54	47	62	53	47	60	52	46						
55	148	90° - 150°	0.0	0.0	6	57	48	41	56	47	41	54	46	41						
65	102	90° - 180°	0.0	0.0	7	51	43	36	51	42	36	49	42	36						
75	57	0° - 180°	839.3	*100.0	8	47	38	33	46	38	32	45	38	32						
85	16			*Efficiency	9	43	35	29	43	35	29	41	34	29						
90	0				10	40	32	27	39	32	27	38	31	26						

WF6 LL LED 27K30K35K, 3000K LEDs, input watts: 9.7, delivered lumens: 926, LM/W=95, test no. ISF 36826P14

	<table><tr><th>Ave</th><th>Lumens</th></tr><tr><td>0</td><td>334</td></tr><tr><td>5</td><td>333</td></tr><tr><td>15</td><td>321</td></tr><tr><td>25</td><td>295</td></tr><tr><td>35</td><td>258</td></tr><tr><td>45</td><td>212</td></tr><tr><td>55</td><td>163</td></tr><tr><td>65</td><td>112</td></tr><tr><td>75</td><td>63</td></tr><tr><td>85</td><td>18</td></tr><tr><td>90</td><td>0</td></tr></table>		Ave	Lumens	0	334	5	333	15	321	25	295	35	258	45	212	55	163	65	112	75	63	85	18	90	0	<table><tr><th>Zone</th><th>Lumens</th><th>% Lamp</th></tr><tr><td>0° - 30°</td><td>257.8</td><td>27.8</td></tr><tr><td>0° - 40°</td><td>418.8</td><td>45.2</td></tr><tr><td>0° - 60°</td><td>728.2</td><td>78.7</td></tr><tr><td>0° - 90°</td><td>925.8</td><td>100.0</td></tr><tr><td>90° - 120°</td><td>0.0</td><td>0.0</td></tr><tr><td>90° - 130°</td><td>0.0</td><td>0.0</td></tr><tr><td>90° - 150°</td><td>0.0</td><td>0.0</td></tr><tr><td>90° - 180°</td><td>0.0</td><td>0.0</td></tr><tr><td>0° - 180°</td><td>925.8</td><td>*100.0</td></tr><tr><td colspan="3">*Efficiency</td></tr></table>		Zone	Lumens	% Lamp	0° - 30°	257.8	27.8	0° - 40°	418.8	45.2	0° - 60°	728.2	78.7	0° - 90°	925.8	100.0	90° - 120°	0.0	0.0	90° - 130°	0.0	0.0	90° - 150°	0.0	0.0	90° - 180°	0.0	0.0	0° - 180°	925.8	*100.0	*Efficiency			<table><tr><th>pf</th><th colspan="3">80%</th><th colspan="3">20%</th><th colspan="3">50%</th></tr><tr><th>pc</th><th>50%</th><th>30%</th><th>10%</th><th>50%</th><th>30%</th><th>10%</th><th>50%</th><th>30%</th><th>10%</th></tr><tr><th>pw</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>0</td><td>119</td><td>119</td><td>119</td><td>116</td><td>116</td><td>116</td><td>111</td><td>111</td><td>111</td></tr><tr><td>1</td><td>104</td><td>99</td><td>96</td><td>101</td><td>98</td><td>94</td><td>97</td><td>94</td><td>91</td></tr><tr><td>2</td><td>90</td><td>84</td><td>78</td><td>88</td><td>82</td><td>77</td><td>85</td><td>80</td><td>75</td></tr><tr><td>3</td><td>79</td><td>71</td><td>65</td><td>78</td><td>70</td><td>64</td><td>75</td><td>68</td><td>63</td></tr><tr><td>4</td><td>70</td><td>62</td><td>55</td><td>69</td><td>61</td><td>54</td><td>67</td><td>59</td><td>54</td></tr><tr><td>5</td><td>63</td><td>54</td><td>47</td><td>62</td><td>53</td><td>47</td><td>60</td><td>52</td><td>46</td></tr><tr><td>6</td><td>57</td><td>48</td><td>41</td><td>56</td><td>47</td><td>41</td><td>54</td><td>46</td><td>41</td></tr><tr><td>7</td><td>51</td><td>43</td><td>36</td><td>51</td><td>42</td><td>36</td><td>49</td><td>42</td><td>36</td></tr><tr><td>8</td><td>47</td><td>38</td><td>33</td><td>46</td><td>38</td><td>32</td><td>45</td><td>38</td><td>32</td></tr><tr><td>9</td><td>43</td><td>35</td><td>29</td><td>43</td><td>35</td><td>29</td><td>41</td><td>34</td><td>29</td></tr><tr><td>10</td><td>40</td><td>32</td><td>27</td><td>39</td><td>32</td><td>27</td><td>38</td><td>31</td><td>26</td></tr></table>										pf	80%			20%			50%			pc	50%	30%	10%	50%	30%	10%	50%	30%	10%	pw										0	119	119	119	116	116	116	111	111	111	1	104	99	96	101	98	94	97	94	91	2	90	84	78	88	82	77	85	80	75	3	79	71	65	78	70	64	75	68	63	4	70	62	55	69	61	54	67	59	54	5	63	54	47	62	53	47	60	52	46	6	57	48	41	56	47	41	54	46	41	7	51	43	36	51	42	36	49	42	36	8	47	38	33	46	38	32	45	38	32	9	43	35	29	43	35	29	41	34	29	10	40	32	27	39	32	27	38	31	26	<table><tr><th colspan="2">50° beam - 63.5°</th><th colspan="2">10° beam - 108.5°</th></tr><tr><th>Mounting Height</th><th>Initial FC Center Beam</th><th>Diameter</th><th>FC</th><th>Diameter</th><th>FC</th></tr><tr><td>8.0</td><td>11.0</td><td>6.8</td><td>5.5</td><td>15.3</td><td>1.1</td></tr><tr><td>10.0</td><td>5.9</td><td>9.3</td><td>3.0</td><td>20.8</td><td>0.6</td></tr><tr><td>12.0</td><td>3.7</td><td>11.7</td><td>1.8</td><td>26.4</td><td>0.4</td></tr><tr><td>14.0</td><td>2.5</td><td>14.2</td><td>1.3</td><td>31.9</td><td>0.3</td></tr><tr><td>16.0</td><td>1.8</td><td>16.7</td><td>0.9</td><td>37.5</td><td>0.2</td></tr></table>				50° beam - 63.5°		10° beam - 108.5°		Mounting Height	Initial FC Center Beam	Diameter	FC	Diameter	FC	8.0	11.0	6.8	5.5	15.3	1.1	10.0	5.9	9.3	3.0	20.8	0.6	12.0	3.7	11.7	1.8	26.4	0.4	14.0	2.5	14.2	1.3	31.9	0.3	16.0	1.8	16.7	0.9	37.5	0.2
	Ave	Lumens																																																																																																																																																																																																																																																													
	0	334																																																																																																																																																																																																																																																													
	5	333																																																																																																																																																																																																																																																													
	15	321																																																																																																																																																																																																																																																													
	25	295																																																																																																																																																																																																																																																													
	35	258																																																																																																																																																																																																																																																													
	45	212																																																																																																																																																																																																																																																													
	55	163																																																																																																																																																																																																																																																													
	65	112																																																																																																																																																																																																																																																													
	75	63																																																																																																																																																																																																																																																													
	85	18																																																																																																																																																																																																																																																													
90	0																																																																																																																																																																																																																																																														
Zone	Lumens	% Lamp																																																																																																																																																																																																																																																													
0° - 30°	257.8	27.8																																																																																																																																																																																																																																																													
0° - 40°	418.8	45.2																																																																																																																																																																																																																																																													
0° - 60°	728.2	78.7																																																																																																																																																																																																																																																													
0° - 90°	925.8	100.0																																																																																																																																																																																																																																																													
90° - 120°	0.0	0.0																																																																																																																																																																																																																																																													
90° - 130°	0.0	0.0																																																																																																																																																																																																																																																													
90° - 150°	0.0	0.0																																																																																																																																																																																																																																																													
90° - 180°	0.0	0.0																																																																																																																																																																																																																																																													
0° - 180°	925.8	*100.0																																																																																																																																																																																																																																																													
*Efficiency																																																																																																																																																																																																																																																															
pf	80%			20%			50%																																																																																																																																																																																																																																																								
pc	50%	30%	10%	50%	30%	10%	50%	30%	10%																																																																																																																																																																																																																																																						
pw																																																																																																																																																																																																																																																															
0	119	119	119	116	116	116	111	111	111																																																																																																																																																																																																																																																						
1	104	99	96	101	98	94	97	94	91																																																																																																																																																																																																																																																						
2	90	84	78	88	82	77	85	80	75																																																																																																																																																																																																																																																						
3	79	71	65	78	70	64	75	68	63																																																																																																																																																																																																																																																						
4	70	62	55	69	61	54	67	59	54																																																																																																																																																																																																																																																						
5	63	54	47	62	53	47	60	52	46																																																																																																																																																																																																																																																						
6	57	48	41	56	47	41	54	46	41																																																																																																																																																																																																																																																						
7	51	43	36	51	42	36	49	42	36																																																																																																																																																																																																																																																						
8	47	38	33	46	38	32	45	38	32																																																																																																																																																																																																																																																						
9	43	35	29	43	35	29	41	34	29																																																																																																																																																																																																																																																						
10	40	32	27	39	32	27	38	31	26																																																																																																																																																																																																																																																						
50° beam - 63.5°		10° beam - 108.5°																																																																																																																																																																																																																																																													
Mounting Height	Initial FC Center Beam	Diameter	FC	Diameter	FC																																																																																																																																																																																																																																																										
8.0	11.0	6.8	5.5	15.3	1.1																																																																																																																																																																																																																																																										
10.0	5.9	9.3	3.0	20.8	0.6																																																																																																																																																																																																																																																										
12.0	3.7	11.7	1.8	26.4	0.4																																																																																																																																																																																																																																																										
14.0	2.5	14.2	1.3	31.9	0.3																																																																																																																																																																																																																																																										
16.0	1.8	16.7	0.9	37.5	0.2																																																																																																																																																																																																																																																										

WF6 LL LED 27K30K35K, 3500K LEDs, input watts: 9.9, delivered lumens: 893, LM/W=90, test no. ISF 36826P15

	<table><tr><th>Ave</th><th>Lumens</th></tr><tr><td>0</td><td>322</td></tr><tr><td>5</td><td>321</td></tr><tr><td>15</td><td>309</td></tr><tr><td>25</td><td>284</td></tr><tr><td>35</td><td>249</td></tr><tr><td>45</td><td>205</td></tr><tr><td>55</td><td>157</td></tr><tr><td>65</td><td>108</td></tr><tr><td>75</td><td>61</td></tr><tr><td>85</td><td>17</td></tr><tr><td>90</td><td>0</td></tr></table>	Ave	Lumens	0	322	5	321	15	309	25	284	35	249	45	205	55	157	65	108	75	61	85	17	90	0	<table><tr><th>Zone</th><th>Lumens</th><th>% Lamp</th></tr><tr><td>0° - 30°</td><td>248.5</td><td>27.8</td></tr><tr><td>0° - 40°</td><td>403.7</td><td>45.2</td></tr><tr><td>0° - 60°</td><td>701.9</td><td>78.7</td></tr><tr><td>0° - 90°</td><td>892.3</td><td>100.0</td></tr><tr><td>90° - 120°</td><td>0.0</td><td>0.0</td></tr><tr><td>90° - 130°</td><td>0.0</td><td>0.0</td></tr><tr><td>90° - 150°</td><td>0.0</td><td>0.0</td></tr><tr><td>90° - 180°</td><td>0.0</td><td>0.0</td></tr><tr><td>0° - 180°</td><td>892.3</td><td>*100.0</td></tr><tr><td colspan="3">*Efficiency</td></tr></table>	Zone	Lumens	% Lamp	0° - 30°	248.5	27.8	0° - 40°	403.7	45.2	0° - 60°	701.9	78.7	0° - 90°	892.3	100.0	90° - 120°	0.0	0.0	90° - 130°	0.0	0.0	90° - 150°	0.0	0.0	90° - 180°	0.0	0.0	0° - 180°	892.3	*100.0	*Efficiency			<table><tr><th>pf</th><th colspan="3">80%</th><th colspan="3">20%</th><th colspan="3">50%</th></tr><tr><th>pc</th><th>50%</th><th>30%</th><th>10%</th><th>50%</th><th>30%</th><th>10%</th><th>50%</th><th>30%</th><th>10%</th></tr><tr><th>pw</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>0</td><td>119</td><td>119</td><td>119</td><td>116</td><td>116</td><td>116</td><td>111</td><td>111</td><td>111</td></tr><tr><td>1</td><td>104</td><td>99</td><td>96</td><td>101</td><td>98</td><td>94</td><td>97</td><td>94</td><td>91</td></tr><tr><td>2</td><td>90</td><td>84</td><td>78</td><td>88</td><td>82</td><td>77</td><td>85</td><td>80</td><td>75</td></tr><tr><td>3</td><td>79</td><td>71</td><td>65</td><td>78</td><td>70</td><td>64</td><td>75</td><td>68</td><td>63</td></tr><tr><td>4</td><td>70</td><td>62</td><td>55</td><td>69</td><td>61</td><td>54</td><td>67</td><td>59</td><td>54</td></tr><tr><td>5</td><td>63</td><td>54</td><td>47</td><td>62</td><td>53</td><td>47</td><td>60</td><td>52</td><td>46</td></tr><tr><td>6</td><td>57</td><td>48</td><td>41</td><td>56</td><td>47</td><td>41</td><td>54</td><td>46</td><td>41</td></tr><tr><td>7</td><td>51</td><td>43</td><td>36</td><td>51</td><td>42</td><td>36</td><td>49</td><td>42</td><td>36</td></tr><tr><td>8</td><td>47</td><td>38</td><td>33</td><td>46</td><td>38</td><td>32</td><td>45</td><td>38</td><td>32</td></tr><tr><td>9</td><td>43</td><td>35</td><td>29</td><td>43</td><td>35</td><td>29</td><td>41</td><td>34</td><td>29</td></tr><tr><td>10</td><td>40</td><td>32</td><td>27</td><td>39</td><td>32</td><td>27</td><td>38</td><td>31</td><td>26</td></tr></table>	pf	80%			20%			50%			pc	50%	30%	10%	50%	30%	10%	50%	30%	10%	pw										0	119	119	119	116	116	116	111	111	111	1	104	99	96	101	98	94	97	94	91	2	90	84	78	88	82	77	85	80	75	3	79	71	65	78	70	64	75	68	63	4	70	62	55	69	61	54	67	59	54	5	63	54	47	62	53	47	60	52	46	6	57	48	41	56	47	41	54	46	41	7	51	43	36	51	42	36	49	42	36	8	47	38	33	46	38	32	45	38	32	9	43	35	29	43	35	29	41	34	29	10	40	32	27	39	32	27	38	31	26	<table><tr><th colspan="2">Mounting Height</th><th colspan="2">Initial FC Center Beam</th><th colspan="2">50° beam - 63.5° Diameter FC</th><th colspan="2">10° beam - 108.5° Diameter FC</th></tr><tr><th>8.0</th><th>10.6</th><th>6.8</th><th>5.3</th><th>15.3</th><th>1.1</th><th></th><th></th></tr><tr><td>10.0</td><td>5.7</td><td>9.3</td><td>2.9</td><td>20.8</td><td>0.6</td><td></td><td></td></tr><tr><td>12.0</td><td>3.6</td><td>11.7</td><td>1.8</td><td>26.4</td><td>0.4</td><td></td><td></td></tr><tr><td>14.0</td><td>2.4</td><td>14.2</td><td>1.2</td><td>31.9</td><td>0.2</td><td></td><td></td></tr><tr><td>16.0</td><td>1.8</td><td>16.7</td><td>0.9</td><td>37.5</td><td>0.2</td><td></td><td></td></tr></table>	Mounting Height		Initial FC Center Beam		50° beam - 63.5° Diameter FC		10° beam - 108.5° Diameter FC		8.0	10.6	6.8	5.3	15.3	1.1			10.0	5.7	9.3	2.9	20.8	0.6			12.0	3.6	11.7	1.8	26.4	0.4			14.0	2.4	14.2	1.2	31.9	0.2			16.0	1.8	16.7	0.9	37.5	0.2		
	Ave	Lumens																																																																																																																																																																																																																																																							
	0	322																																																																																																																																																																																																																																																							
	5	321																																																																																																																																																																																																																																																							
	15	309																																																																																																																																																																																																																																																							
	25	284																																																																																																																																																																																																																																																							
	35	249																																																																																																																																																																																																																																																							
	45	205																																																																																																																																																																																																																																																							
	55	157																																																																																																																																																																																																																																																							
	65	108																																																																																																																																																																																																																																																							
75	61																																																																																																																																																																																																																																																								
85	17																																																																																																																																																																																																																																																								
90	0																																																																																																																																																																																																																																																								
Zone	Lumens	% Lamp																																																																																																																																																																																																																																																							
0° - 30°	248.5	27.8																																																																																																																																																																																																																																																							
0° - 40°	403.7	45.2																																																																																																																																																																																																																																																							
0° - 60°	701.9	78.7																																																																																																																																																																																																																																																							
0° - 90°	892.3	100.0																																																																																																																																																																																																																																																							
90° - 120°	0.0	0.0																																																																																																																																																																																																																																																							
90° - 130°	0.0	0.0																																																																																																																																																																																																																																																							
90° - 150°	0.0	0.0																																																																																																																																																																																																																																																							
90° - 180°	0.0	0.0																																																																																																																																																																																																																																																							
0° - 180°	892.3	*100.0																																																																																																																																																																																																																																																							
*Efficiency																																																																																																																																																																																																																																																									
pf	80%			20%			50%																																																																																																																																																																																																																																																		
pc	50%	30%	10%	50%	30%	10%	50%	30%	10%																																																																																																																																																																																																																																																
pw																																																																																																																																																																																																																																																									
0	119	119	119	116	116	116	111	111	111																																																																																																																																																																																																																																																
1	104	99	96	101	98	94	97	94	91																																																																																																																																																																																																																																																
2	90	84	78	88	82	77	85	80	75																																																																																																																																																																																																																																																
3	79	71	65	78	70	64	75	68	63																																																																																																																																																																																																																																																
4	70	62	55	69	61	54	67	59	54																																																																																																																																																																																																																																																
5	63	54	47	62	53	47	60	52	46																																																																																																																																																																																																																																																
6	57	48	41	56	47	41	54	46	41																																																																																																																																																																																																																																																
7	51	43	36	51	42	36	49	42	36																																																																																																																																																																																																																																																
8	47	38	33	46	38	32	45	38	32																																																																																																																																																																																																																																																
9	43	35	29	43	35	29	41	34	29																																																																																																																																																																																																																																																
10	40	32	27	39	32	27	38	31	26																																																																																																																																																																																																																																																
Mounting Height		Initial FC Center Beam		50° beam - 63.5° Diameter FC		10° beam - 108.5° Diameter FC																																																																																																																																																																																																																																																			
8.0	10.6	6.8	5.3	15.3	1.1																																																																																																																																																																																																																																																				
10.0	5.7	9.3	2.9	20.8	0.6																																																																																																																																																																																																																																																				
12.0	3.6	11.7	1.8	26.4	0.4																																																																																																																																																																																																																																																				
14.0	2.4	14.2	1.2	31.9	0.2																																																																																																																																																																																																																																																				
16.0	1.8	16.7	0.9	37.5	0.2																																																																																																																																																																																																																																																				

WF6 Switchable White 6" LED Wafer Module

PHOTOMETRICS

Distribution Curve	Distribution Data	Output Data	Coefficient of Utilization	Illuminance Data at 30" Above Floor for a Single Luminaire																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								</

WF6 LL LED 30K40K50K, 4000K LEDs, input watts: 10, delivered lumens: 923, LM/W=92, test no. ISF 36826P17

Ave	Lumens	Zone	Lumens	% Lamp	pf	pc	pw	80%			20%			50%		
0	333	0° - 30°	257.0	27.8	0	119	119	119	116	116	116	111	111	111		
5	332	0° - 40°	417.5	45.2	1	104	99	96	101	98	94	97	94	91		
15	320	0° - 60°	725.9	78.7	2	90	84	78	88	82	77	85	80	75		
25	294	0° - 90°	922.9	100.0	3	79	71	65	78	70	64	75	68	63		
35	257	90° - 120°	0.0	0.0	4	70	62	55	69	61	54	67	59	54		
45	212	90° - 130°	0.0	0.0	5	63	54	47	62	53	47	60	52	46		
55	163	90° - 150°	0.0	0.0	6	57	48	41	56	47	41	54	46	41		
65	112	90° - 180°	0.0	0.0	7	51	43	36	51	42	36	49	42	36		
75	63	0° - 180°	922.9	*100.0	8	47	38	33	46	38	32	45	38	32		
85	18	*Efficiency			9	43	35	29	43	35	29	41	34	29		
90	0				10	40	32	27	39	32	27	38	31	26		

50% beam - 63.5°

10% beam - 108.5°

Mounting Height	Initial FC Center Beam	Diameter	FC	Diameter	FC
8.0	11.0	6.8	5.5	15.3	1.1
10.0	5.9	9.3	3.0	20.8	0.6
12.0	3.7	11.7	1.8	26.4	0.4
14.0	2.5	14.2	1.3	31.9	0.3
16.0	1.8	16.7	0.9	37.5	0.2

WF6 LL LED 30K40K50K, 5000K LEDs, input watts: 10, delivered lumens: 886, LM/W=87, test no. ISF 36826P18

	<table><tr><th>Ave</th><th>Lumens</th></tr><tr><td>0</td><td>319</td></tr><tr><td>5</td><td>319</td></tr><tr><td>15</td><td>307</td></tr><tr><td>25</td><td>282</td></tr><tr><td>35</td><td>247</td></tr><tr><td>45</td><td>203</td></tr><tr><td>55</td><td>156</td></tr><tr><td>65</td><td>107</td></tr><tr><td>75</td><td>64</td></tr><tr><td>85</td><td>17</td></tr><tr><td>90</td><td>0</td></tr></table>		Ave	Lumens	0	319	5	319	15	307	25	282	35	247	45	203	55	156	65	107	75	64	85	17	90	0	<table><tr><th>Zone</th><th>Lumens</th><th>% Lamp</th></tr><tr><td>0° - 30°</td><td>246.8</td><td>27.8</td></tr><tr><td>0° - 40°</td><td>400.9</td><td>45.2</td></tr><tr><td>0° - 60°</td><td>697.1</td><td>78.7</td></tr><tr><td>0° - 90°</td><td>886.2</td><td>100.0</td></tr><tr><td>90° - 120°</td><td>0.0</td><td>0.0</td></tr><tr><td>90° - 130°</td><td>0.0</td><td>0.0</td></tr><tr><td>90° - 150°</td><td>0.0</td><td>0.0</td></tr><tr><td>90° - 180°</td><td>0.0</td><td>0.0</td></tr><tr><td>0° - 180°</td><td>886.2</td><td>*100.0</td></tr><tr><td colspan="3">*Efficiency</td></tr></table>		Zone	Lumens	% Lamp	0° - 30°	246.8	27.8	0° - 40°	400.9	45.2	0° - 60°	697.1	78.7	0° - 90°	886.2	100.0	90° - 120°	0.0	0.0	90° - 130°	0.0	0.0	90° - 150°	0.0	0.0	90° - 180°	0.0	0.0	0° - 180°	886.2	*100.0	*Efficiency			<table><tr><th>pf</th><th colspan="3">80%</th><th colspan="3">20%</th><th colspan="3">50%</th></tr><tr><th>pc</th><th>50%</th><th>30%</th><th>10%</th><th>50%</th><th>30%</th><th>10%</th><th>50%</th><th>30%</th><th>10%</th></tr><tr><th>pw</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>0</td><td>119</td><td>119</td><td>119</td><td>116</td><td>116</td><td>116</td><td>111</td><td>111</td><td>111</td></tr><tr><td>1</td><td>104</td><td>99</td><td>96</td><td>101</td><td>98</td><td>94</td><td>97</td><td>94</td><td>91</td></tr><tr><td>2</td><td>90</td><td>84</td><td>78</td><td>88</td><td>82</td><td>77</td><td>85</td><td>80</td><td>75</td></tr><tr><td>3</td><td>79</td><td>71</td><td>65</td><td>78</td><td>70</td><td>64</td><td>75</td><td>68</td><td>63</td></tr><tr><td>4</td><td>70</td><td>62</td><td>55</td><td>69</td><td>61</td><td>54</td><td>67</td><td>59</td><td>54</td></tr><tr><td>5</td><td>63</td><td>54</td><td>47</td><td>62</td><td>53</td><td>47</td><td>60</td><td>52</td><td>46</td></tr><tr><td>6</td><td>57</td><td>48</td><td>41</td><td>56</td><td>47</td><td>41</td><td>54</td><td>46</td><td>41</td></tr><tr><td>7</td><td>51</td><td>43</td><td>36</td><td>51</td><td>42</td><td>36</td><td>49</td><td>42</td><td>36</td></tr><tr><td>8</td><td>47</td><td>38</td><td>33</td><td>46</td><td>38</td><td>32</td><td>45</td><td>38</td><td>32</td></tr><tr><td>9</td><td>43</td><td>35</td><td>29</td><td>43</td><td>35</td><td>29</td><td>41</td><td>34</td><td>29</td></tr><tr><td>10</td><td>40</td><td>32</td><td>27</td><td>39</td><td>32</td><td>27</td><td>38</td><td>31</td><td>26</td></tr></table>										pf	80%			20%			50%			pc	50%	30%	10%	50%	30%	10%	50%	30%	10%	pw										0	119	119	119	116	116	116	111	111	111	1	104	99	96	101	98	94	97	94	91	2	90	84	78	88	82	77	85	80	75	3	79	71	65	78	70	64	75	68	63	4	70	62	55	69	61	54	67	59	54	5	63	54	47	62	53	47	60	52	46	6	57	48	41	56	47	41	54	46	41	7	51	43	36	51	42	36	49	42	36	8	47	38	33	46	38	32	45	38	32	9	43	35	29	43	35	29	41	34	29	10	40	32	27	39	32	27	38	31	26	50% beam - 63.5°				10% beam - 108.5°			
	Ave	Lumens																																																																																																																																																																																																																									
	0	319																																																																																																																																																																																																																									
	5	319																																																																																																																																																																																																																									
	15	307																																																																																																																																																																																																																									
	25	282																																																																																																																																																																																																																									
	35	247																																																																																																																																																																																																																									
	45	203																																																																																																																																																																																																																									
	55	156																																																																																																																																																																																																																									
	65	107																																																																																																																																																																																																																									
	75	64																																																																																																																																																																																																																									
	85	17																																																																																																																																																																																																																									
90	0																																																																																																																																																																																																																										
Zone	Lumens	% Lamp																																																																																																																																																																																																																									
0° - 30°	246.8	27.8																																																																																																																																																																																																																									
0° - 40°	400.9	45.2																																																																																																																																																																																																																									
0° - 60°	697.1	78.7																																																																																																																																																																																																																									
0° - 90°	886.2	100.0																																																																																																																																																																																																																									
90° - 120°	0.0	0.0																																																																																																																																																																																																																									
90° - 130°	0.0	0.0																																																																																																																																																																																																																									
90° - 150°	0.0	0.0																																																																																																																																																																																																																									
90° - 180°	0.0	0.0																																																																																																																																																																																																																									
0° - 180°	886.2	*100.0																																																																																																																																																																																																																									
*Efficiency																																																																																																																																																																																																																											
pf	80%			20%			50%																																																																																																																																																																																																																				
pc	50%	30%	10%	50%	30%	10%	50%	30%	10%																																																																																																																																																																																																																		
pw																																																																																																																																																																																																																											
0	119	119	119	116	116	116	111	111	111																																																																																																																																																																																																																		
1	104	99	96	101	98	94	97	94	91																																																																																																																																																																																																																		
2	90	84	78	88	82	77	85	80	75																																																																																																																																																																																																																		
3	79	71	65	78	70	64	75	68	63																																																																																																																																																																																																																		
4	70	62	55	69	61	54	67	59	54																																																																																																																																																																																																																		
5	63	54	47	62	53	47	60	52	46																																																																																																																																																																																																																		
6	57	48	41	56	47	41	54	46	41																																																																																																																																																																																																																		
7	51	43	36	51	42	36	49	42	36																																																																																																																																																																																																																		
8	47	38	33	46	38	32	45	38	32																																																																																																																																																																																																																		
9	43	35	29	43	35	29	41	34	29																																																																																																																																																																																																																		
10	40	32	27	39	32	27	38	31	26																																																																																																																																																																																																																		
Mounting Height				Initial FC																																																																																																																																																																																																																							
Center Beam				Diameter				FC																																																																																																																																																																																																																			
8.0				6.8				5.3																																																																																																																																																																																																																			
10.0				5.7				4.3																																																																																																																																																																																																																			
12.0				3.5				2.6																																																																																																																																																																																																																			
14.0				2.4				1.8																																																																																																																																																																																																																			
16.0				1.8				1.4																																																																																																																																																																																																																			

WF6 Switchable White 6" LED Wafer Module

ENERGY DATA

WF6 LED 27K30K35K			
Color Temperature	2700K	3000K	3500K
Lumens	1070	1150	1110
CRI	90	90	90
Rated wattage	14.1	13.4	13.9
Lu/Watts	75.9	85.8	79.9
Min. starting temp	-40°C (-40°F)	-40°C (-40°F)	-40°C (-40°F)
EMI/RFI	FCC Title 47 CFR, Part 15, Class B	FCC Title 47 CFR, Part 15, Class B	FCC Title 47 CFR, Part 15, Class B
Sound rating	Class A Standards	Class A Standards	Class A Standards
Input voltage	120V	120V	120V
Min. power factor	0.98	0.98	0.98
Input frequency	50/60 Hz	50/60 Hz	50/60 Hz
Input power	120V	120V	120V
Input current	0.12A	0.12A	0.12A

WF6 LL 27K30K35K			
Color Temperature	2700K	3000K	3500K
Lumens	830	900	860
CRI	90	90	90
Rated wattage	10	9.7	9.9
Lu/Watts	83.0	92.8	86.9
Min. starting temp	-40°C (-40°F)	-40°C (-40°F)	-40°C (-40°F)
EMI/RFI	FCC Title 47 CFR, Part 15, Class B	FCC Title 47 CFR, Part 15, Class B	FCC Title 47 CFR, Part 15, Class B
Sound rating	Class A Standards	Class A Standards	Class A Standards
Input voltage	120V	120V	120V
Min. power factor	0.98	0.98	0.98
Input frequency	50/60 Hz	50/60 Hz	50/60 Hz
Input power	120V	120V	120V
Input current	0.08A	0.08A	0.08A

WF6 LED 30K40K50K			
Color Temperature	3000K	4000K	5000K
Lumens	1090	1190	1120
CRI	90	90	90
Rated wattage	13.8	13.4	13.9
Lu/Watts	79.0	88.8	80.6
Min. starting temp	-40°C (-40°F)	-40°C (-40°F)	-40°C (-40°F)
EMI/RFI	FCC Title 47 CFR, Part 15, Class B	FCC Title 47 CFR, Part 15, Class B	FCC Title 47 CFR, Part 15, Class B
Sound rating	Class A Standards	Class A Standards	Class A Standards
Input voltage	120V	120V	120V
Min. power factor	0.98	0.98	0.98
Input frequency	50/60 Hz	50/60 Hz	50/60 Hz
Input power	120V	120V	120V
Input current	0.12A	0.12A	0.12A

WF6 LL 30K40K50K			
Color Temperature	3000K	4000K	5000K
Lumens	850	920	880
CRI	90	90	90
Rated wattage	9.9	9.8	10
Lu/Watts	85.9	93.9	88.0
Min. starting temp	-40°C (-40°F)	-40°C (-40°F)	-40°C (-40°F)
EMI/RFI	FCC Title 47 CFR, Part 15, Class B	FCC Title 47 CFR, Part 15, Class B	FCC Title 47 CFR, Part 15, Class B
Sound rating	Class A Standards	Class A Standards	Class A Standards
Input voltage	120V	120V	120V
Min. power factor	0.98	0.98	0.98
Input frequency	50/60 Hz	50/60 Hz	50/60 Hz
Input power	120V	120V	120V
Input current	0.08A	0.08A	0.08A

WF6 Switchable White 6" LED Wafer Module

LIGHTING PERFORMANCE DATA



LOW LUMEN

LIGHTING PERFORMANCE DATA DONNÉES SUR LE RENDEMENT DE L'ÉCLAIRAGE	
Light Appearance (CCT) Aspect de la lumière (CCT)	
2700K soft white blanc doux	
830 lumens 83 lumens per watt	
3000K warm white blanc chaud	
900 lumens 90 lumens per watt	
3500K neutral white blanc neutre	
860 lumens 86 lumens per watt	
Watts	10
Color Accuracy (CRI)	90
Précision des couleurs (CRI)	

LIGHTING PERFORMANCE DATA DONNÉES SUR LE RENDEMENT DE L'ÉCLAIRAGE	
Light Appearance (CCT) Aspect de la lumière (CCT)	
3000K warm white blanc chaud	
850 lumens 85 lumens per watt	
4000K cool white blanc froid	
920 lumens 92 lumens per watt	
5000K daylight blanc neutre	
880 lumens 88 lumens per watt	
Watts	10
Color Accuracy (CRI)	90
Précision des couleurs (CRI)	

HIGH LUMEN



LIGHTING PERFORMANCE DATA DONNÉES SUR LE RENDEMENT DE L'ÉCLAIRAGE	
Light Appearance (CCT) Aspect de la lumière (CCT)	
2700K soft white blanc doux	
1070 lumens 76 lumens per watt	
3000K warm white blanc chaud	
1150 lumens 82 lumens per watt	
3500K neutral white blanc neutre	
1110 lumens 79 lumens per watt	
Watts	14
Color Accuracy (CRI)	90
Précision des couleurs (CRI)	

LIGHTING PERFORMANCE DATA DONNÉES SUR LE RENDEMENT DE L'ÉCLAIRAGE	
Light Appearance (CCT) Aspect de la lumière (CCT)	
3000K warm white blanc chaud	
1090 lumens 78 lumens per watt	
4000K cool white blanc froid	
1190 lumens 85 lumens per watt	
5000K daylight blanc neutre	
1120 lumens 80 lumens per watt	
Watts	14
Color Accuracy (CRI)	90
Précision des couleurs (CRI)	